chanhvinh.com

OSRAM KB EELP41.12

Datasheet

Published by ams-OSRAM AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0
ams-osram.com
© All rights reserved


chanhvinh.com

OSRAM

SMARTLED® 0603

KB EELP41.12

The SMARTLED® 0603 is the product of choice for status indication any symbol backlighting in electronics.
The small package size allows compact designs. The improved corrosion robustness and increased junction temperature range makes the devices from this series suitable for professional industrial equipment and applications.



Applications

- Appliances & Tools
- Display Backlighting
- Factory Automation
- Home & Building Automation
- Projection & Display
- Static Signaling
- Transportation

Features

- Package: SMT package 0603, colorless diffused resin
- Chip technology: InGaN on Sapphire
- Typ. Radiation: 130° (horizontal = 0°), 145° (vertical = 90°)
- Color: λ_{dom} = 474 nm (● blue)
- Corrosion Robustness Class: 3B
- ESD: 8 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)

chanhvinh.com

Ordering Information

Type	Luminous Intensity [1] I_F = 5 mA I_v	Ordering Code
KB EELP41.12-P1R2-36-3X4X	≥ 45.0 mcd	Q65113A7464

chanhvinh.com

Maximum Ratings

Parameter	Symbol		Values
Operating Temperature	T_{op}	min. max.	-40 °C 105 °C
Storage Temperature	T_{stg}	min. max.	-40 °C 105 °C
Junction Temperature	T_j	max.	110 °C
Forward current T_S = 25 °C	I_F	min. max.	0.5 mA 25 mA
Forward Current pulsed D = 0.05 ; T_S = 25 °C	$I_{F\ pulse}$	max.	100 mA
Surge Current t ≤ 10 µs; D = 0.05 ; T_S = 25 °C	I_{FS}	max.	250 mA
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 3B)	V_{ESD}		8 kV
Reverse current [2)]	I_R	max.	20 mA

chanhvinh.com

Characteristics

I_F = 5 mA; T_S = 25 °C

Parameter	Symbol		Values
Peak Wavelength	λ_{peak}	typ.	470 nm
Dominant Wavelength [3]	λ_{dom}	min. typ. max.	464 nm 474 nm 480 nm
Spectral Bandwidth at 50% $I_{rel,max}$	$\Delta\lambda$	typ.	20 nm
Viewing angle at 50% I_V values for 0°, 90°	2φ	typ.	130 ° 145 °
Forward Voltage [4] I_F = 5 mA	V_F	min. typ. max.	2.60 V 2.75 V 3.00 V
Reverse voltage (ESD device)	$V_{R\ ESD}$	min.	7 V
Reverse voltage [2] I_R = 20 mA	V_R	max.	1.2 V
Real thermal resistance junction/solderpoint [5]	$R_{thJS\ real}$	typ. max.	410 K / W 490 K / W

chanhvinh.com

Brightness Groups

Group	Luminous Intensity [1] I_F = 5 mA min. I_v	Luminous Intensity. [1] I_F = 5 mA max. I_v	Luminous Flux [6] I_F = 5 mA typ. Φ_V
P1	45.0 mcd	56.0 mcd	197.0 mlm
P2	56.0 mcd	71.0 mcd	247.7 mlm
Q1	71.0 mcd	90.0 mcd	314.0 mlm
Q2	90.0 mcd	112.0 mcd	393.9 mlm
R1	112.0 mcd	140.0 mcd	491.4 mlm
R2	140.0 mcd	180.0 mcd	624.0 mlm

Forward Voltage Groups

Group	Forward Voltage [4] I_F = 5 mA min. V_F	Forward Voltage [4] I_F = 5 mA max. V_F
3X	2.60 V	2.70 V
3Y	2.70 V	2.80 V
3Z	2.80 V	2.90 V
4X	2.90 V	3.00 V

Wavelength Groups

Group	Dominant Wavelength [3] min. λ_{dom}	Dominant Wavelength [3] max. λ_{dom}
3	464 nm	468 nm
4	468 nm	472 nm
5	472 nm	476 nm
6	476 nm	480 nm

Group Name on Label


Example: P1-3-3X

Brightness	Wavelength	Forward Voltage
P1	3	3X

chanhvinh.com


Relative Spectral Emission [6]

$I_{rel} = f(\lambda)$; $I_F = 5$ mA; $T_S = 25$ °C



Radiation Characteristics [6]


$I_{rel} = f(\varphi)$; $T_S = 25$ °C



chanhvinh.com


Forward current 6)

$I_F = f(V_F)$; T_S = 25 °C




Relative Luminous Intensity 6), 7)

$I_v/I_v(5\ mA) = f(I_F)$; T_S = 25 °C



Dominant Wavelength 6)


$\Delta\lambda_{dom} = f(I_F)$; T_S = 25 °C



chanhvinh.com


Forward Voltage [6)]

$\Delta V_F = V_F - V_F(25\ °C) = f(T_j)$; $I_F = 5$ mA




Relative Luminous Intensity [6)]

$I_v/I_v(25\ °C) = f(T_j)$; $I_F = 5$ mA



Dominant Wavelength [6)]


$\Delta\lambda_{dom} = \lambda_{dom} - \lambda_{dom}(25\ °C) = f(T_j)$; $I_F = 5$ mA



chanhvinh.com


Max. Permissible Forward Current [5)]

$I_F = f(T)$




Permissible Pulse Handling Capability

$I_F = f(t_p)$; D: Duty cycle; T_S = 25 °C




Permissible Pulse Handling Capability

$I_F = f(t_p)$; D: Duty cycle; T_S = 85 °C



chanhvinh.com

Dimensional Drawing [8)]



general tolerance ±0.1

lead finish Au

C67062-A0484-A1-03

Further Information:


Approximate Weight: 1.3 mg

Corrosion test: Class: 3B
Test condition: 40°C / 90 % RH / 15 ppm H_2S / 14 days (stricter than IEC 60068-2-43)


ESD advice: The device is protected by ESD device which is connected in parallel to the Chip.

chanhvinh.com

Electrical Internal Circuit



Recommended Solder Pad [8)]




For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for ultra sonic cleaning.

chanhvinh.com

Reflow Soldering Profile

Product complies to MSL Level 2 acc. to JEDEC J-STD-020E




Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat*) 25 °C to 150 °C			2	3	K/s
Time t_S T_{Smin} to T_{Smax}	t_S	60	100	120	s
Ramp-up rate to peak*) T_{Smax} to T_P			2	3	K/s
Liquidus temperature	T_L		217		°C
Time above liquidus temperature	t_L		80	100	s
Peak temperature	T_P		245	260	°C
Time within 5 °C of the specified peak temperature T_P - 5 K	t_P	10	20	30	s
Ramp-down rate* T_P to 100 °C			3	6	K/s
Time 25 °C to T_P				480	s

All temperatures refer to the center of the package, measured on the top of the component
* slope calculation DT/Dt: Dt max. 5 s; fulfillment for the whole T-range

chanhvinh.com


Taping [8)]



C67062-A0484-B1-01

chanhvinh.com

Tape and Reel [9)]




Leader: min. 400mm*
Trailer: min. 160mm*
*)Dimensions acc. to IEC 60286-3; EIA 481-E

Reel Dimensions

A	W	N_{min}	W_1	$W_{2\,max}$	Pieces per PU
180 mm	8 + 0.3 / - 0.1 mm	60 mm	8.4 + 2 mm	14.4 mm	4000


chanhvinh.com

Barcode-Product-Label (BPL)



OHA04563

Dry Packing Process and Materials [8)]




OHA00539

Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.

chanhvinh.com

Type Designation System



chanhvinh.com

Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **moderate risk (exposure time 0.25 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

Based on very short life cycle times in chip technology this component is subject to frequent adaption to the latest chip technology.

For further application related information please visit https://ams-osram.com/support/application-notes

chanhvinh.com

Disclaimer

Attention please!

The information describes the type of component and shall not be considered as assured characteristics.
Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.
For information on the types in question please contact our Sales Organization.
If printed or downloaded, please find the latest version on our website.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.
Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/ applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

chanhvinh.com

Glossary

1) **Brightness:** Brightness groups are tested at a current pulse duration of 25 ms and a tolerance of ±11 %.

2) **Reverse Operation:** This product is intended to be operated applying a forward current within the specified range. Applying any continuous reverse bias or forward bias below the voltage range of light emission shall be avoided because it may cause migration which can change the electro-optical characteristics or damage the LED.

3) **Wavelength:** Wavelengths are tested at a current pulse duration of 25 ms and a tolerance of ±1 nm.

4) **Forward Voltage:** Forward voltages are tested at a current pulse duration of 1 ms and a tolerance of ±0.1 V.

5) **Thermal Resistance:** Rth max is based on statistic values (6σ) used for Derating.

6) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.

7) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.

8) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with ±0.1 and dimensions are specified in mm.

9) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

chanhvinh.com

Revision History

Version	Date	Change
1.0	2024-03-25	Initial Version

chanhvinh.com

EU RoHS and China RoHS compliant product
此产品符合欧盟 RoHS 指令的要求；
按照中国的相关法规和标准，
不含有毒有害物质或元素。

Published by ams-OSRAM AG
Tobelbader Strasse 30, 8141 Premstaetten, Austria
Phone +43 3136 500-0
ams-osram.com
© All rights reserved