
chanhvinh.com

Inductive sensors NAMUR

IFRM 08X9103

dimension drawing



general data

mounting type	unshielded
nominal sensing distance Sn	2 mm
Approvals/certificates	ATEX

electrical data

switching frequency	< 5 kHz
normal operating voltage	8,2 VDC
voltage supply range +Vs	5 ... 30 VDC
current consumption undamped	> 4 mA
current consumption damped	< 1 mA
current consumption max.	10 mA
output circuit	NAMUR
residual ripple	< 10 % Vs

mechanical data

type	cylindrical threaded
housing material	brass nickel plated
dimension	8 mm
housing length	27 mm
connection types	cable, 2 m

ambient conditions

operating temperature	-25 ... +75 °C
protection class	IP 67


safe maximum values

EC-type-examination Certificate	PTB 03 ATEX 2146
marking	II 1G Ex ia IIC T5/6
current Ii	< 37 mA
voltage Ui	< 13,5 VDC
power Pi	< 0,125 W
internal capacitance Ci	< 50 nF
internal inductance Li	< 0,2 mH
operating temperature Ta (temp. class T5)	-25 ... +60 °C
operating temperature Ta (temp. class T6)	-25 ... +40 °C

photo



connection diagram



- connector base version /S35