chanhvinh.com





# AVB 2,3/2/24*

## Short circuit proof PCB transformer

- **Maximum power from minimum size**
- **Vacuum resin moulded (self extinguishing to UL 94 V-0)**

Short circuit proof safety isolating transformer to IEC 61558-2-6, DIN EN 61558-2-6, VDE 0570 part 2-6

*Transformer to IEC 61558-2-1, DIN EN 61558-2-1, VDE 0570 part 2-1 (without VDE-Approval)

Errors and omissions excepted. Please note that product illustrations do not resemple all product variants.

chanhvinh.com





# AVB 2,3/2/24*

**Short circuit proof PCB transformer**

| | |
|---|---|
| **Input data** | |
| Input voltage | 2x115 V |
| Frequency range | 50 - 60 Hz |
| No-load loss (typ.) | 0.6 W |
| **Output data** | |
| Output voltage | 2x24 V |
| No-load voltage (ca. x factor) | 1.43 |
| Efficiency | 59 % |
| Power | 2.30 VA |
| **Standards and security** | |
| Approvals | C-UL-US, ENEC 10 (VDE) |
| Protection index | IP 00 |
| Safety class (prepared) | I |
| Ambient temperature max. | 70 °C |
| Class of Insulation System | VDE=E, UL=105 |
| Test voltage | 5000 V, 50 Hz |
| **Mechanical data** | |
| Type | encapsulated |
| Core type | EI 30/18 |
| Terminals | Pins for printed circuit boards |
| Pin (ø) | 0,8 |
| Wide | 27.3 mm |
| Height | 29 mm |
| Depth | 32.3 mm |
| Weight | 0.11 kg |
| **Order numbers** | |
| Order Number | AVB 2,3/2/24* |

Errors and omissions excepted. Please note that product illustrations do not resemple all product variants.

**BLOCK** Transformatoren-Elektronik GmbH
Max-Planck-Straße 36-46
27283 Verden
Germany
Phone +49 4231 678-0
Fax +49 4231 678-177