chanhvinh.com

Mains transformer
VB 2,3/2/24



Picture shows VB 2,0/2/6

Advantages

- Minimum size at high output
- Inherently short-circuit proof
- Also with dual output voltage for series or parallel connection
- Designed for high ambient temperatures
- Permanent corrosion protection, high insulation value and maximum electrical reliability thanks to XtraDenseFill resin encapsulation
- Self-extinguishing potting material

Applications

As a mains transformer for adjustment of the voltage and simple electrical isolation.

As a safety isolating transformer for the safe electrical isolation of the input and output sides. The transformer is suitable for creating SELV and PELV circuits because of the limit on the output voltage.

Sample application



Standards

Mains transformer
to: VDE 0570 Teil 2-1, DIN EN 61558-2-1, EN 61558-2-1, IEC 61558-2-1, UL 5085-1/-2, CSA 22.2 No.66

Approvals

UL 5085-1/-2, CSA 22.2 No.66

chanhvinh.com



Mains transformer
VB 2,3/2/24

Electrical data

Type	VB 2,3/2/24
Input	
Rated input voltage	230 Vac
Rated frequency	50 - 60 Hz
Output	
Rated output voltage	2 x 24 Vac
Rated Power	2.3 VA
No-load voltage (app. x factor)	1.60
No-load loss (typ.)	1.20 W
Efficiency	52.0 %
Standards	
Classification	Mains transformer
Approvals	
Approvals	cURus, VDE
Environment	
Ambient temperature max.	70 °C
Safety and protection	
Type	Encapsulated
Insulation class	VDE=B, UL=class 130
Protection index	IP 00
Safety class (prepared)	II
Short circuit strength	inherently short-circuit proof
Order numbers	
Order Number	**VB 2,3/2/24**

Mechanical data

Type	VB 2,3/2/24
Terminal and mounting	
Terminals	Pins for printed circuit boards
Measures and weights	
Pin (ø)	0.8 mm
Core type	EI 30/18,0
Weight	0.11 kg



Subject to change.