chanhvinh.com




VC 16/1/9

PCB transformer

- **Maximum power from minimum size**
- **Vacuum resin moulded (self extinguishing to UL 94 V-0)**


Safety isolating transformer to IEC 61558-2-6, DIN EN 61558-2-6, VDE 0570 part 2-6

*Transformer to IEC 61558-2-1, DIN EN 61558-2-1, VDE 0570 part 2-1 (without VDE-Approval)




Dimensions in mm

Prinzipschaltbild



Errors and omissions excepted. Please note that product illustrations do not resemple all product variants.

chanhvinh.com



VC 16/1/9

PCB transformer

Input data	
Input voltage	230 V
Frequency range	50 - 60 Hz
No-load loss (typ.)	1.8 W
Output data	
Output voltage	9 V
No-load voltage (ca. x factor)	1.24
Efficiency	76 %
Power	16.0 VA
Standards and security	
Approvals	C-UL-US, ENEC 10 (VDE)
Short circuit strength	non-short-circuit proof
Protection index	IP 00
Safety class (prepared)	II
Ambient temperature max.	40 °C
Class of Insulation System	VDE=B, UL=105
Test voltage	5000 V, 50 Hz
Mechanical data	
Type	encapsulated
Core type	EI 54/18,8
Terminals	Pins for printed circuit boards
Pin (ø)	0.8 mm
Weight	0.42 kg
Order numbers	
Order Number	VC 16/1/9

Errors and omissions excepted. Please note that product illustrations do not resemple all product variants.

BLOCK Transformatoren-Elektronik GmbH
Max-Planck-Straße 36-46
27283 Verden
Germany
Phone +49 4231 678-0
Fax +49 4231 678-177