chanhvinh.com

ACPL-224/ACPL-244

AC Input, Multi-Channel Half-Pitch Phototransistor Optocoupler

Data Sheet

Description

The ACPL-224 is an AC-input dual-channel, half-pitch phototransistor optocoupler each of which contains two light-emitting diodes connected inversely parallel and optically coupled to two separate phototransistors. It is packaged in an 8-pin SO package.

Likewise, the ACPL-244 is an AC-input quad-channel, half-pitch phototransistor optocoupler each of which contains two light-emitting diodes connected inversely parallel and optically coupled to four separate phototransistors. It is packaged in a 16-pin SO package.

For both devices, the input-output isolation voltage is rated at 3750 V_{RMS}. Response time, t_r, is 2 µs typically, while minimum CTR is 20% at input current of ±1 mA.

Features

- Current transfer ratio
  (CTR: 20% (min) at I_F = ±1 mA, V_{CE} = 5V)
- High input-output isolation voltage
  (V_{ISO} = 3750 V_{RMS})
- Non-saturated response time
  (t_r: 2 µs (typ) at V_{CC} = 10V, I_C = 2 mA, R_L= 100Ω)
- SO package
- CMR 10 kV/µs (typical)
- Safety and regulatory approvals
  - cUL
  - IEC/EN/DIN EN 60747-5-5
- Options available:
  - CTR Rank 0 only

Applications

- I/O Interface for programmable controllers, computers
- Sequence controllers
- System appliances, measuring instruments
- Signal transmission between circuits of different potentials and impedances.

ACPL-224 Pin, ACPL 244 Pin





Pin 1, 3	Anode/ Cathode
Pin 2, 4	Cathode/ Anode
Pin 5, 7	Emitter
Pin 6, 8	Collector

Pin 1, 3, 5, 7	Anode/ Cathod
Pin 2, 4, 6, 8	Cathode/ Anode
Pin 9, 11, 13, 15	Emitter
Pin 10, 12, 14, 16	Collector

chanhvinh.com

Ordering Information

ACPL-2x4-xxxx is UL Recognized with 3750 V_{RMS} for 1 minute per UL1577 and Canadian Component Acceptance Notice #5.

Part Number	RoHS Compliant Option Rank 0, 20% < C R < 400%, I_F = ±1 mA, V_{CE} = 5V	Package	Number of Channels	Surface Mount	Tape and Reel	IEC/EN DIN EN 60747-5-5	Quantity
ACPL-224	-500E	SO-8	Dual	X	X		2000 pcs per reel
	-560E	SO-8	Dual	X	X	X	2000 pcs per reel
ACPL-244	-500E	SO-16	Quad	X	X		2000 pcs per reel
	-560E	SO-16	Quad	X	X	X	2000 pcs per reel

To order, choose a part number from the part number column and combine with the desired option from the option column to form an order entry.

Example 1:

ACPL-224-560E to order product of Dual Channel SO-8 Surface Mount package in Tape and Reel with IEC/EN/DIN EN 60747-5-5 Safety Approval, 20% < CTR < 400% and RoHS compliant.

Example 2:

ACPL-244-500E to order product of Quad Channel SO-16 Surface Mount package in Tape and Reel packaging with 20% < CTR < 400% and RoHS compliant.

Option data sheets are available. Contact your Broadcom sales representative or authorized distributor for information.

chanhvinh.com

Package Outline Drawings

ACPL-224 PACKAGE OUTLINE



DIMENSIONS IN MILLIMETERS [INCHES]

chanhvinh.com

ACPL-244 PACKAGE OUTLINE



DIMENSIONS IN MILLIMETERS[INCHES]

Solder Reflow Temperature Profile

Recommended reflow condition as per JEDEC Standard, J-STD-020 (latest revision). Non-Halide Flux should be used.

chanhvinh.com

Absolute Maximum Ratings

Parameter	Symbol	ACPL-224	ACPL-244	Unit	Note
Storage Temperature	T_S	–55~125		°C	
Operating Temperature	T_A	–55~110		°C	
Average Forward Current	$I_{F(AVG)}$	±50		mA	
Pulse Forward Current	I_{FSM}	±1		A	
Reverse Voltage	V_R	6		V	
LED Power Dissipation (1 channel)	P_I	65		mW	
Collector Current	I_C	50		mA	
Collector-Emitter Voltage	V_{CEO}	80		V	
Emitter-Collector Voltage	V_{ECO}	7		V	
Isolation Voltage (AC for 1 minute, R.H. 40%~60%)	V_{ISO}	3750		V_{RMS}	1 minute
Collector Power Dissipation (1 channel)	P_C	150	100	mW	
Total Power Dissipation	P_{TOT}	200	170	mW	
Lead Solder Temperature	260°C for 10 seconds				

chanhvinh.com

Electrical Specifications

Over recommended ambient temperature at 25°C unless otherwise specified.

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions	Note
Forward Voltage	V_F	—	1.2	1.4	V	I_F = ±20 mA	Figure 6
Reverse Current	I_R	—	—	10	µA	V_R = 5V	
Terminal Capacitance	C_t	—	30	—	pF	V = 0, f = 1 MHz	
Collector Dark Current	I_{CEO}	—	—	100	nA	V_{CE} = 48V, I_F = 0 mA	Figure 12
Collector-Emitter Breakdown Voltage	BV_{CEO}	80	—	—	V	I_C = 0.5 mA, I_F = 0 mA	
Emitter-Collector Breakdown Voltage	BV_{ECO}	7	—	—	V	I_E = 100 µA, I_F = 0 mA	
Current Transfer Ratio	CTR	20	—	400	%	I_F = ±1 mA, V_{CE} = 5V	CTR = (I_C / I_F) × 100%
Saturated CTR	CTR(sat)	—	60	—	%	I_F = ±1 mA, V_{CE} = 0.4V	
Collector-Emitter Saturation Voltage	$V_{CE(}$sat)	—	—	0.4	V	I_F = ±8 mA, I_C = 2.4 mA	Figure 14
Isolation Resistance	R_{iso}	5×10^{10}	1×10^{11}	—	Ω	DC500V, R.H. 40%~60%	
Floating Capacitance	C_F	—	0.6	1	pF	V = 0, f = 1 MHz	
Cut-off Frequency (–3dB)	F_C	—	80	—	kHz	V_{CC} = 5V, I_C = 2 mA, R_L = 100Ω	Figure 2, Figure 19
Response Time (Rise)	t_r	—	2	—	µs	V_{CC} = 10V, I_C = 2 mA, R_L = 100Ω	Figure 1
Response Time (Fall)	t_f	—	3	—	µs		
Turn-on Time	t_{on}	—	3	—	µs		
Turn-off Time	t_{off}	—	3	—	µs		
Turn-ON Time	t_{ON}	—	2	—	µs	V_{CC} = 5V, I_F = 16 mA, R_L 1.9 kΩ	Figure 1, Figure 17
Storage Time	T_S	—	25	—	µs		
Turn-OFF Time	t_{OFF}	—	40	—	µs		
Common Mode Rejection Voltage	CMR	—	10	—	kV/µs	T_A = 25°C, R_L = 470Ω, V_{CM} = 1.5kV(peak), I_F = 0 mA, V_{CC} = 9V, V_{np} = 100 mV	Figure 20

Figure 1 Switching Time Test Circuit



Figure 2 Frequency Response Test Circuit



chanhvinh.com

Figure 3 Forward Current vs. Ambient Temperature



Figure 4 Collector Power Dissipation vs. Ambient Temperature



Figure 5 Pulse Forward Current vs. Duty Cycle Ratio



Figure 6 Forward Current vs. Forward Voltage



Figure 7 Forward Voltage Temperature Coefficient vs. Forward Current



Figure 8 Pulse Forward Current vs. Pulse Forward Voltage



chanhvinh.com

Figure 9 Collector Current vs. Collector-Emitter Voltage



Figure 10 Collector Current vs. Small Collector-Emitter Voltage



Figure 11 Collector Current vs. Forward Current



Figure 12 Collector Dark Current vs. Ambient Temperature



Figure 13 Current Transfer Ratio vs. Forward Current



Figure 14 Collector-Emitter Saturation Voltage vs. Ambient Temperature



chanhvinh.com

Figure 15 Collector Current vs. Ambient Temperature



Figure 16 Switching Time vs. Load Resistance



Figure 17 Switching Time vs. Ambient Temperature



Figure 18 Collector-Emitter Saturation Voltage vs. Forward Current



Figure 19 Frequency Response



Figure 20 CMR Test Circuit



(High Voltage Pulse)



V_{cp} : Voltage that is generated by the displacement current in floating capacitance between primary and secondary sides.

chanhvinh.com

For product information and a complete list of distributors, please go to our web site: www.broadcom.com.

Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, and the A logo are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries and/or the EU.

Copyright © 2010–2017 by Broadcom. All Rights Reserved.

The term "Broadcom" refers to Broadcom Limited and/or its subsidiaries. For more information, please visit www.broadcom.com.

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design.

Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

AV02-0753EN – June 14, 2017

Lead (Pb) Free
RoHS 6 fully compliant
RoHS 6 fully compliant options available;
-xxxE denotes a lead-free product