chanhvinh.com

HDSP-Uxxx Series
HDSP-U1xx/U2xx/U3xx/U4xx/U5xx Series
8 mm (0.31 inch) Ultra Mini Seven Segment Displays

Data Sheet



Description

The 8 mm (0.31 inch) LED seven segment displays are Avago's most space-efficient character size. They are designed for viewing distances up to 3 metres (10 feet). The numeric devices feature a right hand decimal point. All devices are available as either common anode or common cathode.

Typical applications include appliances, temperature controllers, and digital panel meters.

Features

- Compact package
- 8 mm (0.31 inch) character height
- Choice of colors:
  - Wide range of colors
- Excellent appearance:
  - Evenly lighted segments
  - Mitered corners on segments
  - Gray/black surface gives optimum contrast
  - ±50° viewing angle
- Design flexibility:
  - Common anode or common cathode
  - Right hand decimal point
- Categorized for luminous intensity:
  - Yellow and Green also categorized for color
  - Use of like categories yields a uniform display
- High light output
- High peak current
- Excellent for long digit string multiplexing
- Intensity and color selection option

Devices

AlGaAs Red HDSP-	HER HDSP-	Orange HDSP-	Yellow HDSP-	Green HDSP-	Description	Circuit Diagram
U101	U201	U401	U301	U501	Common Anode, Right Hand Decimal, Gray Surface	A
U103	U203	U403	U303	U503	Common Cathode, Right Hand Decimal, Gray Surface	B
U111	U211	U411	U311	U511	Common Anode, Right Hand Decimal, Black Surface	A
U113	U213	U413	U313	U513	Common Cathode, Right Hand Decimal, Black Surface	B

chanhvinh.com

Part Numbering System

5082 - x xx x - x x x xx
HDSP - x xx x - x x x xx

Mechanical Options [1]
00: No mechanical option
36: Special dimensional tolerances

Color Bin Options [1,2]
0: No color bin limitation

Maximum Intensity Bin [1,2]
0: No maximum intensity bin limitation

Minimum Intensity Bin [1,2]
0: No minimum intensity bin limitation

Device Configuration/Color [1]
1: Common Anode
3: Common Cathode

Device Specific Configuration [1]
Refer to respective data sheet

Package [1]
U: 8 mm (0.31 inch) Ultra Mini Single Digit Seven Segment Display

Notes:
1. For codes not listed in the figure above, please refer to the respective data sheet or contact your nearest Avago representative for details.
2. Bin options refer to shippable bins for a part-number. Color and Intensity Bins are typically restricted to 1 bin per tube (exceptions may apply). Please refer to respective data sheet for specific bin limit information.

chanhvinh.com

Package Dimensions





NOTES:
1. ALL DIMENSIONS IN MILLIMETERS (INCHES).
2. ALL UNTOLERANCED DIMENSIONS ARE FOR REFERENCE ONLY.
3. FOR YELLOW AND GREEN SERIES PRODUCT ONLY.

Internal Circuit Diagram



PIN	FUNCTION	
	A	B
1	CATHODE a	ANODE a
2	CATHODE f	ANODE f
3	CATHODE g	ANODE g
4	CATHODE e	ANODE e
5	CATHODE d	ANODE d
6	CATHODE DP	CATHODE DP
7	ANODE DP	ANODE DP
8	CATHODE c	ANODE c
9	ANODE	CATHODE
10	CATHODE b	ANODE b

HDSP-UOXX circuit

chanhvinh.com

Absolute Maximum Ratings

Description	AlGaAs Red HDSP-U1xx Series	HER/Orange HDSP-U2xx/-4xx Series	Yellow HDSP-U3xx Series	Green HDSP-U5xx Series	Units
Average Power per Segment or DP	37	105	80	105	mW
Peak Forward Current per Segment or DP	45 [1]	90 [3]	60 [5]	90 [7]	mA
DC Forward Current per Segment or DP	15 [2]	30 [4]	20 [6]	30 [8]	mA
Operating Temperature Range	-20 to +90		-20 to +90		°C
Storage Temperature Range		-30 to +90			°C
Reverse Voltage* per Segment or DP		3.0			V
Wavesoldering Temperature for 3 Seconds (1.60 mm [0.063 in.] below body)		250			°C

* Reverse Voltage is for LED testing purpose and not recommended to be used as application condition.

Note:

1. See Figure 1 to establish pulsed conditions.
2. No derating over specified temperature range.
3. See Figure 5 to establish pulsed conditions.
4. Derate above 53° C at 0.45 mA/°C (see Figure 8).
5. See Figure 6 to establish pulsed conditions.
6. Derate above 81° C at 0.52 mA/°C (see Figure 8).
7. See Figure 7 to establish pulsed conditions.
8. Derate above 39° C at 0.37 mA/°C (see Figure 8).

Electrical/Optical Characteristics at $T_A = 25°$ C

AlGaAs Red

Device Series - HDSP-U1xx

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity/Segment (Digit Average) [1,2]	I_V	315	600		µcd	I_F = 1 mA
			3600			I_F = 5 mA
Forward Voltage/Segment or DP	V_F		1.6		V	I_F = 1 mA
			1.7			I_F = 5 mA
			1.8	2.2		I_F = 20 mA
Peak Wavelength	λ_{PEAK}		645		nm	
Dominant Wavelength [3]	λ_d		637		nm	
Reverse Voltage/Segment or DP [4]	V_R	3.0	15		V	I_R = 100 µA
Temperature Coefficient of V_F/Segment or DP	ΔV_F/°C		-2		mV/°C	
Thermal Resistance LED Juction-to-Pin	$R\theta_{J\text{-}PIN}$		255		°C/W/Seg	

High Efficiency Red

Device Series - HDSP-U2xx

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity/Segment (Digit Average) [1,2]	I_V	360	980		µcd	I_F = 5 mA
			5390			I_F = 20 mA
Forward Voltage/Segment or DP	V_F		2.0	2.5	V	I_F = 20 mA
Peak Wavelength	λ_{PEAK}		635		nm	
Dominant Wavelength [3]	λ_d		626		nm	
Reverse Voltage/Segment or DP [4]	V_R	3.0	30		V	I_R = 100 µA
Temperature Coefficient of V_F/Segment or DP	ΔV_F/°C		-2		mV/°C	
Thermal Resistance LED Juction-to-Pin	$R\theta_{J\text{-}PIN}$		200		°C/W/Seg	

chanhvinh.com

Orange

Device Series - HDSP-U4xx

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity/Segment (Digit Average) [1,2]	I_V	360	980		µcd	I_F = 5 mA
			5390			I_F = 20 mA
Forward Voltage/Segment or DP	V_F		2.0	2.5	V	I_F = 20 mA
Peak Wavelength	λ_{PEAK}		600		nm	
Dominant Wavelength [3]	λ_d		603		nm	
Reverse Voltage/Segment or DP [4]	V_R	3.0	30		V	I_R = 100 µA
Temperature Coefficient of V_F/Segment or DP	ΔV_F/°C		-2		mV/°C	
Thermal Resistance LED Juction-to-Pin	$R\theta_{J\text{-}PIN}$		200		°C/W/Seg	

Yellow

Device Series - HDSP-U3xx

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity/Segment (Digit Average) [1,2]	I_V	225	480		µcd	I_F = 5 mA
			2740			I_F = 20 mA
Forward Voltage/Segment or DP	V_F		2.2	2.5	V	I_F = 20 mA
Peak Wavelength	λ_{PEAK}		583		nm	
Dominant Wavelength [3,5]	λ_d	581.5	586	592.5	nm	
Reverse Voltage/Segment or DP [4]	V_R	3.0	50.0		V	I_R = 100 µA
Temperature Coefficient of V_F/Segment or DP	ΔV_F/°C		-2		mV/°C	
Thermal Resistance LED Juction-to-Pin	$R\theta_{J\text{-}PIN}$		200		°C/W/Seg	

High Performance Green

Device Series - HDSP-U5xx

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Luminous Intensity/Segment (Digit Average) [1,2]	I_V	860	3000		µcd	I_F = 10 mA
			6800			I_F = 20 mA
Forward Voltage/Segment or DP	V_F		2.1	2.5	V	I_F = 10 mA
Peak Wavelength	λ_{PEAK}		566		nm	
Dominant Wavelength [3,5]	λ_d		571		nm	
Reverse Voltage/Segment or DP [4]	V_R	3.0	50.0		V	I_R = 100 µA
Temperature Coefficient of V_F/Segment or DP	ΔV_F/°C		-2		mV/°C	
Thermal Resistance LED Juction-to-Pin	$R\theta_{J\text{-}PIN}$		200		°C/W/Seg	

Notes:
1. Case temperature of device immediately prior to the intensity measurement is 25° C.
2. The digits are categorized for luminous intensity. The intensity category is designated by a letter on the side of the package.
3. The dominant wavelength, λ_d, is derived from the CIE chromaticity diagram and is that single wavelength which defines the color of the device.
4. Typical specification for reference only. Do not exceed absolute maximum ratings.
5. The Yellow (HDSP-U3XX) series and Green (HDSP-U5XX) series displays are categorized for dominant wavelength. The category is designated by a number adjacent to the luminous intensity category letter.

chanhvinh.com

AlGaAs Red



Figure 1. Maximum Tolerable Peak Current vs. Pulse Duration – AlGaAs Red.



Figure 2. Forward Current vs. Forward Voltage.



Figure 3. Relative Luminous Intensity vs. DC Forward Current.



Figure 4. Relative Efficiency (Luminous Intensity per Unit Current) vs. Peak Current.

HER, Orange, Yellow, Green



Figure 5. Maximum Tolerable Peak Current vs. Pulse Duration – HER, Orange.



Figure 6. Maximum Tolerable Peak Current vs. Pulse Duration – Yellow.

chanhvinh.com

HER, Orange, Yellow, Green



Figure 7. Maximum Tolerable Peak Current vs. Pulse Duration – Green.



Figure 8. Maximum Allowable DC Current vs. Ambient Temperature.



Figure 9. Forward Current vs. Forward Voltage Characteristics.



Figure 10. Relative Luminous Intensity vs. DC Forward Current.



Figure 11. Relative Efficiency (Luminous Intensity per Unit Current) vs. Peak Current.

chanhvinh.com

Intensity Bin Limits (mcd)

AlGaAs Red

HDSP-U1xx		
IV Bin Category	**Min.**	**Max.**
E	0.315	0.520
F	0.428	0.759
G	0.621	1.16
H	0.945	1.71
I	1.40	2.56
J	2.10	3.84
K	3.14	5.75
L	4.70	8.55

HER

HDSP-U2xx		
IV Bin Category	**Min.**	**Max.**
B	0.342	0.630
C	0.516	0.946
D	0.774	1.418
E	1.160	2.127
F	1.740	3.190
G	2.610	4.785
H	3.915	7.177

Orange

HDSP-U4xx		
IV Bin Category	**Min.**	**Max.**
C	0.443	0.677
D	0.554	0.846
E	0.692	1.057
F	0.856	1.322
G	1.082	1.652
H	1.352	2.066
I	1.692	2.581
J	2.114	3.227
K	2.641	4.034
L	3.300	5.042
M	4.127	6.303
N	5.157	7.878

Yelow

HDSP-U3xx		
IV Bin Category	**Min.**	**Max.**
B	0.229	0.387
C	0.317	0.582
D	0.476	0.872
E	0.714	1.311
F	1.073	1.967
G	1.609	2.950
H	2.413	4.425

Green

HDSP-U5xx		
IV Bin Category	**Min.**	**Max.**
H	0.86	1.58
I	1.29	2.37
J	1.94	3.55
K	2.90	5.33
L	4.37	8.01

Color Categories

		Dominant Wavelength (nm)	
Color	**Bin**	**Min.**	**Max.**
Yellow	1	581.50	585.00
	3	584.00	587.50
	2	586.50	590.00
	4	589.00	592.50
Green	2	573.00	577.00
	3	570.00	574.00
	4	567.00	571.00
	5	564.00	568.00

Note:
All categories are established for classification of products. Products may not be available in all categories. Please contact your local Avago representatives for further clarification/information.

chanhvinh.com

Electrical/Optical

For more information on electrical/optical characteristics, please see Application Note 1005.

Contrast Enhancement

For information on contrast enhancement, please see Application Note 1015.

Soldering/Cleaning

Cleaning agents from the ketone family (acetone, methyl ethyl ketone, etc.) and from the chorinated hydrocarbon family (methylene chloride, trichloroethylene, carbon tetrachloride, etc.) are not recommended for cleaning LED parts. All of these various solvents attack or dissolve the encapsulating materials used to form the package of plastic LED parts.

For more information on soldering LEDs, please refer to Application Note 1027.

For product information and a complete list of distributors, please go to our web site: **www.avagotech.com**

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies in the United States and other countries.
Data subject to change. Copyright © 2005-2015 Avago Technologies. All rights reserved. Obsoletes 5988-2220EN
AV02-3584EN - October 9, 2015