chanhvinh.com

PRODUCT DATA SHEET

Part Number: 1902X00X

Type	Size	Rating	Description
LED	M6	-	LED Prominent Panel Indicator

Dimensions (mm)



Part #	Colour	Voltage V_f	Intensity (mcd@10mA)
1902X003	Red	2.0	25
1902X001	Green	2.2	20
1902X002	Yellow	2.1	15
1902X004	Red/Green	2.0/2.2	25/20
1902X005	Red/Yellow	2.0/2.1	25/15
1902X006	Green/Yellow	2.2/2.1	20/15
1902X007	Blue	3.8	30
1902X008	Orange	2.05	30
1902X00W	White	3.2	3000

Bezel types - X=0 satin chrome / X=1 black chrome / X=2 matt chrome

Notes:

1 Electrical & optical data are measured at an ambient temperature of 25ºC
2 Luminous intensity at DC
3 Storage temperature -25 ºC to +80ºC
4 Application temperature -20 ºC to +60ºC
5 Due to component tolerances, colour temperature variations may be observed
6 The terminals are not qualified for soldering
7 Ingress rating IP40
8 The plastic(polycarbonate) has limited chemical resistance
9 RoHS & REACH SVHC compliant

CML Innovative Technologies Ltd • 69-70 Eastern Way • Bury St Edmunds • Suffolk • IP32 7AB • England
Tel: +44 (0) 1284 714700 • Fax: +44 (0) 1284 754406 • Email: bury@cml-it.com • www.cml-it.com
Registered Office: Eastern Way, Bury St Edmunds – Registration No. 265006 England