chanhvinh.com



SERIES RP 3502 SWITCHES

PUSHBUTTON SWITCHES - PANEL MOUNT



FEATURES & BENEFITS

- Single Pole, Single throw with momentary function
- Rugged, Panel mount design
- Available in Nylon or metal frame body

APPLICATIONS/MARKETS

- Test & Instrumentation
- Industrial controls
- Telecommunications
- Networking

SPECIFICATIONS

Contact Rating:	3A @ 120 VAC 1.5A @ 250 VAC
Life Expectancy (Mechanical):	6,000 cycles
Life Expectancy (Electrical):	6,000 cycles
Contact Resistance:	50mΩ (initial max.)
Insulation Resistance:	500MΩ min.
Dielectric Strength:	1,000 VAC 1 minute
Operating Temperature:	-20°C to +65°C

MATERIALS

Plastic:	Nylon (UL flame: 94V-2)
Metal:	Nickel plated brass

HOW TO ORDER

SERIES	MODEL NO.	BODY STYLE	FUNCTION	BUTTON COLOR
RP	3502	None = Plastic M = Metal	A = OFF-(ON) B = ON-(OFF)	BLK = Red RED = Red GRN = Green YEL = Yellow

Example Ordering Number

RP–3502–M–A–BLK

Specifications subject to change without notice.

RP 3502







