chanhvinh.com

Your Expert Partner for **Human Machine Interfaces**

# Indicator

Distribution by
Rs-online

17-210350




https://rs-online.eao.com/component/17-210350...

chanhvinh.com

chanhvinh.com

Your product:



# 17-210350
# Indicator

## FRONT

| | |
|---|---|
| **Front dimension:** | Ø 16 mm |
| **Front form:** | Round |
| **Reflector:** | Metal, polished chromium-plated |

## MOUNTING

| | |
|---|---|
| **Design:** | Raised |
| **Mounting cut-out:** | Ø 14 mm |
| **Mounting type:** | Panel mounting |

## OPERATING-/INDICATION PART

| | |
|---|---|
| **Lens:** | round |
| **Illumination colour:** | Red |

## ELECTRICAL CHARACTERISTICS

| | |
|---|---|
| **Operating voltage:** | 24 V DC ±10 % |
| **Operation current:** | 20 mA ±15 % |
| **Lumi. Intensity:** | 150 mcd |
| **Polarity:** | Anode (+) Brass plug-in connector<br>Cathode (-) Brass tinned plug-in connector |

## MECHANICAL CHARACTERISTICS

| | |
|---|---|
| **Terminal:** | Plug-in terminal, 2.8 x 0.8 mm |
| **Tightening torque:** | Fixing nut max. 0.2 Nm |

| | |
|---|---|
| **Weight:** | 0.014 kg |

## AMBIENT CONDITION

| | |
|---|---|
| **IP Protection:** | IP40 front side, IP65 front side, according to IEC 60529 |
| **Operating temperature:** | – 20 °C ... + 60 °C |
| **Storage temperature:** | – 25 °C ... + 80 °C |


## CERTIFICATE

| | |
|---|---|
| **Approbations:** | UL |
| **Conformities:** | 2011 / 65 / EC (RoHS), 2014 / 35 / EU (230 VAC) |
| **REACH:** | REACH compliant |
| **RoHS:** | RoHS compliant |

## OTHER


| | |
|---|---|
| **Short Description:** | Indicator, Ø 14 mm, Ø 16 mm, Round, Plug-in terminal, 2.8 x 0.8 mm, Red |
| **Kind of illlumination:** | Single-LED |
| **Hints:** | Connectors: Brass terminal = anode (+); brass tinned terminal = cathode (-)<br>IP67 front side gap between LED and reflector and gap between reflector and frontplate sealed to IP67 when using the supplied gasket.<br>The plastic is limited resistant to chemicals. |

**Wiring diagrams:**





**Mounting cut-outs:**

chanhvinh.com




**Dimension drawings:**




A = Protection tube (only 230 VAC)
B = Tri-colour