chanhvinh.com

e a o

Your Expert Partner for **Human Machine Interfaces**

Actuator

Distribution by
Rs-online

45-
290D.2000.113



https://rs-online.eao.com/component/45-290D.2...

chanhvinh.com

chanhvinh.com

Your product:



45-290D.2000.113
Actuator

FRONT

Front dimension:	Ø 29,5 mm
Front form:	Round
Front bezel colour:	Silver
Front bezel material:	Metal

MOUNTING

Design:	Raised
Mounting cut-out:	Ø 22.3 mm
Mounting type:	Panel mounting

MECHANICAL CHARACTERISTICS

Switching action:	Maintained (a) - Rest - Maintained
Switching positions:	3 positions
Switching angle:	45° left / 45° right / -45° ... +45°
Mechanical lifetime:	1 Mil. cycles of operation (RCC/RPB)
Operating frequency:	1 800/h
Weight:	0.079 kg

AMBIENT CONDITION

IP front protection:	IP66, IP67, IP69K
Operating temperature:	– 25 °C ... + 70 °C
Storage temperature:	– 40 °C ... + 80 °C

Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
Vibration resistance:	According to IEC 60068-2-6: 10 … 500 Hz: 5 g
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6


CERTIFICATE

REACH:	REACH compliant
RoHS:	RoHS compliant

OTHER

Short Description:	Actuator, Ø 22.3 mm, Ø 29,5 mm, Round, Silver, Metal, Maintained (a) - Rest - Maintained, IP66, IP67, IP69K
Housing material:	Metal
Hints:	The standard lock: RONIS, T254

Switching positions:




Wiring diagrams:



Mounting cut-outs:

chanhvinh.com

chanhvinh.com



Dimension drawings:

