chanhvinh.com

eao

Your Expert Partner for **Human Machine Interfaces**

Illumination element

Distribution by
Rs-online

45-320.1F46



https://rs-online.eao.com/component/45-320.1F...

chanhvinh.com

Your product:



45-320.1F46
Illumination element

MOUNTING

Component mounting type:	Front mounting

OPERATING-/INDICATION PART

Illumination colour:	Amber

ELECTRICAL CHARACTERISTICS

Operating voltage:	24 V AC/DC
Surge voltage resistance:	4 kV
Lumi. Intensity:	450 - 1120 mcd

MECHANICAL CHARACTERISTICS

Terminal:	Spring-type terminal
Terminal details 1:	Solid 2 x (0.25 … 1.5mm^2) Finely stranded – Without end sleeves 2 x (0.5 … 1.5 mm^2) – With end sleeves 2 x (0.5 … 0.75 mm^2) – For AWG cables for auxiliary contacts 2 x (24 … 16)
Weight:	0.01 kg

CERTIFICATE


REACH:	REACH compliant
RoHS:	RoHS compliant

OTHER

chanhvinh.com

Short Description: Illumination element, Spring-type terminal, Amber, 24 V AC/DC, Front mounting

Wiring diagrams:



Dimension drawings:

