chanhvinh.com

e a o

Your Expert Partner for **Human Machine Interfaces**

Switching element

Distribution by
Rs-online

61-8755.37



https://rs-online.eao.com/component/61-8755.3...

chanhvinh.com

Your product:



61-8755.37
Switching element

ELECTRICAL CHARACTERISTICS

Switching voltage and switching current:

Switch rating AC with gold contact	
Service category AC-15	
according to EN IEC 60947-5-1	
Voltage	50 VAC
Current	0.5 A
Switch rating DC with gold contact	
Service category DC-13	
according to EN IEC 60947-5-1	
Voltage	50 VDC
Current	0.1 A

Contacts: 2 NC

Rated Operational Voltage Ue: 50 VAC / DC, according to EN / IEC 60947-5-1

Rated impulse withstand voltage Uimp: 0.8 kV, according to EN / IEC 60947-5-1

Rated insulation voltage Ui: 320 VAC, according to EN / IEC 60947-5-1

Recommended minimum operational data:

Voltage	10 VAC/DC
Current	2 mA

Switching rating: 50 V AC/DC @ 0,3 A

Pollution degree: 3, according to EN IEC 60947-1

Standards: The switches comply with the “Standards for low-voltage switching devices” EN IEC 61058-1, EN IEC 60947-5-1

Thermal current Ith: 3 A

MECHANICAL CHARACTERISTICS

Terminal: Plug-in terminal, 2.8 x 0.5 mm

Contact material: Gold

Switching system: Slow-make switching element

Switching positions: 2 positions

Wire cross section: 1 wire flexible: 0.5 … 0.75 mm^2
1 wire super flexible: 0.5 mm^2

1 wire rigid: 0.5 … 1.5 mm^2
2 wires flexible: 0.5 … 0.75 mm^2
2 wires super flexible: 0.5 mm^2
2 wires rigid: 0.5 … 1.5 mm^2

Weight: 0.008 kg

AMBIENT CONDITION

Operating temperature: – 25 °C … + 55 °C

Climate resistance: Damp heat, cyclic: 96 hours, + 25 °C/97 %, + 55 °C/93 % relative humidity, as per EN IEC 60068-2-30
Damp heat, steady: 56 days, + 40 °C/93 % relative humidity, according to EN IEC 60068-2-78
Rapid change of temperature: 100 cycles, – 40 °C … + 80 °C, as per EN / IEC 60068-2-14

CERTIFICATE

Approbations: CB (IEC 61058-1), CQC, CSA, DNV, ENEC (EN 61058-1), UL, VDE

Conformities: CE, UKCA, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

REACH: REACH compliant


RoHS: RoHS compliant

OTHER

Short Description: Switching element, Slow-make switching element, 50 V AC/DC @ 0,3 A, Gold, 2 NC, Plug-in terminal, 2.8 x 0.5 mm

Material: Plastic, according to UL 94 V0

Wiring diagrams:



Component layouts:

chanhvinh.com

