chanhvinh.com

Specifications

Eaton 037985



Catalog Number: 037985

Eaton Moeller® series RMQ16 Blanking plug, black, IP65_x Q18BS

General specifications

Product Name Eaton Moeller® series RMQ16 Accessory Blanking plug	**Catalog Number** 037985
	EAN 4015080379850
Product Length/Depth 27 mm	**Product Height** 18 mm
Product Width 18 mm	**Product Weight** 0.004 kg
Certifications UL/CSA certification not required	

Powering Business Worldwide

Product specifications

Type

For grid spacing 18 x 18 mm

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

Resources

Catalogs

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

eaton-rmq-titan-brochure-br047004en-en-us.pdf

Declarations of conformity

DA-DC-00004158.pdf

DA-DC-00004136.pdf

Drawings

eaton-operating-actuation-rmq16-blanking-plug-dimensions.eps

eaton-operating-button-symbol-005.eps

Installation instructions

IL04716016Z

mCAD model

DA-CD-blind_18

DA-CS-blind_18

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Connection to SmartWire-DT

No

Ambient operating temperature - max

60 °C

Ambient operating temperature - min

-25 °C

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Opening diameter

16 mm

Opening height

0 mm

Rated operational current for specified heat dissipation (In)

0 A

Color

Black

Material

chanhvinh.com

Plastic

Degree of protection

IP65

Functions

For closing off of spare mounting locations

Lens type

Square

Static heat dissipation, non-current-dependent Pvs

0 W

Width opening

0 mm

Product category

Accessories

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia