chanhvinh.com

Specifications

Eaton 107066



Catalog Number: 107066

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Busbar support, 3p, for flat busbars

General specifications

Product Name	**Catalog Number**
Eaton xEffect SASY 60i busbar support	107066
EAN	**Product Length/Depth**
4015081068296	50 mm
Product Height	**Product Width**
190 mm	20 mm
Product Weight	**Compliances**
0.154 kg	RoHS conform

Certifications

IEC/EN 60439-1, VDE 0660 Part 500

Powering Business Worldwide

chanhvinh.com

Product specifications

Used with

15 x 5/10 mm
30 x 5/10 mm
12 x 5/10 mm
20 x 5/10 mm
25 x 5/10 mm
60 mm system
System for flat busbar

Special features

Can be fitted to all busbar sizes using concertina system
With screw block inside

Type

60 mm system
System for flat busbar

Features

Self-extinguishing acc. UL 94
Halogen free

Frequency rating

50 Hz / 60 Hz

Creepage resistance

CTI 200

Current rating - max

630 A

Voltage rating

690 V

Ambient operating temperature - max

35 °C

Busbar distance

60 mm

Busbar temperature - max

70 °C

Rated insulation voltage (Ui)

3000 V

Short-circuit duration

20 ms

Resources

Brochures

eaton-xeffect-sasy60i-customer-success-story-css-wagner-mueller-en-us.pdf

Catalogs

eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf

Product Range Catalog Switching and protecting motors

Certification reports

eaton-xeffect-sasy-60i-declaration-of-conformity.pdf

Characteristic curve

eaton-control-panels-xeffect-sasy-busbar-support-characteristic-curve.eps

Drawings

eaton-control-panels-xeffect-sasy-busbar-support-dimensions.eps

eaton-control-panels-xeffect-sasy-busbar-support-3d-drawing-002.eps

Number of poles

Three-pole

Color

Light gray (RAL 7035)

Distance between busbar centers

60 mm

Mounting position

Vertical, horizontal

Current rating (peak withstand)

50 kA (20 x 5 mm)
64 kA (30 x 5 mm)
73 kA (30 x 10 mm)
56 kA (20 x 10 mm)
50 kA (12 x 5 mm)
50 kA (25 x 5 mm)
56 kA (12 x 10 mm)

Functions

Busbar support
IEC busbar support

Frequency rating of contacts

50 Hz / 60 Hz

Temperature resistance

Up to 120 °C

Distance between busbar supports

250 mm

Rated operation current (Ie)

630 A

Suitable for

Three-pole

Flammability characteristics (UL)

Self-extinguishing (UL 94)

Material

Thermoplast, silicon free, chlorine free
Halogen free

Uninterrupted current (Iu) of bar

436 A (25 x 5 mm, Tu=35 °C and Ts=65 °C)
687 A (30 x 10 mm, Tu=35 °C and Ts=65 °C)
273 A (15 x 5 mm, Tu=35 °C and Ts=65 °C)
349 A (20 x 5 mm, Tu=35 °C and Ts=65 °C)
392 A (12 x 10 mm, Tu=35 °C and Ts=65 °C)

chanhvinh.com

491 A (30 x 5 mm, Tu=35 °C and Ts=65 °C)

218 A (12 x 5 mm, Tu=35 °C and Ts=65 °C)

567 A (20 x 10 mm, Tu=35 °C and Ts=65 °C)

chanhvinh.com

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia

chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com