chanhvinh.com

Specifications

Eaton 134811



Catalog Number: 134811

Eaton Moeller® series E53 Proximity switch, capacitive, Sn=20mm, 1 N/C, 3L, PNP, M30, insulated material, line 2m

General specifications

Product Name
Eaton Moeller® series E53 Proximity switch

Catalog Number
134811

EAN
4015081316632

Product Length/Depth
165.1 mm

Product Height
31.75 mm

Product Width
139.7 mm

Product Weight
0.28 kg

Certifications
IEC/EN 60947-5-2
CE

Powering Business Worldwide

chanhvinh.com

Product specifications

Type
Capacitive sensor

Electric connection type
Cable

Enclosure material finishing
Other

Fitted with:
Status indication

Actuation type
Other

Enclosure material
Plastic

Enclosure type
Cylinder, screw-thread

Category (EN 954-1)
B

Explosion safety category for dust
None

Explosion safety category for gas
None

Voltage type
DC

Mounting method
Flush mounting

Material
Insulated material

Connection type
2 m connection cable
3-wire

Installation type
Concise

Degree of protection
NEMA 4
IP65
NEMA 13
NEMA 12

Resources

Catalogs
Product Range Catalog Sensors – products, basic information, applications

Declarations of conformity
DA-DC-00004653.pdf

DA-DC-00004648.pdf

Drawings
eaton-proximity-switches-e53-proximity-switch-dimensions-006.eps

eaton-proximity-switches-e53-proximity-switch-dimensions-008.eps

eaton-proximity-switches-e53-proximity-switch-dimensions-007.eps

1360DRW-93

Installation instructions
IL05307002Z

Interface type

None

LED indicator

Status indication of Switching state: Red LED

Switch function type

Breaker contact

Load current

Max. 300 mA (Ie)

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

Rated control supply voltage (Us) at DC - max

30 V

Rated control supply voltage (Us) at DC - min

10 V

Rated switching distance (Sn)

20 mm

Repeatability

10 %

Sensor height

0 mm

Sensor length

80 mm

Supply voltage - max

30 V

Supply voltage - min

10 V

Switching hysteresis of Sn

20 %

Voltage rating - max

250 V

Width sensor

0 mm

Product category

E53 Capacitive Series

Residual ripple

10 % (U_e)

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Switching frequency

250 Hz

Switching output type

PNP

Temperature drift of sn

10 %

Safety performance level (EN ISO 13849-1)

None

SIL (IEC 61508)

None

Ambient operating temperature - max

70 °C

Ambient operating temperature - min

-25 °C

Diameter sensor

30 mm

Number of contact energized outputs with signalling function

0

Number of contacts (normally closed contacts)

1

Number of outputs (protected contact energized)

0

Number of outputs (protected semiconductor)

0

Number of outputs (semiconductor with signaling function)

1

Output current at protected output - max

0 mA

Rated control supply voltage (Us) at AC, 50 Hz - max

0 V

Rated control supply voltage (Us) at AC, 50 Hz - min

0 V

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

chanhvinh.com



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia

chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com