chanhvinh.com

Specifications

# Eaton 135987

## Catalog Number: 135987

Eaton Moeller® series E57 Proximity switch, E57 Premium+ Series, 1 N/O, 3-wire, 6 - 48 V DC, M30 x 1 mm, Sn= 22 mm, Semi-shielded, PNP, Stainless steel, 2 m connection cable



## General specifications

**Product Name**
Eaton Moeller® series E57 Proximity switch

**Catalog Number**
135987

**EAN**
4015081327805

**Product Length/Depth**
152.4 mm

**Product Height**
50.8 mm

**Product Width**
127 mm

**Product Weight**
0.23 kg

**Certifications**
CSA File No.: none
CSA Class No.: none
IEC/EN 60947-5-2
None

Powering Business Worldwide

chanhvinh.com

## Product specifications

**Type**

Inductive sensor

**Electric connection type**

Cable

**Enclosure material finishing**

Other

**Actuation type**

Metallic Target

**Enclosure material**

Metal

**Enclosure type**

Cylinder, screw-thread

**Category (EN 954-1)**

B

**Explosion safety category for dust**

None

**Explosion safety category for gas**

None

**Safety performance level (EN ISO 13849-1)**

None

**SIL (IEC 61508)**

None

**Ambient operating temperature - max**

70 °C

**Ambient operating temperature - min**

-25 °C

**Diameter sensor**

30 mm

**Number of contact energized outputs with signalling function**

0

**Number of contacts (normally open contacts)**

1

**Number of outputs (protected contact energized)**

0

**Number of outputs (protected semiconductor)**

## Resources

**Brochures**

eaton-sensors-brochure-br053001en-en-us.pdf

**Catalogs**

Product Range Catalog Sensors – products, basic information, applications

**Declarations of conformity**

DA-DC-00004651.pdf

DA-DC-00004656.pdf

**Drawings**

eaton-proximity-switches-e57-proximity-switch-dimensions.eps

1360DRW-93

**eCAD model**

DA-CE-ETN.E57-30LE22-B

**Installation instructions**

IL05301003Z

**Multimedia**

We make what matters

0

Number of outputs (semiconductor with signaling function)

1

Operational current (Ib) in the switched state at 24 V DC

10 A

Output current at protected output - max

0 mA

Rated control supply voltage (Us) at AC, 50 Hz - max

0 V

Voltage type

DC

Mounting method

Semi-shielded mounting

Material

Stainless steel

Connection type

2 m connection cable

3-wire

Installation type

Not flat

Degree of protection

IP67

NEMA 4X, 6, 13

Interface type

None

LED indicator

Status indication of Switching state: Red LED

Switch function type

Normally open contact

Load current

Max. 500 mA (Ie, at 6 - 30 V DC)

Residual current

0.1 mA (through the load in the blocked state at 230 V AC and 24 V DC)

Shock resistance

30 g, Mechanical, Shock duration 11 ms

Switching frequency

300 Hz

Voltage rating - max

48 V

Width sensor

0 mm

Product category

E57 Premium+ Series

Switching output type

PNP

Temperature drift of sn

10 %

Rated control supply voltage (Us) at AC, 50 Hz - min

0 V

Rated control supply voltage (Us) at AC, 60 Hz - max

0 V

Rated control supply voltage (Us) at AC, 60 Hz - min

0 V

Rated control supply voltage (Us) at DC - max

48 V

Rated control supply voltage (Us) at DC - min

6 V

Rated switching distance (Sn) - max

22 mm

Repeatability

3 %

Sensor height

0 mm

Sensor length

67.8 mm

Supply voltage - max

48 V

Supply voltage - min

6 V

Switching hysteresis of Sn

15 %

Voltage drop (Ud)

2.5 V

chanhvinh.com




Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia

chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com
chanhvinh.com