chanhvinh.com

DATASHEET - CSAS4F4CY2202

Connection cable, 4p, AC, coupling M12 flat, open end, L=2m

Part no. CSAS4F4CY2202
166982

General specifications

Product name		Eaton Moeller® series CSAS Accessory Connection cable
Part no.		CSAS4F4CY2202
EAN		4015081642854
Product Length/Depth		165.1 millimetre
Product height		12.7 millimetre
Product width		165.1 millimetre
Product weight		0.09 kilogram
Compliances		CE
Product Tradename		CSAS
Product Type		Accessory
Product Sub Type		Connection cable

Product Specification Details

Cable length		2 m
Cable sheath material		Other
Cable type		Multi-core
Color cable sheath		Yellow
Contact body material		Other
Contact surface material		Other
Continuity resistor		0 mΩ
Degree of protection		Other
Electrical connection type (box-sided)		Other
Electrical connection type (field-sided)		M12
Nominal current		0 A
Number Of Poles		Four-pole
Permitted temperature of outer cable (assembled) without vibration - max		70 °C
Permitted temperature of outer cable (assembled) without vibration - min		40 °C
Permitted temperature of outer cable (assembling/handling) - max		70 °C
Permitted temperature of outer cable (assembling/handling) - min		40 °C
Plug-in contact type (box-sided)		Male (plug)
Plug-in contact type (field-sided)		Female (bus)
Positioning cable feed (box-sided)		Other
Positioning cable feed (field-sided)		Straight
Product category		Accessories
Rated operational voltage (Ue) - max		0 V

Technical data ETIM 9.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)

Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor/actuator adapter, with cable (ecl@ss13-27-06-03-13 [AFR625008])

Number of poles		4
Type of electrical connection, field-sided		M12
Type of plug-in contact, field sided		Female (bus)
Positioning cable feed, field-sided		Straight
Type of electrical connection, box-sided		Other
Type of plug-in contact, box-sided		Male (plug)
Positioning cable feed, box-sided		Other
Cable length	m	2
Material of cable sheath		Other

chanhvinh.com

Halogen free			No
Colour cable sheath			Yellow
With LED indication			No
Screened			No
Cable type			Multi-core
Vulcanize			No
Material contact body			Other
Material of contact surface			Other
Permitted cable outer temperature after assembling without vibration		°C	40 - 70
Permitted cable outer temperature during assembling/handling		°C	40 - 70
Rated current In		A	0
Rated voltage		V	0
Continuity resistance		mOhm	0
Degree of protection (IP)			Other

© 04/2023 by Eaton Industries GmbH