chanhvinh.com

# DATASHEET - 17.5KV 10AMP 2" DIN FUSE



**Fuse-link, medium voltage, 10 A, AC 17.5 kV, 35.5 kA, 2", 51 x 292 mm, back-up, DIN, with striker**

Powering Business Worldwide™

**Part no.** 17.5KV 10AMP 2" DIN FUSE
**Catalog No.** 17.5TDLSJ10

Similar to illustration

## Delivery program

| | | | |
|---|---|---|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | medium voltage |
| Rated current | I | A | 10 |
| Rated voltage | | | AC 17.5 kV |
| Construction size | | | 2" |
| Size | | | 51 x 292 mm |
| Utilization category | | | back-up |
| Status indicator | | | with striker |
| Breaking Capacity | | kA | 35.5 |
| usable for size/applications | | | transformer protection<br>indoor use |
| Standard/Approval | | | DIN |
| Standards/Regulations | | | DIN 43625<br>VDE 0670-4<br>VDE 0670-402<br>IEC 60282-1 |

## Technical data ETIM 7.0

| Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507) | | | |
|---|---|---|---|
| Rated current | | A | 10 |
| Rated voltage | | kV | 17.5 |
| Voltage type | | | AC |
| Rated frequency | | Hz | 50 - 50 |
| Breaking capacity | | kA | 35.5 |
| Utilization category | | | Other |
| Application | | | Primary side transformer protection |
| Length | | mm | 292 |
| Diameter | | mm | 51 |
| Performance category according to IEC 60282-1 | | | Back-up |
| With striker | | | Yes |
| Standard | | | DIN |
| Release characteristic | | | Other |
| Installation technique | | | Air |


© 06/2021 by Eaton Industries GmbH