chanhvinh.com

Specifications

Eaton 291465



Catalog Number: 291465

Eaton Moeller series xPole - Busbar. EV busbars 1Ph., 6HP, 80A for PLS. CLS. PKN., PFIM, PFHM, PFNM

General specifications

Product Name	**Catalog Number**
Eaton Moeller series busbar	291465
EAN	**Product Length/Depth**
4015082914653	29 mm
Product Height	**Product Width**
4.5 mm	105 mm
Product Weight	**Compliances**
0.033 kg	RoHS conform
Certifications	**Catalog Notes**
UL Listed CSA Certified	No end caps required, do not shorten

Powering Business Worldwide

chanhvinh.com

Product specifications

Used with

FAZ or FI breakers

Busbar

EVG

Type

Busbar

EVG

Features

Insulated

Accessory/spare part type

Busbar for residual current circuit breakers

Busbar for miniature circuit breaker

Busbar for combined residual current/power circuit breaker

Electric connection type

Fork

Rated surge voltage

4 KV

Rated uninterrupted current (Iu)

80 A

Suitable for number of devices

6

Number of poles

Single-pole

Color

Other

Rated short-time withstand current (Icw)

0 kA

Cross section

16 mm²

Number of modular spacings

6

Number of phases

1

Pitch dimensions

0 mm

Resources

Declarations of conformity

DA-DC-03_EVG

Drawings

eaton-mcb-busbar-dimensions-002.eps

eaton-busbar-3d-drawing.jpg

eaton-mcb-busbar-3d-drawing-003.eps

chanhvinh.com

Rated operational voltage (Ue) - max

415 V

Rated conditional short-circuit current (Iq)

25 kA

Functions

Busbar

Suitable for

6 devices

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia