
chanhvinh.com

Specifications

Eaton 291471



Catalog Number: 291471

Eaton Moeller series xPole - Busbar. EV busbars 3Ph., 9HP, 80A for PLS. CLS. PKN., PFIM, PFHM, PFNM

General specifications

Product Name	**Catalog Number**
Eaton Moeller series busbar	291471
EAN	**Product Length/Depth**
4015082914714	33 mm
Product Height	**Product Width**
10.4 mm	156 mm
Product Weight	**Compliances**
0.086 kg	RoHS conform

Powering Business Worldwide

chanhvinh.com

Product specifications

Used with

Busbar

EVG

Type

Busbar

EVG

Features

Insulated

Accessory/spare part type

Busbar for miniature circuit breaker

Busbar for combined residual current/power circuit breaker

Busbar for residual current circuit breakers

Electric connection type

Fork

Rated surge voltage

4 KV

Rated uninterrupted current (Iu)

80 A

Suitable for number of devices

2

Number of poles

Three-pole

Color

Other

Rated short-time withstand current (Icw)

0 kA

Cross section

16 mm^2

Number of modular spacings

9

Number of phases

3

Pitch dimensions

0 mm

Rated operational voltage (Ue) - max

415 V

Resources

Declarations of conformity

DA-DC-03_EVG

Drawings

eaton-mcb-busbar-dimensions-008.eps

eaton-busbar-3d-drawing.jpg

chanhvinh.com

Rated conditional short-circuit current (Iq)

25 kA

Functions

Busbar

Suitable for

3 devices

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia