chanhvinh.com

Specifications

# Eaton C14G1




## Catalog Number: C14G1

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 1 Amps, 80 kA Breaking capacity, class gG/gL, without indicator, compatible with a CH14 Modular fuse holder

### General specifications

**Product Name**
Eaton Bussmann series low voltage cylindrical fuse

**Catalog Number**
C14G1

**EAN**
5027590493772

**UPC**
051712667272

**Product Length/Depth**
51 mm

**Product Height**
14.3 mm

**Product Width**
14.3 mm

**Product Weight**
20.3 g

**Compliances**
CE Marked
GoST-R
RoHS Compliant

**Certifications**
IEC 60269

Powering Business Worldwide

chanhvinh.com

## Electrical data

**Amperage Rating**

1 A

**Voltage rating**

690 V

**Voltage type**

AC

**Breaking capacity**

80 kA

**Utilization category**

gG (cable protection/equipment protection)

**Frequency rating - max**

62 Hz

## Compatible fuse holder

**Suitable for**

CH14 Modular fuse holder

## Resources

**Catalogs**

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

**Declarations of conformity**

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

**Technical data sheets**

720115 Cylindrical fuses

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia