chanhvinh.com

Specifications

Eaton OPM-NG-SC3



Catalog Number: OPM-NG-SC3

Eaton Bussmann series Optima fuse holders, 0-30 A, Three-pole, 65°C, -10°C, 200 kA, Philslot screws/pressure plate, 200 kAIC, Thermoplastic, 35 mm DIN rail, #8 Screw, 600 V or less, Use with LP-CC, KTK-R, FNQ-R Class CC

General specifications

Product Name
Eaton Bussmann series Optima fuse holders

Catalog Number
OPM-NG-SC3

UPC
051712674171

Product Length/Depth
2.7 in

Product Height
3.5 in

Product Width
1.8 in

Product Weight
0.423 lb

Warranty
Not Applicable

Compliances
CE Marked
RoHS Compliant

Certifications
Contact Manufacturer
UL Listed
CSA Certified

Powering Business Worldwide

chanhvinh.com

chanhvinh.com

Electrical rating

Amperage Rating

0-30A

Interrupt rating

200 kAIC

Short-circuit rating

200 kA

Voltage rating

600 V or less

Physical details

Material

Thermoplastic

Number of Poles

Three-pole

Operating temperature - max

65 °C

Operating temperature - min

-10 °C

General information

Connection

Philslot screws/pressure plate

Mounting method

35 mm DIN rail

#8 Screw

Used with

For use with LP-CC, KTK-R, FNQ-R Class CC Rejection fuse

Resources

Catalogs

Bussmann series full line catalog 1007, section 8 fuse blocks and holders

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - OPM-NG-SC3

Technical data sheets

Bussmann series OPM-NG 3-pole overcurrent protection module no. 1109

Technical service bulletins

Datasheet - FNQ-30

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia