chanhvinh.com

SOLUTION GLOBALE
DE PROTECTION AUX ESD

EUROSTAT

ESD GLOVES *Non coated*

51-680-04XXB



Properties

Usage category:	General purposes
Configuration:	Elastic wrists
Fabric:	▪Polyester 80% ▪Spandex 12% ▪Carbon Liner 8%
Surface resistance:	< 10^6 Ω
Protection level:	1131X
Coating:	No coating
Colour:	Grey
Shelf life:	Functional 3 years
Washable:	Not washable
Packaging:	10 pairs/bag & 25 bags/ctn

PROTECTIVE GLOVES AGAINST MECHANICAL RISKS
Protection levels are measured from area of glove palm.

EN 388:2016



ABCDEF

A. Abrasion resistance, Min. 0; Max. 4
B. Blade cut resistance, Min. 0; Max. 5
C. Tear resistance, Min. 0; Max. 4
D. Puncture resistance, Min. 0; Max. 4
E. Blade Cut Resistance (TDM, EN ISO13997), Min. A; Max. F
F. Impact Protection, P=Pass

Compliancy

IEC standard:	Conform to IEC 61-340-5-1
CE certified:	EN1149-1:2006 ; EN16350:2014 EN 420:2003/A1(2009) ; EN388:2016
Certificate Nr.:	LEC FI00375310
Testing body:	ITS-Testing Services (UK) Limited
Supplier item Nr.:	GCAP

Size, dimensions and part numbers

Part Number	Size	Length +/- 5 mm	Width	Border color
51-680-0402B	XXS	190 mm	75 mm	Yellow
51-680-0401B	XS	195 mm	80 mm	Pink
51-680-0400B	S	210 mm	85 mm	White
51-680-0405B	M	220 mm	90 mm	Green
51-680-0410B	L	230mm	90 mm	Grey
51-680-0415B	XL	240 mm	95 mm	Red
51-680-0420B	XXL	250 mm	95 mm	Brown

chanhvinh.com



EUROSTAT

Instructions for the maintenance and use of protective gloves

Keep gloves away from heat and direct light, not exposed to organic solvents and their vapors. Before use, thoroughly inspect new or used gloves to ensure that they are free of defects. The gloves cannot be washed or chemically cleaned.

Warning

Do not use gloves when there is a risk of catching moving parts of the machine. The protective property only binds to the front of the glove - palm. Always use the correct size gloves and visually check their condition before each use. Never wear worn, damaged or otherwise damaged gloves. In people with sensitive skin, the possibility of skin irritation is not excluded, as the elastic cuff contains natural latex, which causes an allergic reaction in some people. In this case, do not continue to use gloves and seek professional help.

Note

The specified level of protection, according to EN 388, can help with the selection of the glove, but it is important to note that the application conditions cannot be simulated in a laboratory, and it is the responsibility of the user, not the manufacturer, to approve the application in specific conditions (working operation).