chanhvinh.com

# Displacement encoder
# MLO-POT-225-TLF

Part number: 152625



General operating condition

## Data sheet

| Feature | Value |
|---|---|
| CE mark (see declaration of conformity) | To EU EMC Directive |
| Functional principle of measuring system | Analogue |
| Ambient temperature | -30 °C ... 100 °C |
| Recommended wiper current | <1 µA |
| Max. wiper current, short-time | 10000 µA |
| Max. travel speed | 10 m/s |
| Max. travel acceleration | 200 m/s² |
| Displacement resolution | 0.01 mm |
| Non-dependent linearity | 0.07 % |
| Temperature coefficient | 5 ppm/K |
| Stroke | 225 mm |
| Output signal | Analogue |
| Connection resistance | 5 kOhm |
| Connection resistance tolerance | 20 % |
| Nominal operating voltage DC | 10 V |
| Max. operating voltage DC | 42 V |
| Permissible voltage fluctuations | <1% |
| Max. current consumption | 4 mA |
| Electrical connection | 4-pin<br>Type A<br>Plugs<br>To DIN 43650<br>Square design |
| Design | With cover strip<br>With moving slide<br>Open profile |
| Parallel offset of coupling | ± 1.5 mm |
| Angle offset of driver | ± 1 ° |
| Mounting position | optional |
| Product weight | 900 g |
| Material housing | Anodised |
| Material covering | Steel |
| Material slide housing | Die-cast aluminium<br>Polymer |
| Material slide coupling | Steel |
| Material cover | Polymer |
| Material mounting clips | PEI |
| Degree of protection at top | To IEC 60529 |

chanhvinh.com

| Feature | Value |
|---|---|
| Degree of protection at bottom | To IEC 60529 |
| Vibration resistance to DIN/IEC 68 Part 2-6 | Tested to severity level 2 |
| Continuous shock resistance to DIN/IEC 68 Part 2-82 | Tested to severity level 2 |
| LABS (PWIS) conformity | VDMA24364-B2-L |