chanhvinh.com

Sling Swivels • Ø9,5 mm, for slings up to 23 mm

EH 22330.



Product Description

Sling swivels can also be ordered separately from each other. The scope of delivery of the “sling swivels without socket” is one sling swivel.

Material

Pin part
- Stainless steel 1.4305, black

Spring
- Stainless steel


More information

Further products

- Sockets for wood, for sling swivels Ø9,5 mm, fixed position
- Sockets for plastic, for sling swivels Ø9,5 mm, fixed position
- Sockets for wood, for sling swivels Ø9,5 mm, 360° rotatable
- Socket rear stock, lateral, for sling swivels Ø9,5 mm, 360° rotatable

Drawing

Sling swivel



Order information

Nominal diameter [mm]	Dimensions swivel width [mm]	Load capacity for static load max. [kN]	Suitable for	Art. No.
9.5	23	1.2	22330.0534 / .0535 / .0536 / .0554	22330.0560

Compliance

RoHS-compliant
Compliant with Directive 2011/65/EU [RoHS].

Does not contain SVHC substances
No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 04.02.2026.

SCIP-code
N/A

Does not contain Proposition 65 substances
No Proposition 65 substances included.
https://www.P65Warnings.ca.gov/

Free from Conflict Minerals
This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

POP-compliant
Contains no persistent organic pollutants – Stockholm Convention [POP] as of September 2025.

PFAS-compliant
Contains no per- and polyfluoroalkyl substances (PFAS).

TSCA-compliant
Agent concentration in this product does not exceed the specified threshold.