chanhvinh.com

Sockets for plastic • for sling swivels Ø9,5 mm, fixed position

EH 22330.



Product Description

Sockets can also be ordered separately from each other. The scope of delivery of the “sockets without sling swivels” contain 2 identical sockets.


Material

Bushing
- Stainless steel 1.4305, black

Assembly

Easily mounted by an experienced gunsmith in only 30 minutes!
Installation instructions for plastic:
1. Drill locating hole according to specifications.
2. The use of adhesiv for securing is recommended.
3. Screw in socket.

Drawing



Order information

Nominal diameter [mm]	Location hole Bore Hole D Ø[1)] [mm]	Location hole depth of bore hole [mm]	internal hexagon [mm]	Art. No.
9.5	11.2	12.1	5	22330.0535

[1)] depending on the hardness of the plastic.

chanhvinh.com

Compliance

RoHS-compliant
Compliant with Directive 2011/65/EU [RoHS].

Does not contain SVHC substances
No SVHC substances with more than 0.1% w/w contained - SVHC list [REACH] as of 04.02.2026.

SCIP-code
N/A

Does not contain Proposition 65 substances
No Proposition 65 substances included.
https://www.P65Warnings.ca.gov/

Free from Conflict Minerals
This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.

POP-compliant
Contains no persistent organic pollutants – Stockholm Convention [POP] as of September 2025.

PFAS-compliant
Contains no per- and polyfluoroalkyl substances (PFAS).

TSCA-compliant
Agent concentration in this product does not exceed the specified threshold.