chanhvinh.com

Technical Data Sheet

Category 6 LS0H Unshielded


Patch Leads

Application/Product Description

HellermannTyton Category 6 unshielded patch leads are designed and tested to support Primary (Campus), Secondary (Riser) and Tertiary (Horizontal) applications for 10Base-T (Ethernet), 100Base-T(Fast Ethernet), 1000Base-T(Gigabit Ethernet), PoE and PoE+.

When used with HellermannTyton Category 6 unshielded cables, patch panels and outlets the combined performance exceeds Category 6/Class E link and channel requirements.

The patch leads are supplied standard 1m, 2m, 3m, 5m lengths in blue, green, grey, red and yellow, other lengths and colours are available on request.



Category 6 LS0H Unshielded Patch Leads

Technical Data

Electrical Characteristics @ 20°C	Specification
DC Loop Resistance	140Ω/km
Resistance Unbalance	5%
Insulation Resistance	5000MΩ/km
Capacitance Unbalance (pair to ground)	≤330pF/100m
Delay Skew	45ns/100m
NVP (Nominal Velocity of Propagation)	65%

Cable Standards

Cable

- ISO 11801:2002 (inc. Amend. A1 & A2)
- ANSI/TIA/EIA 568-C.2
- IEC 61156-6

Cable Sheath

- IEC 60332-1

Performance Characteristics


Frequency (MHz)		1	100	250
NEXT (dB)	Spec	65.0	46.4	38.8
	Typical	95.9	59.4	49.5
Return Loss (dB)	Spec	19.8	18.0	14.0
	Typical	38.5	27.6	28.1

**Typical values based on a 2m patch lead.*

This document is subject to change without notice.
The current version available from www.htdata.co.uk/site/products/cable

chanhvinh.com

Cable Construction



Product Performance	
Core	
Core Conductor:	26 AWG Stranded Copper Wire
Conductor Diameter:	0.16±0.02mm
Insulation:	HDPE
Insulation Diameter:	0.80±0.05mm
Twisting:	2 cores to the pair
Pair Colour:	Blue-White/Blue, Orange-White/Orange, Green-White/Green, Brown-White/Brown
Final Assembly	
Cable	4 pairs to the core
Sheath	LS0H Blue, Green, Grey, Red, Yellow
Outer Diameter	5.2mm ± 0.3mm
Mechanical and Environmental	
Temp. Operation	-20°C to +75°C
Min. Bend Radius	
During Installation:	8 x outer diameter
During Operation:	12 x outer diameter
Max. Tensile Force:	
During Installation	110N
Packaged Weight	42kg/km

HellermannTyton Data Ltd
Waterside House, Edgar Mobbs Way
Northampton NN5 5JE
United Kingdom

This document is subject to change without notice.
The current version available from www.htdata.co.uk/site/products/cable
tel: +44 (0) 1604 707420 web: www.htdata.co.uk

HellermannTyton