chanhvinh.com

Helaguard
PCS-PC Plain Hole Connector, IP54

Plain hole connector, nickel plated brass.

Features and Benefits

- Two part fitting comprising shell and body without thread
- The body is fitted to the conduit through the opposite side of the entry
- Acts as a locking device
- Provides a smooth entry bush

Technical Table

Article-No.	Type	Conduit Ø	Pack Cont.
166-31200	**PCS10-PC**	10	10
166-31201	**PCS12-PC**	12	10
166-31202	**PCS16-PC**	16	10
166-31203	**PCS20-PC**	20	10
166-31204	**PCS25-PC**	25	10
166-31205	**PCS32-PC**	32	2
166-31206	**PCS40-PC**	40	2
166-31207	**PCS50-PC**	50	1
166-31208	**PCS63-PC**	63	1
166-31209	**PCS75-PC**	75	1

All dimensions in mm. Subject to technical changes.



HelaGuard PCS-PC Plain Hole Connector.

Material Data

Material	**Nickel Plated Brass (NPB)**
Colour	**Metal (ML)**
Operating Temperature	**-100 °C to +300 °C**

Helaguard
PCS-FF Fixed Internal Thread, IP54

Fixed internal thread, nickel plated brass.

Features and Benefits

- Two part fitting comprising shell and body with internal thread
- Can be used to couple two pieces of conduit together when used with a swivel fitting

Technical Table

Article-No.	Type	Conduit Ø	Thread Size (metric)	Pack Cont.
166-31300	**PCS16-FF-M20**	16	M20	10
166-31301	**PCS20-FF-M20**	20	M20	10
166-31302	**PCS25-FF-M25**	25	M25	10
166-31303	**PCS32-FF-M32**	32	M32	10

All dimensions in mm. Subject to technical changes.



HelaGuard PCS-FF Fixed Internal Thread.