chanhvinh.com


Screw Mount D-Clip

Features and Benefits

Screwed D-clips are available in 3 sizes and guarantee time and cost saving by simply pressing the cable into the holder. The flexible grip means that later removal or replacement of cables and pipes is possible. 3 different bore diameters for fixing the holder are available



The clip is held in place by a screw and the bundled cable or pipe is guided securely.



D-Clip

Material Data

Material	**Polyacetal (POM)**
Operating Temperature	**-40 °C to +90 °C Continuous, (+110 °C for 500 h)**
Flammability	**UL94 HB**

RoHS

Technical Table

Article-No.	Type	Length (L)	Length (L2)	Width (W)	Wall (WT)	Fixing Hole Ø (FH)	Bundle Ø max.	Material	Colour
211-70000	**4D10**	17.0	8.0	15.0	2.0	4.0	10.0	POM	Black (BK)
211-70001	**4D15**	25.0	10.0	15.0	2.0	4.0	15.0	POM	Black (BK)
211-70002	**4D20**	28.0	10.0	15.0	2.5	4.0	20.0	POM	Black (BK)
211-70100	**6D10**	17.0	8.0	15.0	2.0	6.0	10.0	POM	Black (BK)
211-70101	**6D15**	25.0	10.0	15.0	2.0	6.0	15.0	POM	Black (BK)
211-70104	**6D20**	28.0	10.0	15.0	2.5	6.0	20.0	POM	Black (BK)
211-70200	**8D10**	17.0	8.0	15.0	2.0	8.0	10.0	POM	Black (BK)
211-70203	**8D15**	25.0	10.0	15.0	2.0	8.0	15.0	POM	Black (BK)
211-70204	**8D20**	28.0	10.0	15.0	2.5	8.0	20.0	POM	Black (BK)

All dimensions in mm. Subject to technical changes.