chanhvinh.com




HEYClip™ Cable Holders - Adhesive Back Mount

WIRE CAPACITY in.	WIRE CAPACITY mm.	PART NO. Rubber	PART NO. Acrylic Natural	PART NO. VHB	DESCRIPTION	OVERALL HEIGHT C in.	OVERALL HEIGHT C mm.	FOOTPRINT A x B in.	FOOTPRINT A x B mm.	STYLE
CH RA Series										
.17 x .12	4,4 x 3,0	**4271**	–	–	CH RA-72	.31	7,9	.37 x .37	9,4 x 9,4	4
.18 x .04 / x .11	4,6 x 1,0 / x 2,8	**–**	**4212A**	**4212V**	CH RA-65	.26	6,5	.37 x .37	9,4 x 9,4	1
		–	**4213A**	**4213V**	CH RA-83	.33	8,3			
.25 x .13	6,4 x 3,2	**4214**	**4214A**	**4214V**	CH RA-102	.40	10,2	.50 x .50	12,7 x 12,7	
.31 x .16	7,9 x 4,1	**4215**	**4215A**	**4215V**	CH RA-119	.47	11,9			
.35 x .24 / x .31	8,9 x 6,1 / x 7,9	**4216**	**4216A**	**4216V**	CH RA-141	.56	14,1			
		–	**4217A**	**4217V**	CH RA-157	.62	15,7			
x .19	x 4,7	**3603**	**3603A**	**3603V**	CH RA-122	.47	12,0	.76 x .74	19,3 x 18,8	2
.45 x .38	11,4 x 9,5	**3608**	**3608A**	**3608V**	CH RA-172	.68	17,2			
x .75	x 19,0	**3613**	**3613A**	**3613V**	CH RA-267	1.05	26,7			
.29 x .25	7,4 x 6,4	**3614**	–	–	CH RA-121	.48	12,1	.50 x 1.00	12,7 x 25,4	3


Standard color natural. Flame retardant UL 94V-0 material available, consult Heyco.

- Gather and direct single or bundles of cable.
- Apply to a clean, dry surface.
- Part Description Key: CH RA-X, where X = Overall Height (mm).
- Part Description Key: CH RA-X, where X = Overall Height (mm).
- Clips without suffix have a load rating of 1 pound per square inch
- Clips with suffix "A" have a load rating of 6 pounds per square inch
- Clips with suffix "V" have a load rating of 105 pounds per square inch


Style 1




Style 2



Style 3



Style 4



HEYClip™ Cable Holders - Blind Head Mount

For .250˝ (6,4 mm) *Minimum* Thickness Panels

WIRE CAPACITY in.	WIRE CAPACITY mm.	PART NO. Natural	DESCRIPTION	OVERALL HEIGHT C in.	OVERALL HEIGHT C mm.	FOOTPRINT A x B in.	FOOTPRINT A x B mm.	MOUNTING HOLE DIA. in.	MOUNTING HOLE DIA. mm.
Top Entry - Regular Gate									
x .19	x 4,8	**4202**	CH RB-13	.51	13,0	.22 x .61	5,6 x 15,5	.312	7,9
.44 x .38	11,1 x 9,7	**4203**	CH RB-18	.71	18,0				
x .74	x 18,8	**4204**	CH RB-27	1.06	26,9				
x 1.05	x 26,7	**4205**	CH RB-35	1.40	35,6				
Top Entry - Latch Gate									
x .14	x 3,6	**4206**	CH LB-13	.51	13,0	.22 x .61	5,6 x 15,5	.312	7,9
.44 x .33	11,1 x 8,4	**4207**	CH LB-18	.71	18,0				
x .69	x 17,5	**4208**	CH LB-27	1.06	27,0				
x 1.00	x 25,4	**4209**	CH LB-35	1.38	35,0				
Side Entry - Regular Gate*									
x .33	x 8,3	**4220**	CH RB-13-90	.20	5,1	.37 x .50	9,5 x 12,7	.157	4,0
.11 x .49	2,8 x 12,5	**4221**	CH RB-17-90	.20	5,1	.37 x .67	9,5 x 17,0		

Standard color natural. Flame retardant UL 94V-0 material available, consult Heyco. *For Panet thickness up to .161˝ (4,1 mm)


Material	Nylon 6/6
Flammability Rating	94V-2
Temperature Range	Nylon: 32°F (0°C) to 185°F (85°C)

Adhesives*
Rubber Adhesive 50°F (10°C) to 155°F (68°C)
Acrylic Adhesive 10°F (-12°C) to 180°F (82°C)
VHB Adhesive -40°F (-40°C) to 194°F (90°C)


*Low temperature reflects minimum application temperature for adhesives




- Gather and route cables.
- Part Description Key: CH RB-X, where X = Overall Height (mm).



Top Entry Regular Gate



Top Entry Latch Gate



Side Entry Regular Gate