chanhvinh.com



Heyco® Foam Washers

Will Fit These Electrical Fitting NPT Trade Sizes	PART NO. Black	DESCRIPTION	PART DIMENSIONS A Inside Dia. in.	A Inside Dia. mm.	B Outside Dia. in.	B Outside Dia. mm.	C Thickness in.	C Thickness mm.
.125˝ (3,2 mm) Thickness								
1/4	**1970**	HFW 500	.500	12,7	.820	20,8	.125	3,2
-	**1971**	HFW 625	.625	15,9	.940	23,9		
	1972	HFW 750	.750	19,1	1.060	26,9		
1/2	**1973**	HFW 875	.875	22,2	1.185	30,1		
	1980	HFW 875 DD*						
-	**1974**	HFW 1000	1.000	25,4	1.390	35,3		
3/4	**1982**	HFW 1125	1.125	28,6	1.515	38,5		
	1981	HFW 1125 DD*						
-	**1983**	HFW 1250	1.250	31,8	1.875	47,6		
1	**1998**	HFW 1375	1.375	34,9	2.000	50,8		
.190˝ (4,8 mm) Thickness								
1/4	**1975**	HFW 1/4	.480	12,2	.860	21,8	.190	4,6
1/2	**1977**	HFW 1/2	.840	21,3	1.200	30,5		
3/4	**1978**	HFW 3/4	1.050	26,7	1.500	38,1		
1	**1979**	HFW 1	1.300	33,0	1.700	43,2		

Standard color black.
*Feature flats across ID: PN 1980 - .750˝ (19,1 mm), PN 1981 - .965˝ (24,5 mm)

- For use with Heyco-Flex fittings.
- Provide additional degree of protection for a variety of fittings.
- Compensate for non-ideal mounting surfaces in application.



Heyco® Thermoplastic Rubber O-Rings

Will Fit These Electrical Fitting NPT Trade Sizes	PART NO. Black	DESCRIPTION	PART DIMENSIONS A Inside Dia. in.	A Inside Dia. mm.	B Outside Dia. in.	B Outside Dia. mm.	C Thickness in.	C Thickness mm.
1/2	**1995**	ROR 1/2	.860	21,8	1.140	28,9	.140	3,5
3/4	**1996**	ROR 3/4	1.050	26,7	1.320	33,5		
1	**1997**	ROR 1	1.300	32,9	1.570	39,9		

Standard color black.
Consult Heyco for 1-1/4˝, 1-1/2˝ and 2˝ Electrical Trade and other sizes.

- For use with Heyco-Flex fittings mounted in non-threaded holes.
- Liquid tight, dust tight and oil tight at enclosure.
- Suitable for wet locations requiring a separate gasket between the fitting and enclosure.
- Resistant to petroleum oil, mineral oil and grease, diesel fuel, weak acids, alkali, and salt solutions.

	HFW	ROR
Material	EPDM	Buna-N (Nitrile Rubber NBR)
Temperature Range	-4°F (-20°C) to 140°F (60°C)	-30°F (-34°C) to 212°F (100°C)

Quick Specs