chanhvinh.com






# Heyco-Flex™ Mounting Brackets

- For mounting Heyco-Flex Conduit or Tubing securely into place, vertically or horizontally. See pages 2-1, 2-7, and 2-8.
- Only fingertip pressure is required to snap conduit or tubing into bracket.
- Low profile design for space savings and pleasing appearance.
- Recommended distance between brackets at intervals not greater than 3 feet (1m) as required by Article 351-27 of 1996 NEC.
- Use one standard #10 (4-5M) screw for attaching bracket to panel (screw not included).
- Resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.

| FITS CONDUIT/ TUBING SIZE | PART NO. Black | PART NO. Gray | DESCRIPTION | PART DIMENSIONS A Inside Dia. in. | A mm. | B Length in. | B mm. | C Height in. | C mm. | D Outside Dia. in. | D mm. | E Width in. | E mm. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 3/8 | **1025** | **1026** | HFB 3/8 | .66 | 16,9 | .91 | 23,2 | .72 | 18,2 | .90 | 22,9 | .75 | 19,1 |
| 1/2 | **1027** | **1028** | HFB 1/2 | .79 | 20,0 | 1.07 | 27,3 | .71 | 18,0 | 1.06 | 26,8 | | |
| 3/4 | **1029** | **1030** | HFB 3/4 | 1.05 | 26,7 | 1.27 | 32,2 | .67 | 17,0 | 1.31 | 33,2 | | |
| 1 | **1031** | **1032** | HFB 1 | 1.24 | 31,5 | 1.52 | 38,6 | .84 | 21,3 | 1.53 | 38,9 | | |

Standard color black or gray.







# Heyco® Sealing Washers

- For use with Heyco-Flex fittings.
- Liquid tight, dust tight, and oil tight at enclosure.
- Suitable for wet locations requiring a separate gasket between the box and fitting.
- Also suitable for other panel sealing applications.
- Easy to install since washers seal off on the perimeter, not on the connector threads.
- Special double sealing ridges compensate for minor unevenness at enclosure.

| Will Fit These Electrical Fitting NPT Trade Sizes | PART NO. Black | DESCRIPTION | PART DIMENSIONS A Inside Diameter in. | A mm. | B Outside Diameter in. | B mm. | C Thickness in. | C mm. |
|---|---|---|---|---|---|---|---|---|
| 1/4 | **3258** | SW 1/4 | .54 | 13,7 | .80 | 20,2 | .13 | 3,2 |
| 3/8 | **3259** | SW 3/8 | .67 | 17,0 | 1.01 | 25,5 | | |
| 1/2 | **3260** | SW 1/2 | .85 | 21,6 | 1.24 | 31,5 | | |
| 3/4 | **3261** | SW 3/4 | 1.03 | 26,2 | 1.50 | 38,1 | .14 | 3,4 |
| 1 | **3262** | SW 1 | 1.28 | 32,5 | 1.77 | 45,0 | .18 | 4,6 |
| 1-1/4 | **3264** | SW 1-1/4 | 1.66 | 42,2 | 2.16 | 54,8 | .16 | 4,1 |
| 1-1/2 | **3265** | SW 1-1/2 | 1.86 | 47,2 | 2.44 | 62,0 | | |
| 2 | **3257** | SW 2 | 2.32 | 58,9 | 2.93 | 74,4 | .18 | 4,6 |

Standard color black.




Quick Specs

| | | |
|---|---|---|
| Material | HFB - Nylon 6/6 | SW - Thermoplastic Elastomer |
| Flammability Rating | HFB - 94V-2 | SW - 94V-0 |
| Temperature Range | -22°F (-30°C) to 221°F (105°C) | |



1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com