chanhvinh.com




Heyco® Original Strain Relief Bushings

Right Angle for Round Cables


- Provides the same protection for your power supply cable as the straight-thru type AND...
- **Exits the cable flush against the panel**, saving space and directing the cable parallel to the panel.
- Overcomes space limitations and acts as a back or bottom bumper.
- See page 4-38 for corresponding **Mounting Hole Plugs** which can be used to fill blank/unused Mounting Holes and thus allow for a single panel design for multiple applications.
- Consult Heyco for other wire types and sizes.
- See pages 4-27 & 4-28 for SR assembly tools.
- For Double D Mounting Hole Punches, see page 4-30.

	WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.		DESC.	PART DIMENSIONS				Mounting Hole Plug
	UL Type	AWG/ Conductors	Approximate Size		A Mounting Hole Dia.		B To Prevent Rotation		Finished Fit Panel Thickness*					C HEAD LENGTH		D BODY LENGTH		
			in.	mm.	in.	mm.	in.	mm.	in.	mm.	Black	White		in.	mm.	in.	mm.	PART NO.
	SV & SVT	18/2	.250	6,4	.500	12,7	.450	11,4	.100	2,5	**1374**	**1375**	SR 15-1	.39	9,9	.69	17,5	2491
		18/3	.265	6,7	.500-.515	12,7-13,1												
	HPD	18/2	.270	6,9	.500	12,7												
		16/2	.290	7,4	.500-.515	12,7-13,1												
	SJ, SJO & SJT	18/2	.300	7,6	.625	15,9	.550	14,0	.125	3,2	**1320**	**1321**	SR 10-2	.56	14,3	.97	24,6	2497
		16/2	.325	8,3														
		18/3	.330	8,4														
	SJ	16/3	.330	8,4														
	SJ, SJO & SJT	16/2	.325	8,3	.625	15,9	.550	14,0	.125	3,2	**1327**	**1328**	SR 11-2	.56	14,3	.97	24,6	2497
		18/3	.330	8,4														
		16/3	.335	9,0														
	SJT	18/4	.360	9,1	.750	19,0	.660	16,8	.125	3,2	**1397**	**1398**	SR 17-2	.64	16,3	1.09	27,7	2503
	SJT & SJTO	14/3	.370	9,4														
	SJ & ST	18/2	.390	9,9														
		18/3	.405	10,3														
		16/2	.405	10,3														
		16/3	.430	10,9	.750-.781	19,0-19,8												
NEW!	S	14/2	.530	13,5	.875	22,2	.815	20,7	.125	3,2	**1401**	**1402**	SR 18-2	.84	21,4	1.36	34,5	2509
		14/3	.560	14,2														

Standard color black. Consult Heyco for other colors.
*Maximum Panel Thickness. Part has additional clearance. Consult Heyco for your Custom Finished Fit Panel Thickness.



MOUNTING HOLES



Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E15331
	Certified by the Canadian Standards Association File 8919
Flammability Rating	94V-2
Temperature Range	-.04°F (-18°C) to 221°F (105°C)

Quick Specs

1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com