chanhvinh.com

Heyco® PG and Metric Threaded Plugs

Round Head with Slot




Plastic

THREAD TYPE/SIZE	PART NO. Gray	PART NO. Black	DESCRIPTION	PART DIMENSIONS A Head Diameter in.	A Head Diameter mm.	B Overall Height in.	B Overall Height mm.
PG Threads – Polystyrene							
PG 7	**3405**	**3405B**	TP PG 7	.59	15,0	.32	8,0
PG 9	**3407**	**3407B**	TP PG 9	.75	19,0	.37	9,5
PG 11	**3402**	**3402B**	TP PG 11	.87	22,0		
PG 13	**3412**	**3412B**	TP PG 13	.98	25,0	.39	10,0
PG 16	**3414**	**3414B**	TP PG 16	1.06	27,0		
PG 21	**3416**	**3416B**	TP PG 21	1.30	33,0	.47	12,0
PG 29	**3418**	**3418B**	TP PG 29	1.73	44,0		
PG 36	**3415**	**3415B**	TP PG 36	2.17	55,0	.55	14,0
PG 42	**3400**	**3400B**	TP PG 42	2.44	62,0		
PG 48	**3417**	**3417B**	TP PG 48	2.72	69,0	.63	16,0
Metric Threads – Nylon							
M12 x 1,5	**3403**	**3403B**	TP M12	.59	15,0		
M16 x 1,5	**3404**	**3404B**	TP M16	.79	20,0	.41	10,5
M20 x 1,5	**3406**	**3406B**	TP M20	.95	24,0		
M25 x 1,5	**3408**	**3408B**	TP M25	1.18	30,0	.51	13,0
M32 x 1,5	**3409**	**3409B**	TP M32	1.48	37,0	.53	13,5
M40 x 1,5	**3410**	**3410B**	TP M40	1.81	46,0	.55	14,0
M50 x 1,5	**3411**	**3411B**	TP M50	2.20	56,0	.63	16,0
M63 x 1,5	**3413**	**3413B**	TP M63	2.76	70,0	.71	18,0

Standard color gray and black. Consult Heyco for other colors.

- **Used to close unneeded PG and Metric threaded holes** when other threaded accessories may be added at a later time.
- Designed with slot for screwdriver installation
- For PG Threaded specifications, see page 3-57.
- For Heyco Snap-In Metric Dome Plugs, see page 6-30.
- Nickel-Plated Brass Plugs are ideal where extra durability and strength are needed such as harsh environmental conditions.
- Nickel-Plated Brass Plugs include NBR O-ring




Nickel-Plated Brass




THREAD TYPE/SIZE	PART NO.	DESCRIPTION	PART DIMENSIONS A Head Diameter in.	A Head Diameter mm.	B Overall Height in.	B Overall Height mm.
PG Threads						
PG 7	**13405**	BRASS TP PG 7	.55	14,0	.31	8,0
PG 9	**13407**	BRASS TP PG 9	.67	17,0	.35	9,0
PG 11	**13402**	BRASS TP PG 11	.79	20,0		
PG 13	**13412**	BRASS TP PG 13	.87	22,0	.37	9,5
PG 16	**13414**	BRASS TP PG 16	.94	24,0		
PG 21	**13416**	BRASS TP PG 21	1.18	30,0	.43	11,0
PG 29	**13418**	BRASS TP PG 29	1.54	39,0	.47	12,0
PG 36	**13415**	BRASS TP PG 36	1.97	50,0	.59	15,0
PG 42	**13400**	BRASS TP PG 42	2.36	60,0	.63	16,0
PG 48	**13417**	BRASS TP PG 48	2.56	65,0		
Metric Threads						
M6 x1.0	**13397**	BRASS TP M6*	.35	9,0		
M8 x1.25	**13398**	BRASS TP M8*	.39	10,0		
M10 x1.5	**13399**	BRASS TP M10*	.47	12,0	.31	8,0
M12 x 1,5	**13403**	BRASS TP M12	.55	14,0		
M16 x 1,5	**13404**	BRASS TP M16	.75	19,0		
M20 x 1,5	**13406**	BRASS TP M20	.94	24,0	.35	9,0
M25 x 1,5	**13408**	BRASS TP M25	1.10	28,0	.43	11,0
M32 x 1,5	**13409**	BRASS TP M32	1.38	35,0	.47	12,0
M40 x 1,5	**13410**	BRASS TP M40	1.77	45,0	.55	14,0
M50 x 1,5	**13411**	BRASS TP M50	2.17	55,0	.59	15,0
M63 x 1,5	**13413**	BRASS TP M63	2.76	70,0	.63	16,0

* Metric course-pitch threads

PG



Metric



	Plastic TP Plugs	Brass TP Plugs
Material	Nylon 6/6 or Impact Resistant Polystrene	Nickel-Plated Brass with an NBR O-ring
Flammability Rating	94V-2	
Temperature Range	-4° F (-20° C) to 176° F (80° C)	-40°F (-40° C) to 212°F (100°C)
IP Rating	IP 50	IP 68

Quick Specs