chanhvinh.com

HIRSCHMANN® Test & Measurement
A BRAND OF SKS


SKS® SKS Kontakttechnik GmbH

Measuring leads

MAL S GG-B 200/2,5



CE

Product	MAL S GG-B 200/2,5
description	Safety adapter test lead according to IEC 61010 with 4 mm safety plug straight outlet and 4 mm saftey socket on the other end. Highly flexible, double insulated stranded lead, shatter-proof grip sleeve. Built in color indicator for easy indentification of insulation damages.
operating instruction	BA453
article-no. / *colour	9340471xx 00 black · 01 red · 02 blue · 03 yellow · 04 green · 88 yellow green Ni
drawing	
	
technical data	
rated voltage(1)	AC/DC 1000 V
measurement cat. acc. to IEC 61010	CAT III
rated current(1) (consider derating curve)	32 A
material plug	brass, nickel plated
material socket	brass, nickel plated
housing material	PA
temperature range acc. To IEC61010(2)	-15 °C to +70 °C
inflammability class acc. to UL 94 (only valid for basic material of housing)	V-2
cable length	200 cm
conductor size	2,5 mm²
cable material	PVC

4 mm safety system

chanhvinh.com

HIRSCHMANN® Test & Measurement
A BRAND OF SKS

SKS® SKS Kontakttechnik GmbH

[1] for normal environmental conditions 5°C to 40°C
[2] contact the manufacturer for applications at deviating temperature ranges
stand: 13.06.2022