chanhvinh.com

HIRSCHMANN® Test & Measurement
A BRAND OF SKS

SKS Kontakttechnik GmbH

Measuring leads

MLS WS 25/1



CE

Product	MLS WS 25/1
description	Safety measuring lead to IEC 61010 standard, at either end 4 mm diameter safety connector with onward connection capability (4mm socket). Nickel-plated copper beryllium contact spring. Highly flexible, double insulated stranded lead, shatter-proof grip sleeve and lead. Built in color indicator for easy indentification of insulation damages.
operating instruction	BA452
article-no. / *colour	9340671xx 00 black · 01 red · 02 blue · 03 yellow · 04 green Ni
drawing	
	
technical data	
rated voltage	AC/DC 1000 V
measurement cat. acc. to IEC 61010	CAT II
rated current (consider derating curve)	16 A
material plug	brass, nickel plated
housing material	PA
temperature range acc. To IEC61010(1)	-15 °C to +70 °C
inflammability class acc. to UL 94 (only valid for basic material of housing)	V-2
cable length	25 cm

4 mm safety system

chanhvinh.com

conductor size	1 mm²
cable material	PVC

(1) contact the manufacturer for applications at deviating temperature ranges
stand: 21.06.2022

stand: 21.06.2022