chanhvinh.com

DATA SHEET

SENCITY® Rail Low Profile Antenna with GPS

1399.99.0032

Properties

- Railway rooftop antenna for 2G/3G/4G cellular and Wi-Fi 4/Wi-Fi 6 bands
- Multiple Antenna installations support Cellular and Wi-Fi MIMO
- Includes embedded passive GPS antenna (requires separate LNA such as 86010142)
- Rugged design, meets EN 50155 Railway Standard
- Fire retardant according to EN 45545-2
- Extremely low profile (40mm)

Electrical data				
	Band 1	**Band 2**	**Band 3**	**Band 4**
Name				
Frequency	790 MHz ... 806 MHz	806 MHz ... 870 MHz	870 MHz ... 960 MHz	1350 MHz ... 2700 MHz
Impedance	50 Ω	50 Ω	50 Ω	50 Ω
VSWR	2.2	1.8	1.5	2
Gain	5 dBi	5 dBi	5 dBi	5 dBi
Ambient Temperature	25 °C	25 °C	25 °C	25 °C
Composite Power max	200 W	192 W	183 W	123 W

	Band 5	**Band 6**
Name		GPS
Frequency	4900 MHz ... 6425 MHz	1574.397 MHz ... 1576.443 MHz
Impedance	50 Ω	50 Ω
VSWR	2.1	1.5
Gain	8 dBi	
Ambient Temperature	25 °C	
Composite Power max	67 W	

HUBER+SUHNER

chanhvinh.com

SENCITY® Rail Low Profile Antenna with GPS

1399.99.0032

Electrical remarks	
Remarks	Indicated VSWR values are valid for a metallic ground plane of 0.2 x 0.2m or larger. Indicated gain values will be achieved on a metallic ground plane of 1 x 1 m or larger.The tolerance of the VSWR values is 0.5dB
	High-voltage-protection: no voltage on RF port, if catenary line touches antenna (EN 50124-1, 24 kVAC/1min). High-current-protection: Designed acc. to UIC 533, DC-grounded antenna element protection against lightning and short circuit with catenary lines (EN50388, EN 50122-1, 40kA/0.1sec)

Ports	Port 1	Port 2
Connector	N, jack (female)	TNC, plug (male)
Polarization	vertical	circular right
DC grounded	Yes	No

Connections	Port 1	Port 2
Band 1	✓	
Band 2	✓	
Band 3	✓	
Band 4	✓	
Band 5	✓	
Band 6		✓

Mechanical data	
Weight	0.527 kg
Dimensions	40 mm x 100 mm x 145 mm (Height x Width x Depth)
Windload	Wind Speed survival: 500 km/h
Remarks	Corrosion Low corrosion design acc. to MIL-F-14072(E). Mounting Shall be installed in longitudinal position to the wind/driving direction. Suitable for installation on high speed trains with a maximum speed of 500 km/hr. 4x composite sealing washers included for silicone-free sealing of the mounting screws

Material data	
Radome material	PC (Polycarbonate)
Radome colour	RAL 7043 (dark grey)
Back plate/base plate material	Aluminum
Back plate/base plate plating	Passivated (Plating)
Back plate/base plate colour	Grey

Environmental data	
Operation temperature	-40 °C ... 85 °C
Storage temperature	-55 °C ... 85 °C
Environment (application)	Outdoor
Ingress protection (IP Rating)	Mated / IP67, IP69

chanhvinh.com

DATA SHEET

SENCITY® Rail Low Profile Antenna with GPS

1399.99.0032

Environmental data	
Flammability rating	EN 45545-2
Solar radiation	DIN 75220

Environmental remarks
Environmental tests: EN 50155:2022

Additional Information
This product meets the Deutsche Bahn specifications for rolling stock equipment.

Antenna accessories		
Item description	Item number	Product name
9091.99.0257	85068234	SENCITY® Rail - M10 sealing washer kit
9090.99.0062	84098894	SENCITY® Rail mounting plate
86010142	84460305	SENCITY® Low Noise Amplifier GNSS (GPS, GLONASS, BeiDou, Galileo)

Antenna accessories remarks
9090.99.0062 Sencity Rail Mounting plate xxxCustomer specificxxx 9091.99.0257 Sencity Rail - M10 sealing washer kit

Ordering information		
Item description	Item number	Product name
1399.99.0032	84076252	SENCITY® Rail Low Profile Antenna with GPS

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3217 / Date of publication: 07.10.2026 / uncontrolled copy

HUBER+SUHNER