chanhvinh.com



DATA SHEET

# COAXIAL ADAPTER, BNC - A, X Ohm, plug / jack (male / female)

33_BNC-A-0-1/0--_-

## Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



| Product configuration | | |
|---|---|---|
| Interface type | Gender | Standard |
| BNC | plug (male) | IEC 61169-8_MIL-STD-348A/301_CECC 22120 |
| A | jack (female) | HUBER+SUHNER-A |

| Interface and material data | | |
|---|---|---|
| BNC | | |
| **Piece parts** | **Material** | **Plating** |
| Centre contact | Brass | Silver Plating |
| Outer conductor | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |
| Coupling nut | Brass | SUCOPLATE (R) Plating |
| Gasket | VMQ (Silicone rubber) | |
| A | | |
| **Piece parts** | **Material** | **Plating** |
| Centre contact | Brass | Silver Plating |
| Outer conductor | Brass | Silver Plating |
| Body | Bronze | |
| Insulator | PFA / PTFE | |

| Electrical data | |
|---|---|
| Interface frequency | 4 GHz |

| Mechanical data | |
|---|---|
| Weight | 0.0192 kg |
| Mating cycles | 500 |



HUBER+SUHNER

chanhvinh.com



# COAXIAL ADAPTER, BNC - A, X Ohm, plug / jack (male / female)

33_BNC-A-0-1/0--_-

| Environmental data | |
|---|---|
| Operation temperature | -20 °C ... 85 °C |

| Material compliance | | | |
|---|---|---|---|
| Item number | Directive / Regulation | Rating | Exemptions / Details |
| 22540589 | RoHS 2011/65/EU and (EU) 2015/863 | Compliant with exemption | 6c |

| Ordering Information Table | | |
|---|---|---|
| Item number | Item description | Packaging type |
| 22540589 | 33_BNC-A-0-1/0--_-E | Single |

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2252 / Date of publication: 12.07.2025 / uncontrolled copy