chanhvinh.com



DATA SHEET

# COAXIAL ADAPTER, UHF - BNC, X Ohm, plug / jack (male / female)

33_UHF-BNC-0-1/032_-

## Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



| Product configuration | | |
|---|---|---|
| Interface type | Gender | Standard |
| UHF | plug (male) | IEC 60169-12 |
| BNC | jack (female) | IEC 61169-8_MIL-STD-348A/301_CECC 22120 |

| Interface and material data | | |
|---|---|---|
| UHF | | |
| **Piece parts** | **Material** | **Plating** |
| Centre contact | Bronze | Silver Plating |
| Outer conductor | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PP (Polypropylene) | |
| Coupling nut | Brass | Nickel Plating |
| BNC | | |
| **Piece parts** | **Material** | **Plating** |
| Centre contact | Bronze | Silver Plating |
| Outer conductor | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

| Electrical data | |
|---|---|
| Interface frequency | 0.2 GHz |

| Mechanical data | |
|---|---|
| Weight | 0.0228 kg |
| Mating cycles | 500 |



HUBER+SUHNER

chanhvinh.com



# COAXIAL ADAPTER, UHF - BNC, X Ohm, plug / jack (male / female)

33_UHF-BNC-0-1/032_-

| Environmental data | |
|---|---|
| Operation temperature | -25 °C ... 100 °C |

| Material compliance | | | |
|---|---|---|---|
| Item number | Directive / Regulation | Rating | Exemptions / Details |
| 23013454 | RoHS 2011/65/EU and (EU) 2015/863 | Compliant with exemption | 6c |

| Ordering Information Table | | |
|---|---|---|
| Item number | Item description | Packaging type |
| 23013454 | 33_UHF-BNC-0-1/032_-E | Single |

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2135 / Date of publication: 12.07.2025 / uncontrolled copy