chanhvinh.com

icotek

KEL 24
Cable entry frames





Split inserts



Surrounding tongue
and groove connection

Product description

The KEL-24 matches exactly the cut-out dimensions of 24-pole standard industrial connectors.

The split insert matching the cable diameter is placed around the cable and inserted into the cable entry frame.

Either a cut out of 36mm or 46mm tall can be chosen depending on the cables being routed. This flexibility is perfect for pre-terminated cables.

Advantages





- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and inserts
- Strain relief according DIN EN 50262

Specification

Material	**Polyamide**
Flame class	**UL-94 Vo, self-extinguishing**
Protection class	**IP 54, with gasket and correct selection of the cable inserts**
Temperature	**- 40°C to + 140°C (static)**
Properties	**halogen-free, silicone-free**
Cut-out dimensions	**36 x 112 mm / page 106**

Accessories

KT Cable inserts	Page 20 | 24
KEL-SNAP SNAP frames	Page 15
KEL-EMC Cable collector	Page 82 | 84
KDR2 | KDR Base plates	Page 90 | 93
FP Flanged plates	Page 94 | 97
MP Module plates	Page 98

Description	Type	Order No.	Inserts KT small | large	PU
	**KEL 24 | 10**	**42241**	**10 | -**	**10**
	**KEL 24 | 7**	**42247**	**6 | 1**	**10**
	**KEL 24 | 5**	**42248**	**5 | -**	**10**
	**KEL 24 | 4**	**42244**	**2 | 2**	**10**

chanhvinh.com

icotek

KEL 16
Cable entry frames







Surrounding tongue and groove connection



Split inserts



Type	Order No.	Inserts KT small | large	PU	Description
KEL 16 | 8	42168	8 | -	10	
KEL 16 | 5	42165	4 | 1	10	
KEL 16 | 4	42164	4 | -	10	
KEL 16 | 2	42162	- | 2	10	

Product description

The KEL-16 matches exactly the cut-out dimensions of 16-pole standard industrial connectors.

The split insert matching the cable diameter is placed around the cable and inserted into the cable entry frame.

Either a cut out of 36mm or 46mm tall can be chosen depending on the cables being routed. This flexibility is perfect for pre-terminated cables.

Advantages

- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and inserts
- Strain relief according DIN EN 50262

Specification

Material	**Polyamide**
Flame class	**UL-94 V0, self-extinguishing**
Protection class	**IP 54, with gasket and correct selection of the cable inserts**
Temperature	**- 40°C to + 140°C (static)**
Properties	**halogen-free, silicone-free**
Cut-out dimensions	**36 x 86 mm / page 106**

Accessories

KT Cable inserts	Page 20 | 24
KEL-SNAP SNAP frames	Page 15
KEL-EMC Cable collector	Page 82 | 84
KDR Base plates	Page 92 | 93

chanhvinh.com

icotek

KEL 10
Cable entry frames





Split inserts



Surrounding tongue
and groove connection

Product description

The KEL-10 matches exactly the cut-out dimensions of 10-pole standard industrial connectors.

The split insert matching the cable diameter is placed around the cable and inserted into the cable entry frame.

Either a cut out of 36mm or 46mm tall can be chosen depending on the cables being routed. This flexibility is perfect for pre-terminated cables.

Advantages



- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- High packing density, wide variety of frames and inserts
- Strain relief according DIN EN 50262

Specificationen

Material	**Polyamide**
Flame class	**UL-94 V0, self-extinguishing**
Protection class	**IP 54, with gasket and correct selection of the cable inserts**
Temperature	**- 40°C to + 140°C (static)**
Properties	**halogen-free, silicone-free**
Cut-out dimensions	**36 x 65 mm / page 106**

Accessories

KT Cable inserts	Page 20 | 24
KEL-SNAP SNAP frames	Page 15
KEL-EMC Cable collector	Page 83 | 84

Descripton	Type	Order No.	Inserts KT small | large	PU
	**KEL 10 | 6**	**42216**	**6 | -**	**10**
	**KEL 10 | 3**	**42212**	**2 | 1**	**10**

chanhvinh.com

KEL - B
Cable entry frames





Surrounding tongue and groove connection



Split inserts



Type	Order No.	Inserts KT small | large	PU	Description
KEL - B4	42204	4 | -	10	
KEL - B1	42206	- | 1	10	

Product description

The KEL-B matches exactly the cut-out dimensions of 46 x 46 mm measuring instruments.

The split insert matching the cable diameter is placed around the cable and inserted into the cable entry frame.

For routing cables and conduits up to 34 mm diameter.

Advantages

- Warranty of pre-terminated cables remains
- Retrofitting and maintenance can be carried out easily and quickly
- Space saving shape
- Small cut-out, high packing density
- Strain relief according DIN EN 50262

Specification

Material	**Polyamide**
Flame class	**UL-94 Vo, self-extinguishing**
Protection class	**IP 54, with gasket and correct selection of the cable inserts**
Temperature	**- 40°C to + 140°C (static)**
Properties	**halogen-free, silicone-free**
Cut-out dimensions	**46 x 46 mm / page 106**

Accessories

KT Cable inserts	Page 20 | 24
KEL-SNAP SNAP frames	Page 15
KEL-EMC Cable collector	Page 83 | 84