
chanhvinh.com

IE5453

Inductive sensor

IEB3002BBPKG/V4A/ZH

customer-specific



Product characteristics		
Electrical design		PNP
Output function		normally open
Sensing range	[mm]	2
Housing		threaded type
Dimensions	[mm]	M8 x 1 / L = 30
Electrical data		
Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 15
Protection class		III
Reverse polarity protection		yes
Outputs		
Electrical design		PNP
Output function		normally open
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	100
Switching frequency DC	[Hz]	1500
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes
Detection zone		
Sensing range	[mm]	2
Real sensing range Sr	[mm]	2 ± 10 %
Operating distance	[mm]	0...1.62
Accuracy / deviations		
Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	1...15
Switch point drift	[% of Sr]	-10...10

chanhvinh.com

IE5453

Inductive sensor


IEB3002BBPKG/V4A/ZH

Operating conditions			
Ambient temperature	[°C]	10...85	
Protection		IP 67	
Tests / approvals			
EMC		EN 61000-4-2 ESD	4 kV CD / 8 kV AD
		EN 61000-4-3 HF radiated	10 V/m
		EN 61000-4-4 Burst	2 kV
		EN 61000-4-6 HF conducted	10 V
		EN 55011	class B
Mechanical data			
Weight	[g]	47.6	
Housing		threaded type	
Mounting		flush mountable	
Dimensions	[mm]	M8 x 1 / L = 30	
Thread designation		M8 x 1	
Materials		housing: stainless steel (1.4404 / 316L); sensing face: LCP	
Tightening torque	[Nm]	A = 5 mm: 2 Nm; B: 3 Nm	
Displays / operating elements			
Display		switching status	1 x LED, yellow
Accessories			
Items supplied		lock nuts: 2	
Remarks			
Notes		customer-specific	
Pack quantity		1 pcs.	

Electrical connection

Cable: 2 m, PUR; 3 x 0.14 mm²

Connection



	Core colours
BK	black
BN	brown
BU	blue

chanhvinh.com

IE5453

Inductive sensor

IEB3002BBPKG/V4A/ZH

Diagrams and graphs

Installation

