
chanhvinh.com

MX5000

Speed sensor

MXD31,8 ANOG/AMP/H



Product characteristics		
Electrical design		NPN
Sensing range	[mm]	1.7; (Using toothed wheels with a different modulus has an influence on the sensing range and the phase position.)
Dimensions	[mm]	Ø 15 / L = 70
Electrical data		
Operating voltage	[V]	7...30 DC
Current consumption	[mA]	< 30
Protection class		III
Reverse polarity protection		no
Outputs		
Electrical design		NPN
Permanent current rating of switching output DC	[mA]	50
Switching frequency DC	[Hz]	2...15000
Short-circuit protection		no
Detection zone		
Sensing range	[mm]	1.7; (Using toothed wheels with a different modulus has an influence on the sensing range and the phase position.)
Operating distance	[mm]	1
Operating conditions		
Ambient temperature	[°C]	-32...140
Ambient temperature	[°C]	125
Note on ambient temperature		for the plug area
Protection		IP 67; IP 69K; (plug: IP 54)
Tests / approvals		
EMC		EN 61000-4-2 — 4 kV CD / 8 kV AD
		EN 61000-4-3 — 10 V/m
		EN 61000-4-4 — 2 kV
		EN 61000-4-6 — 10 V
		EN 61000-4-8 — 30 A/m
Shock resistance		DIN EN 60068-2-27 — 30 g 11 ms half-sine; 3 shocks each in every direction of the 3 coordinate axes

chanhvinh.com

MX5000

Speed sensor

MXD31,8 ANOG/AMP/H

Salt spray test		EN 60068/2-11	96 h 5 % NaCl bei 25 °C
MTTF	[years]	2247	

Mechanical data


Weight	[g]	23.5
Dimensions	[mm]	Ø 15 / L = 70
Materials		socket: brass; housing: PA; O-ring: FKM
Tightening torque	[Nm]	7
Toothed wheel module	[mm]	1.25
Installation length	[mm]	45

Remarks

Pack quantity	1 pcs.

Electrical connection

Connection




A: Pulse output
B: Pulse output

Connector: 1 x AMP-Junior Timer (282 192-1)

Diagrams and graphs

switching signals



phase shift 90° +/- 20°

pulse/pause ratio 50 % +/- 10 %

Using toothed wheels with a different modulus has an influence on the sensing range and the phase position.