
chanhvinh.com


Silicon Schottky Diode

- General-purpose diode for high-speed switching
- Circuit protection
- Voltage clamping
- High-level detecting and mixing
- BAS70-04S: For orientation in reel see package information below
- Pb-free (RoHS compliant) package
- Qualified according AEC Q101[1)]




AEC Qualified RoHS


BAS170W
BAS70-02L
BAS70-02W
BAS70-02V




BAS70




BAS70-04
BAS70-04W




BAS70-04S




BAS70-05
BAS70-05W



BAS70-06
BAS70-06W



BAS70-07
BAS70-07W



[1]BAS70-02L is not qualified according AEC Q101

chanhvinh.com

Type	Package	Configuration	L_S(nH)	Marking
BAS170W	SOD323	single	1.8	white 7
BAS70	SOT23	single	1.8	73s
BAS70-02L	TSLP-2-1	single, leadless	0.4	F
BAS70-02V	SC79	single	0.6	c
BAS70-02W*	SCD80	single	0.6	73
BAS70-04	SOT23	series	1.8	74s
BAS70-04S	SOT363	dual series	1.6	74s
BAS70-04W	SOT323	series	1.4	74s
BAS70-05	SOT23	common cathode	1.8	75s
BAS70-05W	SOT323	common cathode	1.4	75s
BAS70-06	SOT23	common anode	1.8	76s
BAS70-06W	SOT323	common anode	1.4	76s
BAS70-07	SOT143	parallel pair	2	77s
BAS70-07W	SOT343	parallel pair	1.8	77s

* Not for new design

Maximum Ratings at T_A = 25 °C, unless otherwise specified

Parameter	Symbol	Value	Unit
Diode reverse voltage	V_R	70	V
Forward current	I_F	70	mA
Non-repetitive peak surge forward current $t \leq$ 10ms	I_{FSM}	100	
Total power dissipation	P_{tot}		mW
BAS70, BAS70-07, $T_S \leq$ 72 °C		250	
BAS70-02L, $T_S \leq$ 117 °C		250	
BAS70-02W, -02V, $T_S \leq$ 107 °C		250	
BAS70-04, BAS70-06, $T_S \leq$ 48 °C		250	
BAS70-04S/W/-06W, BAS170W, $T_S \leq$ 97 °C		250	
BAS70-05, $T_S \leq$ 22 °C		250	
BAS70-05W, $T_S \leq$ 90 °C		250	
BAS70-07W, $T_S \leq$ 114 °C		250	
Junction temperature	T_J	150	°C
Operating temperature range	T_{op}	-55 ... 125	
Storage temperature	T_{Stg}	-55 ... 150	

chanhvinh.com

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point[1)]	R_{thJS}		K/W
BAS70, BAS70-07		≤ 310	
BAS70-02L		≤ 130	
BAS70-02W, -02V		≤ 170	
BAS70-04, BAS70-06		≤ 410	
BAS70-04S/W, BAS70-06W		≤ 210	
BAS70-05		≤ 510	
BAS70-05W		≤ 240	
BAS70-07W		≤ 145	
BAS170W		≤ 190	

Electrical Characteristics at T_A = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Breakdown voltage $I_{(BR)}$ = 10 µA	$V_{(BR)}$	70	-	-	V
Reverse current V_R = 50 V	I_R	-	-	0.1	µA
Forward voltage	V_F				mV
I_F = 1 mA		300	375	410	
I_F = 10 mA		600	705	750	
I_F = 15 mA		720	880	1000	
Forward voltage matching[2)] I_F = 10 mA	ΔV_F	-	-	20	

[1]For calculation of R_{thJA} please refer to Application Note AN077 (Thermal Resistance Calculation)

[2]ΔV_F is the difference between lowest and highest V_F in a multiple diode component.

chanhvinh.com


Electrical Characteristics at T_A = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
AC Characteristics					
Diode capacitance V_R = 0 , f = 1 MHz	C_T	-	1.5	2	pF
Forward resistance I_F = 10 mA, f = 10 kHz	r_f	-	34	-	Ω
Charge carrier life time I_F = 25 mA	τ_{rr}	-	-	100	ps

chanhvinh.com


Diode capacitance $C_T = f(V_R)$

f = 1MHz




Forward resistance $r_f = f(I_F)$

f = 10 kHz




Reverse current $I_R = f(V_R)$

T_A = Parameter




Forward current $I_F = f(V_F)$

T_A = Parameter




chanhvinh.com


Forward current $I_F = f(T_S)$
BAS70, BAS70-07




Forward current $I_F = f(T_S)$
BAS70-02L



Forward current $I_F = f(T_S)$
BAS70-02W, -02V




Forward current $I_F = f(T_S)$
BAS70-04, BAS70-06




chanhvinh.com


Forward current $I_F = f(T_S)$
BAS70-04S/W, BAS70-06W, BAS170W




Forward current $I_F = f(T_S)$
BAS70-05



Forward current $I_F = f(T_S)$
BAS70-05W




Forward current $I_F = f(T_S)$
BAS70-07W



chanhvinh.com


Forward current $I_F = f(T_S)$

BAS170W



Permissible Puls Load $R_{thJS} = f(t_p)$


BAS70



Permissible Pulse Load


$I_{Fmax}/I_{FDC} = f(t_p)$

BAS70



Permissible Puls Load $R_{thJS} = f(t_p)$

BAS70-02L




chanhvinh.com

Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f(t_p)$

BAS70-02L



Permissible Puls Load $R_{thJS} = f(t_p)$


BAS70-02W, -02V



Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f(t_p)$

BAS70-02W, -02V



Permissible Puls Load $R_{thJS} = f(t_p)$

BAS70-04, BAS70-06




chanhvinh.com

Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f(t_p)$

BAS70-04, BAS70-06



Permissible Puls Load $R_{thJS} = f(t_p)$


BAS70-04S



Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f(t_p)$

BAS70-04S



Permissible Puls Load $R_{thJS} = f(t_p)$

BAS70-04W, BAS70-06W




chanhvinh.com

Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f(t_p)$

BAS70-04W, BAS70-06W



Permissible Puls Load $R_{thJS} = f(t_p)$


BAS70-05



Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f(t_p)$

BAS70-05



Permissible Puls Load $R_{thJS} = f(t_p)$

BAS70-05W




chanhvinh.com

Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f(t_p)$

BAS70-05W



Permissible Puls Load $R_{thJS} = f(t_p)$


BAS70-07W



Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f(t_p)$

BAS70-07W



Permissible Puls Load $R_{thJS} = f(t_p)$

BAS170W




chanhvinh.com

Permissible Pulse Load


$I_{Fmax}/ I_{FDC} = f (t_p)$

BAS170W




chanhvinh.com


Package Outline



Foot Print




Marking Layout (Example)




Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø180 mm = 8.000 Pieces/Reel (2 mm Pitch)
Reel ø330 mm = 10.000 Pieces/Reel




chanhvinh.com


Package Outline



Foot Print




Marking Layout (Example)



Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø180 mm = 8.000 Pieces/Reel (2 mm Pitch)
Reel ø330 mm = 10.000 Pieces/Reel



chanhvinh.com


Date Code marking for discrete packages with one digit (SCD80, SC79, SC75[1]) CES-Code

Month	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014
01	a	p	A	P	a	p	A	P	a	p	A	P
02	b	q	B	Q	b	q	B	Q	b	q	B	Q
03	c	r	C	R	c	r	C	R	c	r	C	R
04	d	s	D	S	d	s	D	S	d	s	D	S
05	e	t	E	T	e	t	E	T	e	t	E	T
06	f	u	F	U	f	u	F	U	f	u	F	U
07	g	v	G	V	g	v	G	V	g	v	G	V
08	h	x	H	X	h	x	H	X	h	x	H	X
09	j	y	J	Y	j	y	J	Y	j	y	J	Y
10	k	z	K	Z	k	z	K	Z	k	z	K	Z
11	l	2	L	4	l	2	L	4	l	2	L	4
12	n	3	N	5	n	3	N	5	n	3	N	5


1) New Marking Layout for SC75, implemented at October 2005.

chanhvinh.com


Package Outline



Foot Print




Marking Layout (Example)




Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel



chanhvinh.com


Package Outline



Note: Mold flash, protrusions or gate burrs of 0,2 mm max. per side are not included


SOT143-PO V09

Foot Print




SOT143-FPR V09

Marking Layout (Example)



Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel




SOT143-TP

chanhvinh.com

Package Outline






1) Lead width can be 0.6 max. in dambar area


SOT23-PO V08

Foot Print




SOT23-FPR V08

Marking Layout



Standard Packing


Reel o 180 mm: 3.000 Pieces / Reel
Reel o 330 mm = 10.000 Pieces / Reel




SOT23-TP V02


chanhvinh.com

Package Outline






Foot Print




Marking Layout (Example)



Standard Packing


Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel




chanhvinh.com

Package Outline






Foot Print




Marking Layout (Example)




Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel




chanhvinh.com

Package Outline




Foot Print



Marking Layout (Example)


Small variations in positioning of
Date code, Type code and Manufacture are possible.



Standard Packing


Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel

For symmetric types no defined Pin 1 orientation in reel.



chanhvinh.com


Package Outline




1) Dimension applies to plated terminal

Foot Print

For board assembly information please refer to Infineon website "Packages"




Marking Layout (Example)



Standard Packing

Reel ø180 mm = 15.000 Pieces/Reel
Reel ø330 mm = 50.000 Pieces/Reel (optional)



chanhvinh.com

Edition 2009-11-16

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2009 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (<www.infineon.com>).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.