

chanhvinh.com

Silicon Schottky Diode

- For mixer applications in VHF/UHF range
- For high-speed switching application
- Pb-free (RoHS compliant) package[1)]
- Qualified according AEC Q101



BAT17 **BAT17-04** **BAT17-04W** **BAT17-05** **BAT17-05W** **BAT17-06W** **BAT17-07**



ESD (**E**lectro**s**tatic **d**ischarge) sensitive device, observe handling precaution!

Type	Package	Configuration	L_S(nH)	Marking
BAT17	SOT23	single	1.8	53s
BAT17-04	SOT23	series	1.8	54s
BAT17-04W	SOT323	series	1.4	54s
BAT17-05	SOT23	common cathode	1.8	55s
BAT17-05W	SOT323	common cathode	1.4	55s
BAT17-06W	SOT323	common anode	1.4	56s
BAT17-07	SOT143	parallel pair	2	57s

[1]Pb-containing package may be available upon special request

chanhvinh.com

Maximum Ratings at T_A = 25°C, unless otherwise specified

Parameter	Symbol	Value	Unit
Diode reverse voltage	V_R	4	V
Forward current	I_F	130	mA
Total power dissipation	P_{tot}		mW
BAT17, $T_S \leq 77$°C		150	
BAT17-04, $T_S \leq 61$°C		150	
BAT17-05, $T_S \leq 46$°C		150	
BAT17-04W, -05W, -6W, $T_S \leq 92$ °C		150	
BAT17-07, $T_S \leq 60$ °C		150	
Junction temperature	T_j	150	°C
Operating temperature range	T_{op}	-55 ... 125	
Storage temperature	T_{stg}	-55 ... 150	

Thermal Resistance

Parameter	Symbol	Value	Unit
Junction - soldering point[1)]	R_{thJS}		K/W
BAT17		≤ 490	
BAT17-04, BAT17-07		≤ 590	
BAT17-05		≤ 690	
BAT17-04W, BAT17-05W, BAT17-06W		≤ 390	

[1]For calculation of R_{thJA} please refer to Application Note Thermal Resistance

chanhvinh.com

Electrical Characteristics at T_A = 25°C, unless otherwise specified


Parameter	Symbol	Values			Unit
		min.	typ.	max.	
DC Characteristics					
Breakdown voltage $I_{(BR)}$ = 10 µA	$V_{(BR)}$	4	-	-	V
Reverse current	I_R				µA
V_R = 3 V		-	-	0.25	
V_R = 4 V		-	-	10	
V_R = 3 V, T_A = 60 °C		-	-	1.25	
Forward voltage	V_F				mV
I_F = 0.1 mA		200	275	350	
I_F = 1 mA		250	340	450	
I_F = 10 mA		350	425	600	
Forward voltage matching[1)] I_F = 1 mA	ΔV_F	-	-	20	
AC Characteristics					
Diode capacitance V_R = 0 , f = 1 MHz	C_T	0.4	0.55	0.75	pF
Differential forward resistance I_F = 5 mA, f = 10 kHz	R_F	-	8	15	Ω

[1] ΔV_F is the difference between lowest and highest V_F in multiple diode component.

chanhvinh.com


Diode capacitance $C_T = f(V_R)$

f = 1MHz




Forward resistance $r_f = f(I_F)$

f = 10kHz




Reverse current $I_R = f(V_R)$

T_A = Parameter



Forward current $I_F = f(V_F)$


T_A = Parameter



chanhvinh.com


Forward current $I_F = f(T_S)$

BAT17




Forward current $I_F = f(T_S)$

BAT17-04, BAT17-07




Forward current $I_F = f(T_S)$

BAT17-05




chanhvinh.com


Package Outline



Foot Print




Marking Layout (Example)




Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel




chanhvinh.com

Package Outline




1) Lead width can be 0.6 max. in dambar area

Foot Print




Marking Layout (Example)



Standard Packing


Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel




chanhvinh.com

Package Outline






Foot Print




Marking Layout (Example)



Standard Packing

Reel ø180 mm = 3.000 Pieces/Reel
Reel ø330 mm = 10.000 Pieces/Reel



chanhvinh.com

Edition 2006-02-01
Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2007.
All Rights Reserved.

Attention please!

The information given in this dokument shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.
Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.
Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.