chanhvinh.com

BCR431U Low Voltage Drop LED Driver IC

Features

- Supply voltage from 6 V to 42 V
- Controls up to 36.5 mA LED current
- Max. 200 mV saturation voltage at 32.8 mA
- LED current precision ±10 %
- Smart over temperature protection function

Advantages with respect to discrete solutions

- Low BOM count
- Lower assembly cost
- Smaller form factor
- Higher reliability due to less parts and soldering joints

Potential Applications

- LED strips
- LED displays and channel letters
- Architectural and landscape lighting
- Retail lighting

Product Validation

- Qualified for industrial applications according to the relevant tests of JEDEC47/20/22

Product Name	Package
BCR431U	PG-SOT23-6

Description

BCR431U is a linear LED driver IC in a small PG-SOT23-6 package regulating the LED current in standalone operation without any external power transistor. The IC supply voltage range is from 6 V up to 42 V. The LED current level can be adjusted up to 36.5 mA connecting a high ohmic resistor Rset to pin RS. The maximum voltage drop at the integrated LED driver stage is 200 mV at 32.8 mA improving the overall system efficiency and providing extra voltage headroom to compensate for tolerances of LED forward voltage or supply voltage. The smart over temperature protection function reduces the LED current when junction temperature of BCR431U is very high.

chanhvinh.com

Table of contents

Features 1

Advantages with respect to discrete solutions 1

Potential Applications 1

Description 1

Table of contents 2

1 Application circuit 3

2 Pin configuration 3

3 Functional description 4

4 Electrical characteristics and parameters 6

5 Package dimensions 8

6 References 10

Revision history 10

Disclaimer 11

chanhvinh.com

1 Application circuit




Figure 1 Typical Application Circuit of BCR431U

* A ceramic capacitor of 10nF in parallel to LED pin needed for a long line to compensate parasitic line inductance.

2 Pin configuration

Pin No.	Pin Name	Pin Type	Function
1	N.C.	-	Not connected
2	GND	GND	IC ground & thermal connection to heat spreader on PCB
3	RS	Output	Connection of Rset resistor
4	VS	Input	Supply voltage
5	N.C.	-	Not connected
6	LED	Input	Driver pin to control the LED current




Figure 2 Pinout BCR431U

chanhvinh.com

3 Functional description

LED current configuration

The LED current is configured by the external resistor Rset at pin RS. The current flowing into pin LED is proportional to the current flowing out of pin RS by a ratio of about 760:1. Therefore, the LED current depends on the value of Rset.




Figure 3 Relation between I_{LED} and R_{set}

chanhvinh.com

Functional description

Smart over temperature protection function

BCR431U reduces the LED current with increasing junction temperature by reducing the voltage at pin RS. The reduced voltage of pin RS drives less current through the external resistor Rset, causing the current into pin LED to reduce. The LED current is never turned off fully.




Figure 4 Relative reduction of LED current versus junction temperature of BCR431U

Maximum Permitted Power Dissipation

To avoid damage of the IC the power dissipation of BCR431U must be reduced with increasing ambient temperature according to ***Figure 5***.




Figure 5 Maximum permitted total power dissipation of BCR431U on a JESD 51-7 board

chanhvinh.com

4 Electrical characteristics and parameters

Table 1 Maximum Ratings at T_A = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit	Note or test condition
		Min.	Typ.	Max.		
Junction temperature	T_J	-40	-	150	°C	
Supply voltage	V_S	0	-	45	V	
Voltage at LED pin	V_{LED}	0	-	15	V	
Driver LED current	I_{LED}	0	-	42	mA	
RS maximum voltage	V_{RS}	0	-	5	V	
RS output current	I_{RS}	0	-	60	µA	
Power dissipation	P_{tot}	-	-	600	mW	JESD 51-7 test board, $T_A \leq 36$ °C
ESD robustness	$V_{ESD,HBM}$	6	-	-	kV	HBM according to JEDEC JS-001

***Attention**: Stresses above the max. values listed here may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Maximum ratings are absolute ratings; exceeding only one of these values may cause irreversible damage to the integrated circuit. These values are not tested, only production test.*

Table 2 Thermal Resistance at T_A = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit	Note or Test Condition
		Min.	Typ.	Max.		
Thermal resistance junction to ambient	$R_{thJA,1s0p,0}$	-	-	288	K/W	JEDEC 1s0p (JESD 51-3) footprint w/o extra cooling area
	$R_{thJA,1s0p,300}$	-	-	182	K/W	JEDEC 1s0p (JESD 51-3) with 300 mm^2 cooling area connected to GND pin
	$R_{thJA,2s2p}$	-	-	190	K/W	JEDEC 2s2p (JESD 51-7)
Thermal resistance junction to soldering pint	R_{thJS}	-	70	-	K/W	

Table 3 Electrical Characteristics at T_A = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit	Note or Test Condition
		Min.	Typ.	Max.		
Supply voltage	V_S	6	-	42	V	Operational voltage range

chanhvinh.com

Electrical characteristics and parameters

Table 3 Electrical Characteristics at T_A = 25 °C, unless otherwise specified (continued)

Parameter	Symbol	Values			Unit	Note or Test Condition
		Min.	Typ.	Max.		
Supply current	I_S	-	-	1.8	mA	V_{LED} = 1 V, R_{set} = 24.9 kΩ, V_S = 6 V
		-	-	2		V_{LED} = 1 V, R_{set} = 24.9 kΩ, V_S = 42 V
Driver LED capability	I_{LED}	32.8	-	-	mA	V_{LED} = 1 V, R_{set} = 24.9 kΩ
Driver LED current by R_{set}	I_{LED}	-	8	-	mA	R_{set} = 114 kΩ, V_{LED} =1 V, V_S = 24 V
		-	10	-		R_{set} = 90.9 kΩ, V_{LED} = 1 V, V_S = 24 V
		-	15	-		R_{set} = 60.4 kΩ, V_{LED} = 1 V, V_S = 24 V
		-	20	-		R_{set} = 45.3 kΩ, V_{LED} = 1 V, V_S = 24 V
		-	24	-		R_{set} = 36.5 kΩ, V_{LED} = 1 V, V_S = 24 V
		-	36.5	-		R_{set} = 24.9 kΩ, V_{LED} = 1 V, V_S = 24 V
Driver saturation voltage	$V_{LED,sat}$	-	-	200	mV	I_{LED} = 32.8 mA, R_{set} = 24.9 kΩ, V_S = 6 V
Driver saturation voltage	$V_{LED,sat}$	-	-	200	mV	I_{LED} = 32.8 mA, R_{set} = 24.9 kΩ, V_S = 24 V
RS pin voltage	V_{RS}	1.172	1.197	1.22	V	R_{set} = 45.3 kΩ, V_{LED} = 1 V, V_S = 24 V
V_{LED} pin leakage current	$I_{VLED,leak}$	-	-	350	µA	R_{set} opened, V_{LED} = 15 V, V_S = 42 V

chanhvinh.com

5 Package dimensions




Figure 6 Package outline PG-SOT23-6

chanhvinh.com

Package dimensions




Figure 7 Footprint PG-SOT23-6

chanhvinh.com




Figure 8 Tape & Reel PG-SOT23-6

6 References

Revision history

Document version	Date of release	Description of changes
1.0	2020-03-03	First data sheet release

chanhvinh.com

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2020-03-03

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2020 Infineon Technologies AG

All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference

IFX-jwu1549524732233

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”) .

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer’s compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer’s products and any use of the product of Infineon Technologies in customer’s applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer’s technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies’ products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury