chanhvinh.com

Diode

Rapid Switching Emitter Controlled Diode

IDP15E65D1

Emitter Controlled Diode Rapid 1 Series

Data sheet

Industrial Power Control

chanhvinh.com

Rapid Switching Emitter Controlled Diode

Features:

- 650 V Emitter Controlled technology
- Temperature stable behaviour of key parameters
- Low forward voltage (V_F)
- Ultra fast recovery
- Low reverse recovery charge (Q_{rr})
- Low reverse recovery current (I_{rrm})
- Softness factor >1
- 175 °C junction operating temperature
- Pb-free lead plating; RoHS compliant



Applications:

- AC/DC converters
- Boost diode in PFC stages
- Free wheeling diodes in inverters and motor drives
- General purpose inverters
- Switch mode power supplies



Green

Halogen-Free

RoHS

Key Performance and Package Parameters

Type	V_{rrm}	I_f	V_f, T_{vj}=25°C	T_{vjmax}	Marking	Package
IDP15E65D1	650V	15A	1.35V	175°C	E15ED1	PG-TO220-2-1

chanhvinh.com

Table of Contents

Description 2
Table of Contents 3
Maximum Ratings 4
Thermal Resistance 4
Electrical Characteristics 4
Electrical Characteristics Diagrams 6
Package Drawing 9
Testing Conditions 10
Revision History 11
Disclaimer 11

chanhvinh.com

Maximum Ratings

For optimum lifetime and reliability, Infineon recommends operating conditions that do not exceed 80% of the maximum ratings stated in this datasheet.

Parameter	Symbol	Value	Unit
Repetitive peak reverse voltage	V_{RRM}	650	V
Diode forward current, limited by T_{vjmax} T_C = 25°C T_C = 100°C	I_F	 30.0 15.0	A
Diode pulsed current, t_p limited by T_{vjmax}	I_{Fpuls}	45.0	A
Diode surge non repetitive forward current T_C = 25°C, t_p = 10.0ms, sine halfwave	I_{FSM}	120.0	A
Power dissipation T_C = 25°C	P_{tot}	92.0	W
Operating junction temperature	T_{vj}	-40...+175	°C
Storage temperature	T_{stg}	-55...+150	°C
Soldering temperature, wave soldering 1.6 mm (0.063 in.) from case for 10s		260	°C
Mounting torque, M3 screw Maximum of mounting processes: 3	M	0.6	Nm

Thermal Resistance

Parameter	Symbol	Conditions	Max. Value	Unit
Characteristic				
Diode thermal resistance,[1)] junction - case	$R_{th(j-c)}$		1.64	K/W
Thermal resistance junction - ambient	$R_{th(j-a)}$		62	K/W

Electrical Characteristic, at T_{vj} = 25°C, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Static Characteristic						
Diode forward voltage	V_F	I_F = 15.0A T_{vj} = 25°C T_{vj} = 125°C T_{vj} = 175°C	 - - -	 1.35 1.30 1.26	 1.70 - -	V
Reverse leakage current	I_R	V_R = 650V T_{vj} = 25°C T_{vj} = 175°C	 - -	 - -	 40.0 4000.0	µA

Electrical Characteristic, at T_{vj} = 25°C, unless otherwise specified

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Dynamic Characteristic						
Internal emitter inductance measured 5mm (0.197 in.) from case	L_E		-	7.0	-	nH

[1)] Please be aware that in non standard load conditions, due to high Rth(j-c), Tvj close to Tvjmax can be reached.

chanhvinh.com

Switching Characteristic, Inductive Load

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Diode Characteristic, at T_{vj} = 25°C						
Diode reverse recovery time	t_{rr}	T_{vj} = 25°C, V_R = 400V, I_F = 15.0A, di_F/dt = 1000A/µs	-	71	-	ns
Diode reverse recovery charge	Q_{rr}		-	0.37	-	µC
Diode peak reverse recovery current	I_{rrm}		-	8.6	-	A
Diode peak rate of fall of reverse recovery current during t_b	di_{rr}/dt		-	-810	-	A/µs
Diode reverse recovery time	t_{rr}	T_{vj} = 25°C, V_R = 400V, I_F = 15.0A, di_F/dt = 200A/µs	-	114	-	ns
Diode reverse recovery charge	Q_{rr}		-	0.28	-	µC
Diode peak reverse recovery current	I_{rrm}		-	3.4	-	A
Diode peak rate of fall of reverse recovery current during t_b	di_{rr}/dt		-	-150	-	A/µs

Switching Characteristic, Inductive Load

Parameter	Symbol	Conditions	Value			Unit
			min.	typ.	max.	
Diode Characteristic, at T_{vj} = 175°C/125°C						
Diode reverse recovery time	t_{rr}	T_{vj} = 175°C, V_R = 400V, I_F = 15.0A, di_F/dt = 1000A/µs	-	95	-	ns
Diode reverse recovery charge	Q_{rr}		-	0.91	-	µC
Diode peak reverse recovery current	I_{rrm}		-	14.1	-	A
Diode peak rate of fall of reverse recovery current during t_b	di_{rr}/dt		-	-720	-	A/µs
Diode reverse recovery time	t_{rr}	T_{vj} = 125°C, V_R = 400V, I_F = 15.0A, di_F/dt = 200A/µs	-	146	-	ns
Diode reverse recovery charge	Q_{rr}		-	0.52	-	µC
Diode peak reverse recovery current	I_{rrm}		-	4.7	-	A
Diode peak rate of fall of reverse recovery current during t_b	di_{rr}/dt		-	-230	-	A/µs

chanhvinh.com



Figure 1. **Power dissipation as a function of case temperature**
(T_{vj}≤175°C)



Figure 2. **Diode forward current as a function of case temperature**
(T_{vj}≤175°C)



Figure 3. **Diode transient thermal impedance as a function of pulse width**
($D=t_p/T$)



Figure 4. **Typical reverse recovery time as a function of diode current slope**
(V_R=400V)

chanhvinh.com



Figure 5. **Typical reverse recovery charge as a function of diode current slope**
(V_R=400V)



Figure 6. **Typical peak reverse recovery current as a function of diode current slope**
(V_R=400V)



Figure 7. **Typical diode peak rate of fall of reverse recovery current as a function of diode current slope**
(V_R=400V)



Figure 8. **Typical diode forward current as a function of forward voltage**

chanhvinh.com



Figure 9. **Typical diode forward voltage as a function of junction temperature**

chanhvinh.com

PG-TO220-2-1



DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.50	0.169	0.177
A1	1.17	1.37	0.046	0.054
A2	2.30	2.50	0.091	0.098
b	0.65	0.85	0.026	0.033
b1	1.19	1.69	0.047	0.066
b2	1.19	1.39	0.047	0.055
c	0.40	0.60	0.016	0.024
D	15.35	15.95	0.604	0.628
D1	9.05	9.45	0.356	0.372
D2	12.30	13.05	0.484	0.514
E	9.80	10.20	0.386	0.402
E1	7.25	8.60	0.285	0.339
e1	5.08		0.200	
N	2		2	
H1	5.90	6.90	0.232	0.272
L	13.00	14.00	0.512	0.551
L1	3.30	3.70	0.130	0.146
øP	3.55	3.70	0.140	0.146
Q	2.60	3.00	0.102	0.118

DOCUMENT NO.
Z8B00150560

SCALE
0 2.5 5mm

EUROPEAN PROJECTION

ISSUE DATE
28-10-2008

REVISION
01

chanhvinh.com



Figure A. Definition of switching times



Figure B. Definition of switching losses



Figure C. Definition of diodes switching characteristics



Figure D. Thermal equivalent circuit



Figure E. Dynamic test circuit
Parasitic inductance L_σ,
Parasitic capacitor C_σ,
Relief capacitor C_r
(only for ZVT switching)

chanhvinh.com

Revision History

IDP15E65D1

Revision: 2013-12-16, Rev. 2.2

Previous Revision

Revision	Date	Subjects (major changes since last revision)
1.1	2013-03-13	Preliminary data sheet
2.1	2013-10-21	Final data sheet
2.2	2013-12-16	New Marking Pattern

We Listen to Your Comments
Any information within this document that you feel is wrong, unclear or missing at all ?
Your feedback will help us to continuously improve the quality of this document.
Please send your proposal (including a reference to this document) to: erratum@infineon.com

Published by
Infineon Technologies AG
81726 Munich, Germany
81726 München, Germany
© 2014 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.