
chanhvinh.com


International
IOR Rectifier

IRFHS8242PbF

HEXFET® Power MOSFET

V_{DS}	25	V
$V_{GS\ max}$	±20	V
$R_{DS(on)\ max}$ ($@V_{GS}$ = 10V)	13.0	mΩ
$Q_{g\ (typical)}$ (@ V_{GS} = 4.5V)	4.3	nC
I_D ($@T_{c(Bottom)}$ = 25°C)	8.5②	A





2mm x 2mm PQFN

Applications

- System/Load Switch

Features and Benefits

Features		Resulting Benefits
Low R_{DSon} (≤ 13.0mΩ)		Lower Conduction Losses
Low Thermal Resistance to PCB (≤ 13°C/W)		Enable better thermal dissipation
Low Profile (≤ 1.0 mm)	results in	Increased Power Density
Compatible with Existing Surface Mount Techniques		Easier Manufacturing
RoHS Compliant Containing no Lead, no Bromide and no Halogen		Environmentally Friendlier
MSL1, Industrial Qualification		Increased Reliability

Orderable part number	Package Type	Standard Pack		Note
		Form	Quantity	
IRFHS8242TRPbF	PQFN 2mm x 2mm	Tape and Reel	4000	
~~IRFHS8242TR2PbF~~	~~PQFN 2mm x 2mm~~	~~Tape and Reel~~	~~400~~	EOL notice # 259

Absolute Maximum Ratings

	Parameter	Max.	Units
V_{DS}	Drain-to-Source Voltage	25	V
V_{GS}	Gate-to-Source Voltage	±20	
I_D @ T_A = 25°C	Continuous Drain Current, V_{GS} @ 10V	9.9②	A
I_D @ T_A = 70°C	Continuous Drain Current, V_{GS} @ 10V	8.0	
I_D @ $T_{C(Bottom)}$ = 25°C	Continuous Drain Current, V_{GS} @ 10V	21②	
I_D @ $T_{C(Bottom)}$= 70°C	Continuous Drain Current, V_{GS} @ 10V	17②	
I_D @ $T_{C(Bottom)}$ = 25°C	Continuous Drain Current, V_{GS} @ 10V (Package Limited)	8.5②	
I_{DM}	Pulsed Drain Current ①	84	
P_D @T_A = 25°C	Power Dissipation ④	2.1	W
P_D @T_A = 70°C	Power Dissipation ④	1.3	
	Linear Derating Factor ④	0.02	W/°C
T_J T_{STG}	Operating Junction and Storage Temperature Range	-55 to + 150	°C

Notes ① through ⑥ are on page 2

chanhvinh.com

Static @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	25	—	—	V	V_{GS} = 0V, I_D = 250µA
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temp. Coefficient	—	18	—	mV/°C	Reference to 25°C, I_D = 1mA
$R_{DS(on)}$	Static Drain-to-Source On-Resistance	—	10.0	13.0	mΩ	V_{GS} = 10V, I_D = 8.5A ③②
		—	17.0	21.0		V_{GS} = 4.5V, I_D = 6.8A ③
$V_{GS(th)}$	Gate Threshold Voltage	1.35	1.8	2.35	V	V_{DS} = V_{GS}, I_D = 25µA
$\Delta V_{GS(th)}$	Gate Threshold Voltage Coefficient	—	-6.8	—	mV/°C	
I_{DSS}	Drain-to-Source Leakage Current	—	—	1.0	µA	V_{DS} = 20V, V_{GS} = 0V
		—	—	150		V_{DS} = 20V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Forward Leakage	—	—	100	nA	V_{GS} = 20V
	Gate-to-Source Reverse Leakage	—	—	-100		V_{GS} = -20V
gfs	Forward Transconductance	19	—	—	S	V_{DS} = 10V, I_D = 8.5A②
Q_g	Total Gate Charge ⑥	—	4.3	—	nC	V_{GS} = 4.5V, V_{DS} = 13V, I_D = 8.5A②
Q_g	Total Gate Charge ⑥	—	10.4	—	nC	V_{DS} = 13V
Q_{gs}	Gate-to-Source Charge ⑥	—	1.8	—		V_{GS} = 10V
Q_{gd}	Gate-to-Drain Charge ⑥	—	1.6	—		I_D = 8.5A② (See Fig. 6 & 16)
R_G	Gate Resistance	—	1.9	—	Ω	
$t_{d(on)}$	Turn-On Delay Time	—	6.5	—	ns	V_{DD} = 13V, V_{GS} = 4.5V③
t_r	Rise Time	—	19	—		I_D = 8.5A②
$t_{d(off)}$	Turn-Off Delay Time	—	5.4	—		R_G=1.8Ω
t_f	Fall Time	—	5.3	—		See Fig.17
C_{iss}	Input Capacitance	—	653	—	pF	V_{GS} = 0V
C_{oss}	Output Capacitance	—	171	—		V_{DS} = 10V
C_{rss}	Reverse Transfer Capacitance	—	78	—		f = 1.0MHz

Diode Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current (Body Diode)	—	—	8.5②	A	MOSFET symbol showing the integral reverse p-n junction diode.
I_{SM}	Pulsed Source Current (Body Diode) ①	—	—	84		
V_{SD}	Diode Forward Voltage	—	—	1.0	V	T_J = 25°C, I_S = 8.5A②, V_{GS} = 0V ③
t_{rr}	Reverse Recovery Time	—	11	17	ns	T_J = 25°C, I_F = 8.5A②, V_{DD} = 13V
Q_{rr}	Reverse Recovery Charge	—	11	17	nC	di/dt = 280 A/µs ③
t_{on}	Forward Turn-On Time	Time is dominated by parasitic Inductance				

Thermal Resistance

	Parameter	Typ.	Max.	Units
$R_{\theta JC}$ (Bottom)	Junction-to-Case ⑤	—	13	°C/W
$R_{\theta JC}$ (Top)	Junction-to-Case ⑤	—	90	
$R_{\theta JA}$	Junction-to-Ambient ④	—	60	
$R_{\theta JA}$	Junction-to-Ambient (<10s) ④	—	42	

Notes:

① Repetitive rating; pulse width limited by max. junction temperature.

② Current limited by package.

③ Pulse width ≤ 400µs; duty cycle ≤ 2%.

④ When mounted on 1 inch square copper board

⑤ R_θ is measured at T_J of approximately 90°C.

⑤ For DESIGN AID ONLY, not subject to production testing.

chanhvinh.com




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance vs. Temperature




Fig 5. Typical Capacitance vs.Drain-to-Source Voltage




Fig 6. Typical Gate Charge vs.Gate-to-Source Voltage

chanhvinh.com




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current vs. Case (Bottom) Temperature




Fig 10. Threshold Voltage vs. Temperature




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case (Bottom)

chanhvinh.com




Fig 12. On-Resistance vs. Gate Voltage




Fig 13. Typical On-Resistance vs. Drain Current





Fig 14. Typical Power vs. Time



* V_{GS} = 5V for Logic Level Devices

Fig 15. Peak Diode Recovery dv/dt Test Circuit for N-Channel HEXFET® Power MOSFETs

chanhvinh.com




Fig 16a. Gate Charge Test Circuit




Fig 16b. Gate Charge Waveform




Fig 17a. Switching Time Test Circuit





Fig 17b. Switching Time Waveforms

chanhvinh.com

PQFN 2x2 Outline Package Details




SYMBOL	COMMON					
	DIMENSIONS MILLIMETER			DIMENSIONS INCH		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.80	0.90	1.00	0.032	0.036	0.040
A1	0.00	0.02	0.05	0.000	0.001	0.002
A2	0.203 REF			0.008 REF		
b	0.25	0.30	0.35	0.010	0.012	0.014
D	1.90	2.00	2.10	0.075	0.079	0.083
D2	0.95	1.00	1.05	0.038	0.040	0.042
E	1.90	2.00	2.10	0.075	0.079	0.083
E2	1.15	1.20	1.25	0.046	0.048	0.050
e	0.65 BSC			0.026 BSC		
L	0.20	0.25	0.30	0.008	0.010	0.012
Kx	0.23 REF			0.010 REF		
Ky	0.785 REF			0.031 REF		

NOTES :

1. DIMENSION AND TOLERANCING CONFORM TO ASME Y14.5M-1994.
2. CONTROLLING DIMENSIONS : MILLIMETER
3. DIMENSION b APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 mm. FROM TERMINAL TIP.

For footprint and stencil design recommendations, please refer to application note AN-1154 at
http://www.irf.com/technical-info/appnotes/an-1154.pdf

PQFN 2x2 Outline Part Marking



Note: For the most current drawing please refer to IR website at: http://www.irf.com/package/

chanhvinh.com

PQFN 2x2 Outline Tape and Reel





TABLE 1: REEL DETAILS

TAPE WIDTH	T	W1	W2	W3	PART NO
8 MM	3 ± 0.50	$8.4^{+1.5}_{-0.0}$	14.4 Max	7.90 Min 10.9 Max	91586-1
12 MM	5 ± 0.50	$12.4^{+2.0}_{-0.0}$	18.4 Max	11.9 Min 15.4 Max	91586-2

Note: Surface resistivity is $\geq 1x10^{5}$ but $< 1x10^{12}$ ohm/sq.



Note: For the most current drawing please refer to IR website at: http://www.irf.com/package/

chanhvinh.com

Qualification information†

Qualification level	Industrial† (per JEDEC JESD47F †† guidelines)	
Moisture Sensitivity Level	PQFN 2mm x 2mm	MSL1 (per JEDEC J-STD-020D††)
RoHS compliant	Yes	

† Qualification standards can be found at International Rectifier's web site http://www.irf.com/product-info/reliability

†† Applicable version of JEDEC standard at the time of product release.

Revision History

Date	Comments
12/17/2013	• Updated ordering information to reflect the End-Of-life (EOL) of the mini-reel option (EOL notice #259) • Updated Qual level from "Consumer" to "Industrial" on page 1, 9 • Updated data sheet with new IR corporate template

International IOR Rectifier

IR WORLD HEADQUARTERS: 101 N. Sepulveda Blvd., El Segundo, California 90245, USA
To contact International Rectifier, please visit http://www.irf.com/whoto-call/

chanhvinh.com

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”) .

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer’s compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer’s products and any use of the product of Infineon Technologies in customer’s applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer’s technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies office (**www.infineon.com**).

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies’ products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.