chanhvinh.com

Quartz Crystal Specification

Part No.: ***LFXTAL062558***

Customer Part:

Description


- 2.0 x 1.2mm SMD crystal in a hermetically sealed ceramic package with an electron beam sealed metal lid. Suitable for real time clock applications.
- Model IQXC-25
- Model Issue number 5



Frequency Parameters

- Frequency 32.7680kHz
- Frequency Tolerance ±10.00ppm
- Tolerance Condition @ 25°C ±5°C
- Operating Temperature Range -40.00 to 85.00°C
- Overtone Order Fundamental
- Ageing ±3ppm max per year @ 25°C
- Frequency Stability Coefficient: -0.03 ±0.01ppm/°C²
- Drive Level: 0.1µW recommended, ±0.5µW max
- Motional Capacitance (C1): 6.5fF typ

Outline (mm)



Electrical Parameters

- Load Capacitance (CL) 9.00pF
- Shunt Capacitance (C0) 1.3pF typ, 1.7pF max
- ESR ****See Technical Notes****


Environmental Parameters

- Storage Temperature Range: –55 to 125°C
- Shock: IEC 60068-2-27: 1000g, 1ms, 3 times in each of the 3 mutually perpendicular planes.
- Vibration: IEC 60068-2-6: 1.5mm amplitude, 10Hz-55Hz, 1min in 3 mutually perpendicular planes for the total of 6 hours (2 hours in each plane).

Manufacturing Details

- Maximum Reflow Temperature: 260°C for 5secs max
- RoHS Terminations Au over Ni over W base
- RoHS Reflow Temp 260°C max for 5secs max

Recommended Solder Pad Layout



Compliance

- RoHS Status (2015/863/EU) Compliant
- REACh Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details

- Tape & reel in accordance with EIA-481
  Quantities below the standard reel size to be supplied on cut tape.

  Standard Pack Quantity: 3,000

Technical Notes

- *ESR 70k Ohms max*

Sales Office Contact Details:

UK: +44 (0)1460 270200


Email: info@iqdfrequencyproducts.com

Web: www.iqdfrequencyproducts.com

chanhvinh.com

Customer Part:

Typical Frequency Stability Characteristics



Sales Office Contact Details:
UK: +44 (0)1460 270200
Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com