chanhvinh.com

cannon

D-Sub Accessories Catalog



ITT

chanhvinh.com

We Connect

When it matters most

For more than a century, ITT Cannon has developed innovative interconnect solutions for the world's harshest environments. With facilities in the United States, Germany, Italy, Mexico, China and Japan, each with its unique strengths, we offer our customers interconnect solutions that are truly Engineered for Life.

In addition to this truly global footprint, we offer highly specialized, segmented industry expertise. We have a proven track record as an industry leader in harsh-environment applications. This has equipped us with the knowledge needed to continue to produce the most resilient, reliable connectors for our customers' most challenging conditions.

Interconnect solutions for the harshest environments.

cannon

The ITT Cannon difference

- Global capabilities & local support
- Proven application expertise
- A century of interconnect leadership
- A committed innovator & business partner

About ITT

ITT is a diversified leading manufacturer of highly engineered critical components and customized technology solutions for the energy, transportation and industrial markets. Building on its heritage of innovation, ITT partners with its customers to deliver enduring solutions to the key industries that underpin our modern way of life. Founded in 1920, ITT is headquartered in Stamford, Connecticut, with employees in more than 35 countries and sales in a total of approximately 125 countries. For more information, visit itt.com.



chanhvinh.com

cannon















Our connector portfolio remains the most extensive in the industry.

Offering a reliable and cost effective range of interconnect solutions.

ITT


chanhvinh.com

Introduction to D-Sub Accessories

Originally designed & patented by Cannon engineers for use on commercial & military aviation systems, D-Sub Connectors were manufactured as a smaller, lightweight alternative to many of the large, heavier circular electronic plugs of the time. This small but robust rectangular interconnect solution was quickly adopted across a number of applications and industries, and the Cannon D-Sub soon became the first multi-purpose connector of its kind.

Today, Cannon offers an array of commercial or military grade D-Sub styles, sizes, configurations and accessories.

- EMI Shielded, Metal or Plastic Backshells
- Straight or Angled Exit
- One –Piece Snap Together or Locking Backshells
- Locking Hardware
- Guide Pin Plates
- Interfacial Seals
- Dust Camps



chanhvinh.com

Table of contents

We Connect when it matters most 2
Introduction to D-Sub Accessories 4
Accessory Selection Guide 6
Aluminum Metal Backshell
- Aluminum D-Sub Backshell Ordering Guide 7
- Backshell Drawings for Mounting Hardware Code 0-7 ... 8
- Backshell Drawings for Mounting Hardware Code 8 8
- Closure Screw Kits 9
- Mounting Hardware For Hardware Code 0-7 9

Zinc Metal Backshell
- Die Cast Zinc, EMI Shielded Straight Exit 10
- Zinc Metal Backshell Straight Exit 11
- Zinc Metal Backshell 45° Exit 12
- Clamps 13-14

Plastic Backshell
- Snap-Together Metalized Plastic, EMI Shielded 15
- Locking Hardware for Snap-Together Plastic Backshell 16
- Low Cost Metalized Plastic, Straight Exit 16
- Snap-Together Universal 17
- One-Piece Snap-Together 17
- One-Piece Straight Exit 18
- One-Piece Plastic, 90° Exit 18

Locking Hardware
- Screw Lock Assemblies 19-20
- Slide Lock Assemblies 21
- Spring Latch Assemblies 22
- Jackscrew/Jackpot Assemblies 23

Guide Pin Plate
- Female Guide Pin Plate 24
- Male Guide Pin Plate 25

Connector Saver
- High Reliability Connector Saver 26

Miscellaneous
- Polarizing Plates 27
- Right Angle Brackets 27
- Wire Hole Fillers 27
- Dust Cap 28
- Interfacial Seal 28
- Potting Shell. 28

Part Number Index 29
D-Subminiature Connectors 30
About ITT Cannon 31
Product Safety Warranty 32

chanhvinh.com

D-Sub Accessories Guide for Backshells and Locking Hardware

Backshell Locking Hardware

Backshell Material	Backshell Style	Female Screw Lock see page 19	Male crew Lock see page 18	Sliding Lock Retainer see page 20	Slide Lock Post see page 20	Spring Latch Plate see page 21	Spring Latch see page 21	Jackscrew Assembly see page 22	Jackpost Assembly see page 22	Recessed Jackscrew see page 15	Extended Jackscrew see page 15	Thumbscrew see page 15	Jackpost for In-Line Connections see page 15
EMI Shielded	Snap-Together Metalized Plastic Straight Exit see page 15	—	—	—	—	—	—	—	—	●	●	●	●
EMI Shielded	Snap-Together Metalized Plastic 50° Exit see page 15	—	—	—	—	—	—	—	—	●	●	●	●
EMI Shielded	Die Cast Zinc Metal see page 12	—	▲	—	—	—	—	—	—	—	—	—	—
EMI Shielded Aluminum Metal Backshell	Straight, 45°, 90° Exit see page 7	EMI shielded aluminum metal backshells may be ordered with or without hardware. Please reference page 7 for all hardware options including jackpost, spring latch, spring latch plate, side latch screws, slide latch locking post, rack mount, and tie down straps.											
Zinc Metal Backshell	Metal Backshell 45° Exit see page 10	—	—	—	—	—	—	—	—	—	—	—	—
Zinc Metal Backshell	Deep Straight Clamp see page 13	●	●	●	●	●	—	—	●	—	—	—	—
Zinc Metal Backshell	Round Cable Clamp see page 13	●	●	●	●	●	—	—	●	—	—	—	—
Zinc Metal Backshell	Short Straight Clamp see page 14	●	●	●	●	●	—	—	●	—	—	—	—
Zinc Metal Backshell	90° Entry see page 14	●	●	●	●	●	—	—	—	—	—	—	—
Plastic	Snap-Together Universal see page 17	●	●	—	—	—	—	—	—	—	—	—	—
Plastic	One-Piece Snap-Together see page 17	—	▲	—	—	—	—	—	—	—	—	—	—
Plastic	One-Piece Plastic Straight Exit see page 18	—	—	●	●	●	—	—	—	—	—	—	—
Plastic	One-Piece Plastic 90° Exit see page 18	—	—	●	●	●	—	—	—	—	—	—	—

▲ Supplied with backshell ● Optional compatible locking hardware — Not compatible

chanhvinh.com

Aluminum Metal Backshell

Lightweight, High-Performance Straight, 90°, and 45° Aluminum Backshells with EMI Shielding



ITT Cannon's new aluminum backshell technology meets all harsh-environment performance requirements while providing over 50% weight reduction compared to traditional D-Sub backshells without compromising on Electromagnetic Interference (EMI) Shielding and maximum wire termination space and protection.

Specifications	
Temperature Range	-60 deg. C to 200 deg. C
Material & Finish	
Backshell Material:	A380 die cast Aluminum
Backshell Finish:	Electroless Nickel
Hardware Material	Stainless Steel
Hardware Finish	Passivate

Product Features

- Straight, 45°, and 90° cable exit
- Optimal EMI shielding performance with minimal air gaps
- Innovative, lightweight A380 aluminum construction
- Electroless Nickel Plating
- 360° compression shielding
- Front mounting with #4-40 fillister head screws
- Layout with side mount slots accommodating ty-wrap or #4-40 fillister head screws
- RoHS and REACH Compliant

Aluminum D-Sub Backshell Ordering Guide

	1 - Series	2 - Shell Size	3 - Type	4 - Orientation	5 - Entry Size Code	6 - Mounting Hardware Code
PN Example	**D**	**E**	**BS**	**S**	**09**	**0**

1 - Series	
D	D-Subminiature
2 - Shell Size	
E	Size 9 (MIL-DTL-24308 Size 1)
A	Size 15 (MIL-DTL-24308 Size 2)
B	Size 25 (MIL-DTL-24308 Size 3)
C	Size 37 (MIL-DTL-24308 Size 4)
D	Size 50 (MIL-DTL-24308 Size 5)

3 - Type	
BS	Backshell
4 - Orientation	
S	Straight Exit
A	45 Degree Exit
B	90 Degree Exit (0 Code Only)
5 - Entry Size Code	
09, 12, 15, 17 - See Table Below	

6 - Mounting Hardware Code*	
0	Backshells & Closure Screws Only
1	Jackpost set
2	Spring Latch Set
3	Spring Latch Plate
4	Slide Lock Plate with Screws
5	Slide Lock Locking Posts
6	Tie Down Straps
7	Rack Mount Hardware
8	Backshells with 2 Jackscrews, 2 Clips & Closure Screws


*For additional information or to order hardware separately, please reference next page.

Dimensions shown in mm
Specifications and dimensions subject to change


Dimensions shown in mm
Specifications and dimensions subject to change

chanhvinh.com

Backshell Drawings for Mounting Hardware Code 0-7



Backshell Drawings for Mounting Hardware Code 8



Hardware Code 0		Hardware Code 8		Size Code	Entry Code	Angle	A ± .06	B ±.010	C ±.06	D ±.06	E ±.06	ØF ±.02	Weight (g) Less Hardware*	Tie Down Strap	Screw QTY
Descriptive Part Number	Numerical Part Number	Descriptive Part Number	Numerical Part Number												
DEBSS090	070372-0001	DEBS003S098	070372-0048	E	09	STR	1.23	.984	1.25	.75	.58	.35	10.4	-5	2
DEBSA090	070372-0002	DEBS003A098	070372-0049	E	09	45°	1.23	.984	1.50	.75	.58	.35	12.6	-5	2
DEBSB090	070372-0003	NA		E	09	90°	1.23	.984	0.95	1.33	.58	35	11.4	-5	2
DABSS090	070372-0004	DABS003S098	070372-0050	A	09	STR	1.55	1.312	1.30	1.00	.15	35	11.1	-5	2
DABSA090	070372-0005	DABS003A098	070372-0051	A	09	45°	1.55	1.312	1.80	1.00	.58	.35	17.4	-5	2
DABSB090	070372-0006	NA		A	09	90°	1.55	1.312	1.10	1.65	.58	.35	15	-5	2
DBBSS120	070372-0007	DBBS003S128	070372-0052	B	12	STR	2.10	1.852	1.80	1.48	.58	.35	20.2	-1	2
DBBSA120	070372-0008	DBBS003A128	070372-0053	B	12	45°	2.10	1.852	1.80	1.48	.58	47	21.8	-1	3
DBBSB120	070372-0009	NA		B	12	90°	2.10	1.852	1.20	2.20	.58	.47	18	-1	3
DCBSS150	070372-0010	DCBS003S158	070372-0054	C	15	STR	2.75	2.500	2.00	2.16	.58	.58	29.3	-1	4
DCBSA150	070372-0011	DCBS003A158	070372-0055	C	15	45°	2.75	2.500	2.00	2.16	.58	.58	27.9	-1	3
DCBSB150	070372-0012	NA		C	15	90°	2.75	2.500	1.50	2.84	.58	.58	29.7	-1	3
DDBSS170	070372-0013	DDBS003S178	070372-0056	D	17	STR	2.65	2.406	2.00	2.09	.69	.65	29.9	-1	4
DDBSA170	070372-0014	DDBS003A178	070372-0057	D	17	45°	2.65	2.406	2.00	2.09	.69	.65	27.2	-1	3
DDBSB170	070372-015	NA		D	17	90°	2.65	2.406	1.50	2.75	.69	.65	32.7	-1	3

*Mounting Hardware 8 add 2.3 grams weight as supplied with hardware

chanhvinh.com


Closure Screw Kits

Part Number	Package Quantity
070372-0045	2 Screws
070372-0046	3 Screws
070372-0047	4 Screws

Mounting Hardware For Hardware Code 0-7

Code	Description	Part Number	Shell Size	Material
1	Jackpost Set (2)	D70372-0016	E, A, B, C, D	Stainless Steel
2	Spring Latch Set	D70372-0017	E, A, B, C,	
		D70372-0018	D	
3	Spring Latch Plate	D70372-0019	E, A, B, C,	
		D70372-0020	D	
4	Side Latch With Screws	D70372-0021	E	
		D70372-00122	A	
		D70372-0023	B	
		D70372-0024	C	
		D70372-0025	D	
5	Slide Latch Locking Posts	D70372-0026	E, A, B, C, D	
Attachment Option				
6	Tie Down Strap	D70372-0027	E, A	Nylon
		D70372-0028	B, C, D	
7	Rack Mount Hardware, 4-40, Bushing Only (2)*	D70372-0029	E, A, B, C, D	Aluminum, Nickel Plating

*0.125" long through hole standoff for a 4-40 screw.




Dimensions shown in mm
Specifications and dimensions subject to change

chanhvinh.com

Zinc Metal Backshell

Die Cast Zinc Backshell, Straight Exit, EMI Shielded





Die cast metal backshells reduce EMI/RFI emissions. Die cast metal backshells offer improved shielding in a rugged package.

Product Features


- Improves conformance to FCC DOC #20780 shielding requirements
- No crimp ferrule tooling needed
- Kit consists of 1 front shell, 1 rear shell, 2 screws, 2 hex nuts, 2 mounting screws, 2 end brackets, 1 set of compression inserts

Shell size	Layout	Part Number	A ±0,13 (.005)	B ±0,13 (.005)	C ±0,13 (.005)	D ±0,13 (.005)	øE ±0,13 (.005)	F ±0,13 (.005)
DE	9	980-2000-345	31,12 (1.225)	37,21 (1.465)	15,75 (.620)	15,75 (.620)	10,16 (.400)	24,99 (.984)
DA	15	980-2000-346	39,12 (1.540)	40,64 (1.600)	15,75 (.620)	15,75 (.620)	10,16 (.400)	33,32 (1.312)
DB	25	980-2000-347	53,09 (2.090)	39,37 (1.550)	17,53 (690)	15,75 (.620)	13,34 (.525)	47,17 (1.857)
DC	37	980-2000-348	69,34 (2.730)	45,72 (1.800)	21,95 (.864)	15,75 (.620)	18,44 (.726)	63,50 (2.500)
DD	50	980-2000-349	66,70 (2.626)	45,72 (1.800)	21,95 (.864)	18,54 (.730)	18,44 (.726)	61,11 (2.406)

Specifications	
Attenuation:	-50 dB @ 1000MHz
Temperature Range:	-20° C to 80° C

Materials and Finishes	
Backshell Material:	Zinc
Backshell Finish:	Clear Zinc
Compression Inserts:	PVC
Hardware Material:	Steel
Hardware Finish:	Clear Zinc


Attenuation



Compression inserts (included with die cast zinc metal backshell)


Compression inserts accommodate a wide variety of cable sizes.

9 and 15 Position*




Cable Diameter
4,83/8,89 (.190/.350)

25 Position*



Cable Diameter
4,83/11,68 (.190/.460)

37 and 50 Position*



Cable Diameter
7,62/17,27 (.300/.680)

* Inserts may be supplied mirror image.

	#1		#2		#3		#4		#5		#6	
Position	O.D.	I.D.	O.D.	I.D.	O.D.	I.D.	O.D.	I.D.	O.D.	I.D.	O.D.	I.D.
9,15	12,07 (.475)	8,13 (.320)	9,14 (.360)	8,00 (.315)	9,14 (.360)	6,48 (.255)	9,14 (.360)	7,24 (.285)	9,14 (.360)	5,33 (.210)	-	-
25	15,24 (.600)	11,43 (.450)	11,43 (.450)	10,41 (.410)	11.43 (.450)	9,40 (.370)	11.43 (.450)	7,62 (.300)	11.43 (.450)	5,84 (.230)	-	-
37.50	16,64 (.655)	14,48 (.570)	17,78 (.700)	15,75 (.620)	20,57 (.810)	16,51 (.650)	16,64 (.655)	12,70 (.500)	16,64 (.655)	10,80 (.425)	16,64 (.655)	8,89 (.350)

chanhvinh.com

cannon

Zinc Metal Backshell Straight Exit - D*FM


D*FM metal Backshells for D-Subminiature Connectors offers protection from magnetic and radio interferences to cable assemblies.


RoHS COMPLIANT PART NUMBERS


Product Features

- No crimp ferrule tooling needed
- Material: Zinc, blue chromated
- Unique metal filled plastic cable strain relief guarantees 360° shielding
- RoHS compliant
- -40 - +120°C temperature range
- Corrosion resistant

Size 15







Part Description With #4-40 UNC Jackscew	Part Description With M3 Jackscrew	Shell Size	A	B	C	D	Cable Diameter
DEFME-101	DEFMX-101	Size 9	39,55mm [1.555inch]	31,3mm [1.232inch]	14,6mm [0.575inch]	25,0mm [0.984inch]	4 - 9mm
DAFME-101	DAFMX-101	Size 15	41,7mm [1.642inch]	39,3mm [1.547inch]	14,6mm [0.575inch]	33,3mm [1.311inch]	4 - 9mm
DBFME-101	DBFMX-101	Size 25	49,0mm [1.929inch]	53,5mm [2.106inch]	14,6mm [0.575inch]	47,0mm [1.850inch]	4 - 9mm
DCFME-101	DCFMX-101	Size 37	53,3mm [1.098inch]	69,7mm [2.744inch]	14,6mm [0.575inch]	63,5mm [2.500inch]	4 - 9mm

Kit consists of 1 front shell, 1 rear shell, 4 strain reliefs, 2 mounting crosshead screws, and 2 jack screws.

Assembly instructions Size 9, 15, 25, 37



Use two halves of strain relief (different sizes can be mixed)




Strip cable 18mm and shape cable to two pigtails



Attach the strain relief around the cable



Bend cable shielding back on outside of strain relief




Mount connector and cable into the backshell



Assemble the other half (screwing force: 100-120 Ncm)

Attenuation



Dimensions shown in mm
Specifications and dimensions subject to change

ITT

chanhvinh.com

Zinc Metal Backshell 45° Exit

D*FM metal Backshells for D-Subminiature Connectors offers protection from magnetic and radio interferences to cable assemblies.

RoHS COMPLIANT PART NUMBERS


Product Features


- No crimp ferrule tooling needed
- Material: Zinc, blue chromated
- Unique metal filled plastic cable strain relief guarantees 360° shielding
- RoHS compliant
- -40 - +120°C temperature range
- Corrosion resistant

Size 15



Size 50






Part Description With #4-40 UNC Jackscew	Part Description With M3 Jackscrew	Shell Size	A	B	C	D	Cable Diameter
DEFME-100	DEFMX-100	Size 9*	37,5mm [1.476inch]	35,5mm [1.398inch]	14,6mm [0.575inch]		4 - 9mm
DAFME-100	DEFMX-100	Size 15**	41,5mm [1.634inch]	39,5mm [1.555inch]	14,6mm [0.575inch]	33,3mm [1.311inch]	4 - 9mm
DBFME-100	DBFMX-100	Size 25**	41,5mm [1.634inch]	53,5mm [2.106inch]	14,5mm [0.571inch]	47,0mm [1.850inch]	4 - 9mm
DCFME-100	DCFMX-100	Size 37**	41,5mm [1.634inch]	70,0mm [2.756inch]	14,5mm [0.571inch]	63,5mm [2.500inch]	4 - 9mm
DDFME-100	DDFMX-100	Size 50***	45,0mm [1.772inch]	67,5mm [2.657inch]	17,4mm [0.69inch]	61,0mm [2.402inch]	13-16mm

*Size 9 Backshell: Kit consists of 1 front shell, 1 rear shell, 4 strain reliefs, 2 mounting crosshead screws, 1 jack screw
**Size 15, 25, 37 Backshell: Kit consists of 1 front shell, 1 rear shell, 4 strain reliefs, 2 mounting crosshead screws, 2 jack screws
***Size 50 Backshell: Kit consists of 1 front shell, 1 rear shell, 1 cable clamp, 4 mounting crosshead screws, 2 jack screws

Assembly instructions Size 9, 15, 25, 37



Use two halves of strain relief (different sizes can be mixed)



Strip cable 18mm and shape cable to two pigtails



Attach the strain relief around the cable



Bend cable shielding back on outside of strain relief




Mount connector and cable into the backshell



Assemble the other half (screwing force: 100-120 Ncm)

Attenuation



ITT

Dimensions shown in mm
Specifications and dimensions subject to change

chanhvinh.com

cannon

Zinc Metal Backshell

Metal Backshells provide strain relief.
Various profiles available for different cable routing requirements.


Materials and Finishes	
Backshell Material:	Low Carbon Steel or Brass
Backshell Finish:	Chromate over Cadmium (Mil Spec) or Zinc (RoHS)
Hardware Material:	Steel or brass


Product Features

- Qualified to MIL-Spec M85049

Deep Straight Clamp







- Kit consists of 1 shell, 2 cable clamps (clamps not displayed), 2 screws, 2 hex nuts.


		Mil-Spec Parts (Brass)		Brass
Shell Size	RoHS Compliant Part Number	Mil-Spec Part Number	Part Number	50 µ in. Gold over Copper
DE	DE24657-29	M85049/48-1-6F	DE24657-5	DE24657-16
DA	DA24658-28	M85049/48-1-7F	DA24658-2	DA24658-15
DB	DB24659-27	M85049/48-1-8F	DB24659-2	DB24659-15
DC	DC24660-27	M85049/48-1-9F	DC24660-11	DC24660-16
DD	DD24661-27	M85049/48-1-10F	DD24661-4	DD24661-13


Shell Size	Layout	Part Number	Mil Spec Part Number*	A ±0,38 (.015)	B ±0,572 (.0225)	C ±0,38 (.015)	D max.	E ±0,38 (.015)	F ±0,38 (.015)	G ±0,38 (.015)	H max.
DE	9	DE24657	M85049/48-1-1F	30,56 (1.203)	12,484 (.4915)	24,99 (.984)	14,68 (.578)	9,53 (.375)	9,53 (.375)	19,05 (.750)	31,75 (1.250)
DA	15	DA24658	M85049/48-1-2F	38,89 (1.531)	12,484 (.4915)	33,32 (1.312)	14,68 (.578)	18,11 (.713)	7.93 (.312)	19,05 (.750)	31,75 (1.250)
DB	25	DB24659	M85049/48-1-3F	52,78 (2.078)	12,484 (.4915)	47,04 (1.852)	14,68 (.578)	25,40 (1.000)	7.93 (.312)	25,40 (1.000)	39,70 (1.563)
DC	37	DC24660	M85049/48-1-4F	69,04 (2.718)	12,484 (.4915)	63,50 (2.500)	14,68 (.578)	34,93 (1.375)	7.93 (.312)	25,40 (1.000)	39,70 (1.563)
DD	50	DD24661	M85049/48-1-5F	66,68 (2.625)	15,253 (.6005)	61,11 (2.406)	17,45 (.687)	35,71 (1.406)	10,31 (.406)	28,57 (1.125)	42,88 (1.688)

* Parts ordered with no suffix or "Z" suffix will be substituted with "F" suffix.

Round Cable Clamp







- Kit consists of 1 shell, 2 cable clamps, 2 screws, 2 hex nuts.

		Mil-Spec Parts (Brass)		Brass
Shell Size	RoHS Compliant Part Number	Mil-Spec Part Number	Part Number	50 µ in. Gold over Copper
DE	DE44994-14	M85049/48-2-6F	DE44994-3	DE44994-2
DA	DA20961-26	M85049/48-2-7F	DA20961-3	DA20961-16
DB	DB20962-30	M85049/48-2-8F	DB20962-8	DB20962-18
DC	DC20963-27	M85049/48-2-9F	DC20963-8	DC20963-17
DD	DD20964-32	M85049/48-2-10F	DD20964-8	DD20964-19

Shell Size	Layout	Part Number	Mil Spec Part Number*	A ±0,38 (.015)	B ±0,572 (.0225)	C ±0,38 (.015)	D max.	E ±0,38 (.015)	F ±0,38 (.015)	G ±0,38 (.015)
DE	9	DE44994	M85049/48-2-1F	30,68 (1.208)	12,70 (.500)	24,99 (.984)	10,31 (.406)	16,79 (.661)	3,18 (.125)	26,18 (1.031)
DA	15	DA20961	M85049/48-2-2F	38,89 (1.531)	12,70 (.500)	33,33 (1.312)	10,31 (.406)	24,99 (.984)	3,18 (.125)	26,18 (1.031)
DB	25	DB20962	M85049/48-2-3F	52,78 (2.078)	12,70 (.500)	47,04 (1.852)	15,06 (.593)	38,48 (1.515)	4,75 (.187)	26,98 (1.062)
DC	37	DC20963	M85049/48-2-4F	69,04 (2.718)	12,70 (.500)	63,50 (2.500)	18,23 (.718)	55,14 (2.171)	6,35 (.250)	26,98 (1.062)
DD	50	DD20964	M85049/48-2-5F	66,68 (2.625)	15,47 (.609)	61,11 (2.406)	20,62 (.812)	53,16 (2.093)	7,92 (.312)	26,98 (1.062)

* Parts ordered with no suffix or "Z" suffix will be substituted with "F" suffix.

Dimensions shown in mm
Specifications and dimensions subject to change


ITT

chanhvinh.com

Short Straight Clamp



- Kit consists of 1 shell, 2 or 3 screws, 2 or 3 hex nuts




Shell Size	RoHS Compliant Part Number	Mil-Spec Parts (Brass)		Brass
		Mil-Spec Part Number	Part Number	50 µ in. Gold over Copper
DA	DA19678-212	M85049/48-3-7F	DA19678-38	DA19678-167
DB	DB19678-213	M85049/48-3-8F	DB19678-53	DA19678-168
DC	DC19678-214	M85049/48-3-9F	DC19678-85	DA19678-138
DD	DD19678-216	M85049/48-3-10F	DD19678-55	DA19678-161


Shell Size	Layout	Part Number	Mil Spec Part Number*	No. of Cable Locking Screws Included	A ±0,38 (.015)	B ±0,38 (.015)	C ±0,13 (.005)	E ±0,38 (.015)	F ±0,38 (.015)	G ±0,98 (.035)
DA	15	DA19678-1	M85049/48-3-2F	2	38,88 (1.531)	12,70 (.500)	33,33 (1.312)	7,51 (.296)	7.93 (.312)	16,36 (.644)
DB	25	DB19678-2	M85049/48-3-3F	2	52,78 (2.078)	12,70 (.500))	47,04 (1.852)	7,51 (.296)	20,22 (.796)	16,36 (.644)
DC	37	DC19678-3	M85049/48-3-4F	3	69,04 (2.718)	12,70 (.500)	63,50 (2.500)	7,51 (.296)	17,45 (.687)	16,36 (.644)
DD	50	DD19678-4	M85049/48-3-5F	3	66,68 (2.625)	15,47 (.690)	61,11 (2.406)	9,91 (.390)	17,45 (.687)	17,63 (.694)

* Parts ordered with no suffix or "Z" suffix will be substituted with "F" suffix.

90° Entry



- Kit consists of 1 shell, 1 cable clamp, 1 screw, 1 nut, 2 rivnuts (assembled)



Shell Size	RoHS Compliant Part Number	Mil-Spec Parts (Brass)		Brass
		Mil-Spec Part Number	Part Number	50 µ in. Gold over Copper
DE	DE19977-72	M85049/50-6F	DE19977-20	DE19977-47
DA	DA19977-68	M85049/50-7F	DA19977-6	DE19977-40
DB	DB19977-69	M85049/50-8F	DB19977-17	DE19977-43
DC	DC19977-70	M85049/50-9F	DC19977-18	DE19977-45
DD	DC19977-71	M85049/50-10F	DD19977-19	DE19977-44

Shell Size	Layout	Part Number	Mil Spec Part Number*	A ±0,38 (.015)	B ±0,38 (.015)	C ±0,13 (.005)	E ±0,38 (.015)	F ±0,38 (.015)	G ±0,98 (.035)	H
DE	9	DE19977-5	M85049/50-1F	30,56 (1.203)	18,24 (.718)	24,99 (.984)	11,10 (.437)	11,10 (.437)	11,89 (.468)	7,14 (.281)
DA	15	DA19977-1	M85049/50-2F	38,89 (1.531)	12,70 (.500)	33,33 (1.312)	11,10 (.437)	11,10 (.437)	11,89 (.468)	7,14 (.281)
DB	25	DB19977-2	M85049/50-3F	52,78 (2.078)	12,70 (.500)	47,04 (1.852)	11,10 (.437)	15,88 (.625)	11,89 (.468)	7,14 (.281)
DC	37	DC19977-3	M85049/50-4F	69,04 (2.718)	12,70 (.500)	63,50 (2.500)	11,10 (.437)	20,63 (.812)	11,89 (.468)	7,14 (.281)
DD	50	DD19977-4	M85049/50-5F	66,68 (2.625)	15,47 (.690)	61,11 (2.406)	14,28 (.562)	23,01 (.906)	13,47 (.531)	8,71 (.343)

* Parts ordered with no suffix or "Z" suffix will be substituted with "F" suffix.

chanhvinh.com


Plastic Backshell


Snap-Together Metalized Plastic

Metalized plastic backshells reduce EMI/RFI emissions.
Metalized plastic provides a lightweight solution.
Includes integral strain relieving cable clamp.

Product Features


- Improves conformance to FCC DOC #20780 shielding requirements
- No crimp ferrule tooling needed
- Quick and simple assembly using snap-together design feature
- Non-metalized, non-shielded versions available





Note: Cable grounding tang not available on DE size backshell.

Attenuation




Specifications	
Attenuation:	-49 dB @ 100MHz
Temperature Range:	-20° C to 80° C

Materials and Finishes	
Material:	Thermoplastic, UL 94V-0 rated
Finish:	Nickel over Copper

Straight Exit

RoHS COMPLIANT PART NUMBERS

- Kit consists of 1 front shell, 1 rear shell, 1 cable clamp, 2 screws
- Optional locking hardware sold separately, see page 15




Shell Size	Layout	Computer Cable			Ribbon Cable		A ±0,15 (.006)	B ±0,30 (.012)	C ±0,30 (.012)	D ±0,30 (.120)	E ±0,20 (.008)	øH Max.
		Shielded	Non-Shielded Gray	Non-Shielded Black	Shielded	Non-Shielded Gray						
DE	9	DE121073-154	DE121073-159	DE121073-259	DE121073-164	DE121073-169	24,95 (.982)	30,81 (1.213)	23,70 (.933)	16,00 (.630)	35,99 (1.417)	7,32 (.288A
DA	15	DA121073-150	DA121073-155	DA121073-255	DA121073-160	DA121073-165	33,30 (1.311)	39,09 (1.539)	31,80 (1.252)	16,00 (.630)	42,00 (1.654)	8,31 (.327)
DB	25	DB121073-151	DB121073-156	DB121073-256	DB121073-161	DB121073-166	47,00 (1.850)	53,01 (2.087)	45,01 (1.772)	16,00 (.630)	42,00 (1.654)	10,52 (.414)
DC	37	DC121073-152	DC121073-157	DC121073-257	DC121073-162	DC121073-167	63,45 (2.498)	69,29 (2.728)	60,30 (2.374)	16,00 (.630)	42,00 (1.654)	12,32 (.485)
DD	50	DD121073-153	DD121073-158	DD121073-258	-	-	61,10 (2.410)	66,90 (2.634)	58,30 (2.295)	19,00 (.748)	42,00 (1.654)	13,00 (.512)

50° Exit

RoHS COMPLIANT PART NUMBERS

- Kit consists of 1 front shell, 1 rear shell, 1 cable clamp, 2 screws
- Optional locking hardware sold separately, see page 15




Shell Size	Layout	Shielded Part #	Non-Shielded Part # Gray	B ±0,30 (.012)	C ±0,30 (.012)	D ±0,30 (.012)	E ±0,20 (.008)	Cable Diameter Min.	Cable Diameter Max.
DE	9	DE121073-54	DE121073-59	35,99 (1.417)	22,00 (8.66)	16,00 (.630)	35,99 (1.417)	3,51 (.138)	7,49 (.295)
DA	15	DA121073-50	DA121073-55	44,29 (1.744)	27,31 (1.075)	16,00 (.630)	42,01 (1.654)	6,50 (.256)	8,99 (.354)
DB	25	DB121073-51	DB121073-56	57,99 (2.283)	41,00 (1.614)	16,00 (.630)	42,01 (1.654)	6,50 (.256)	11,00 (.433)
DC	37	DC121073-52	DC121073-57	74,50 (2.933)	57,51 (2.264)	16,00 (.630)	42,01 (1.654)	6,50 (.256)	11,00 (.433)
DD	50	DD121073-53	DD121073-58	72,97 (2.873)	54.99 (2.165)	19,00 (.748)	42,01 (1.654)	8,99 (.354)	13,00 (.512)


Dimensions shown in mm
Specifications and dimensions subject to change

chanhvinh.com


Locking Hardware for Snap-Together Plastic Backshell


Recessed Jackscrew







Extended Jackscrew





Thumbscrew







Materials and Finishes			
Part Number	**Material**	**Finish**	**Quantity Required per Connector**
250-8501-004	Brass	Nickel	2
250-8501-009 (M3) ,250-8501-010 (#4-40)	Brass	Nickel	2
250-8501-013	Brass	Nickel	2

Jackpost for In-Line Connections


Rectangular Nut



Jackpost



Jackpost Assembly




- Assembly consists of 1 rectangular nut, 1 jackpost, 1 # 4-40 lock washer.


Materials and Finishes			
Part Number	**Material**	**Finish**	**Quantity Required per Connector**
D121073-19	Brass	Nickel	2

Straight Exit - Metalized Plastic Low Cost



- Kit consists of 1 front shell, 1 rear shell, 1 cable clamp, 2 screws, screw lock assembly kit





Shell Size	Layout	Part Number	A	B	C	D	ø E	F
DE	9	980-2000-350	30,91 (1.217)	39,29 (1.547)	16,26 (.640)	16,26 (.640)	10,16 (.400)	24,99 (.984)
DA	15	980-2000-351	39,24 (1.545)	38,23 (1.505)	16,26 (.640)	16,26 (.640)	10,16 (.400)	33,32 (1.312
DB	25	980-2000-352	53,09 (2.090)	42,04 (1.655)	18,03 (.710)	16,26 (.640)	13,26 (.522)	47,17 (1.857)
DC	37	980-2000-353	69,44 (2.734)	46,48 (1.830)	23,01 (.906)	16,26 (.640)	18,44 (.726)	63,50 (2.500)
DD	50	980-2000-354	67,18 (2.645)	47,12 (1.855)	23,88 (.940)	19,56 (.770)	18,44 (.726)	61,11 (2.406)

Materials and Finishes: Thermoplastic, UL 94V-0 rated, Nickel plated

ITT


Dimensions shown in mm
Specifications and dimensions subject to change

chanhvinh.com

Snap-Together Universal



RoHS COMPLIANT PART NUMBERS



- 2-piece snap-together design for quick assembly.
- Customer furnishes tie-wrap.


Materials and Finishes	
Material:	Black Thermoplastic, UL 94V-0 rated

Shell Size	Layout	Part Number	øB max.	C ±0,20 (.008)	D ±0,20 (.008)
DE	9	DE115339-20	7,01 (.276)	17,00 (.669)	19,51 (.768)
DA	15	DA115339-21	9,60 (.378)	17,00 (.669)	27,79 (1.094)
DB	25	DB115339-22	11,61 (.457)	17,00 (.669)	41,61 (1.638)
DC	37	DC115339-23	13,00 (.512)	17,00 (.669)	59,99 (2.283)
DD	50	DD115339-24	16,00 (.630)	19,81 (.780)	52,32 (2.060)

Note: Part Numbers above replace the following part number series: DE110963-1 to DD110963-5

One-Piece Snap-Together





- Low cost, mounting hardware included with 2 thumbscrews, 1 cable clamp

Materials and Finishes	
Backshell Material:	Polypropylene
Hardware Material:	Steel
Hardware Finish:	Black Nickel

Shell Size	Layout	Part Number	A	C	ø D max.	E
DE	9	DEBS-9	35,20 (1.386)	24,99 (.984)	5,69 (.224)	27,51 (1.083)
DA	15	DABS-15	43,31 (1.705)	33,33 (1.312)	5,69 (.224)	31,19 (1.228)
DB	25	DBBS-25	57,20 (2.252)	47,04 (1.852)	6,50 (.256)	38,30 (1.508)
DC	37	DCBS-37	72,00 (2.83)	62,00 (2.44)	7,80 (.307)	43,08 (1.69)
DD	50	DDBS-50	73,70 (2.90)	63,70 (2.50)	8,20 (.322)	48,04 (1.89)


Dimensions shown in mm
Specifications and dimensions subject to change


chanhvinh.com

One-Piece Plastic

Straight Exit








- Kit consists of 1 shell, 1 cable clamp, 1 set screw
- Mounting hardware included
- 2 screws #4-24 x 5/16 long self-tapping
- Accommodates spring latches


Materials and Finishes	
Material:	Black Thermoplastic, UL 94V-0 rated
Hardware Material:	Steel
Hardware Finish:	Chromate over Zinc

Shell Size	Layout	Part Number	A ±0,38 (.015)	B ±0,38 (.015)	C ±0,13 (.005)	D ±0,38 (.015)	øE ±0,25 (.010)	F ±0,25 (.010)	G ±0,25 (.010)
DE	9	DE51218	30,94 (1.218)	25,40 (1.000)	24,99 (.984)	12,70 (.500)	7,14 (.281)	—	—
DA	15	DA51210	39,27 (1.546)	25,40 (1.000)	33,33 (1.312)	12,70 (.500)	9,14 (.360)	—	—
DB	25	DB51212	53,16 (2.093)	31,75 (1.250)	47,04 (1.852)	12,70 (.500)	—	12,52 (.493)	9.15 (.360)
DC	37	DC51214	69,44 (2.734)	38,10 (1.500)	63,50 (2.500)	12,70 (.500)	—	17,63 (.694)	9.15 (.360)

90° Exit







- Kit consists of 1 shell, 1 cable clamp, 1 set screw
- Mounting hardware included
- 2 screws #4-24 x 5/16 long self-tapping

Materials and Finishes	
Material:	Black Thermoplastic, UL 94V-0 rated
Hardware Material:	Steel
Hardware Finish:	Chromate over Zinc

Shell Size	Layout	Part Number	A ±0,38 (.015)	B ±0,38 (.015)	C ±0,13 (.005)	D ±0,38 (.015)	øH ±0,25 (.010)	J ±0,25 (.010)	K ±0,25 (.010)
DE	9	DE51219	37,95 (1.494)	25,40 (1.000)	24,99 (.984)	12,70 (.500)	7,14 (.281)	—	—
DA	15	DA51211	46,28 (1.822)	25,40 (1.000)	33,33 (1.312)	12,70 (.500)	9,14 (.360)	—	—
DB	25	DB51213	60,15 (2.368)	31,75 (1.250)	47,04 (1.852)	12,70 (.500)	—	12,52 (.493)	9.15 (.360)
DC	37	DC51215	76,43 (3.009)	38,10 (1.500)	63,50 (2.500)	12,70 (.500)	—	17,63 (.694)	9.15 (.360)
DD	50	DD51217	74,04 (2.915)	38,10 (1.500)	61,11 (2.406)	15,47 (.690)	—	18,64 (.734)	11,89 (.468)

chanhvinh.com


Locking Hardware


Screw Lock Assemblies

Refer to the accessories selection guide on page 6 for use with Cannon backshells. Male or Female RoHS compliant stainless steel and brass versions are available. Please contact factory for more information.

Product Features


- Ensures positive mating
- Provides locking and latching for high vibration applications





Male Screw Lock





- Kits may be ordered with either 1 or 2 screws and clips per part number
- Each connector requires 2 screws and 2 clips each, please order accordingly
- Similar to M24308/25

Materials and Finishes	
Material:	Steel
Finish:	Chromate over Cadmium/Zinc

Shell Size	each P/N Cd	2 each P/N Cd	A ±0,38(.015)	B ±0,2 (.010)	C ±0,13 (.005)	RoHS Compliant P/N each Zn	RoHS Compliant P/N 2 each Zn	Stainless Steel P/N each	Stainless Steel Allen Head P/N each
DE, DA, DB, DC	D20419	D20419-119	14,10 (.555)	6,35 (.250)	1,22 (.048)	D20419-211	D20419-218	D20419-14	D20419-95
DE, DA, DB, DC	D20419-18	D20419-121	14,10 (.555)	7,14 (.281)	1,70 (.067)	D20419-212	D20419-219	D20419-38	D20419-97
DE, DA, DB, DC	D20419-21	D20419-122	14,10 (.555)	7,14 (.281)	2,34 (.092)	D20419-213	D20419-220	-	-
DE, DA, DB, DC	D20419-104	D20419-216	14,10 (.555)	7,92 (.312)	2,34 (.092)	D20419-214	D20419-221	-	-
DD	D20420	D20420-097	16,66 (.656)	6,35 (.250)	1,22 (.048)	D20420-157	D20420-163	D20420-21	D20420-81
DD	D20420-13	D20420-099	16,66 (.656)	7,14 (.281)	1,70 (.067)	D20420-158	D20420-164	D20420-136	D20420-83
DD	D20420-15	D20420-100	16,66 (.656)	7,14 (.281)	2,34 (.092)	D20420-159	D20420-165	D20420-70	-
DD	D20420-86	D20420-162	16,66 (.656)	7,92 (.312)	2,34 (.092)	D20420-160	D20420-166	-	-


Dimensions shown in mm
Specifications and dimensions subject to change

chanhvinh.com


Female Screw Lock



Front Panel Mount



Rear Panel Mount




- Each assembly consists of 1 nut, 3 washers, 1 lock washer, 1 hex nut.
- Assemblies can be ordered 1 each or a Kit of 2 each. Each connector requires 2 assemblies each.
- Qualified supplier of M24308/26 female screw locks.


Materials and Finishes	
Material:	Steel
Finish:	Chromate over Cadmium (Mil Spec) or Zinc (RoHS)

NOTE: (1) A 6 inch/pound (female) and 4 inch/pound (male) maximum torque during assembly is recommended on steel screw lock assemblies. (2) A third flat washer is supplied for front panel mounting of tab shell connectors.

Yellow Chromate over cadmium each	Over Cadmium Kit of 2 each	Yellow Chromate over zinc each	RoHS Compliant Part Number	A ± 0,38 (.015)	Mil-Spec Part Number Ref	Stainless Steel Part Number
D20418-145	D20418-82	D20418-128	D20418-134	7,92 (.312)	M24308/26-1	D20418-14
D20418-50	D20418-131	-	D20418-135	12,70 (.500)	-	D20418-102
D20418-147	D20418-83	D20418-129	D20418-136	15,88 (.625)	M24308/26-2	D20418-77
D20418-74	D20418-132	-	D20418-137	19,05 (.750)	-	-

Screw Locks for Connectors with Integral Threaded Inserts






- Kit consists of 1 jackpost, 1 lock washer.
- Order 2 per connector.

	Thread Type	
Part Number	THD A	THD B
D121073-39	# 4-40 UNC-2B	# 4-40 UNC-2A
D112041 *	# 4-40 UNC-2B	# 4-40 UNC-2A
D121073-42	M3	M3

Loose Spacer

	Dim A
Part Number: 253-0343-000 (D*M Style)	5.84 ± .08 (.230 ± .003)
Part Number: 253-0343-011 (D*MA Style)	9.40 ± .13 (.370 ± .005)
Part Number: 253-0343-016 (D*MA Style) St. Stl.	9,40 +/- 0,13 (.370 +/- .005)

Materials and Finishes	
Material:	Aluminum
Finish:	Chromate over Cadmium



RoHS compliant stainless steel and brass versions are available, please contact factory for more information.

chanhvinh.com


cannon

Slide Lock Assemblies

ITT offers the largest variety of locking and latching hardware. Refer to the accessories selection guide on page 6 for use with Cannon backshells.

Product Features


- Ensures positive mating
- Provides locking and latching for high vibration applications



Sliding Lock Retainer Assembly



RoHS COMPLIANT PART NUMBERS



- Kit consists of 1 sliding lock plate, 2 mounting screws, 2 lock washer, 2 hex nuts
- Order 1 kit per connector

Descriptions	Material	Finish/Treatment
Sliding Lock Plate	Stainless Steel	Passivated
Screw, Mounting	Steel	Trivalent Chromate over Zinc
Washer Lock	Steel	
Nut, Hex	Steel	

Shell Size	Layout	Part Number	A ± 0,38 (.015)	B ± 0,38 (.015)	C ± 0,13 (.005)
DE	9	DE51224-1	35,05 (1.380)	12,70 (.500)	25,00 (.984)
DA	15	DA51220-1	43,70 (1.720)	12,70 (.500)	33,32 (1.312)
DB	25	DB51221-1	57,40 (2.260)	12,70 (.500)	47,04 (1.852)
DC	37	DC51222-1	73,86 (2.908)	12,70 (.500)	63,50 (2.500)
DD	50	DD51223-1	71,47 (2.814)	15,47 (.609)	61,11 (2.406)


Slide Lock Post Assemblies



RoHS COMPLIANT PART NUMBERS

- Consists of 1 post, 2 washers, 1 lock washer, and 1 hex nut.[1]
- Order 2 per connector.[2]

Part Number:		
Each[1,2]	Kit of 2 each	
D53018*	D53018-11*	Material: Steel, Finish: Chromate over Cadmium
D53018-14	D53018-20	Material: Stainless Steel, Finish: Passivated
P/N D53018-21	D53018-22	Material: Steel, Finish: Chromate over Zinc



NOTE: When rear-mounting connector to a 1/16" panel, delete the second spacer washer.

* Not RoHS Compliant.

Dimensions shown in mm
Specifications and dimensions subject to change

ITT

chanhvinh.com


Spring Latch Assemblies

Refer to the accessories selection guide on page 6 for use with Cannon backshells.


Product Features

- Low Cost
- Minimizes field connection time
- Positive lock between connectors
- Packaged 2 kits per bag

Unlocked




Locked





Materials and Finishes	
Material:	Stainless Steel
Finish:	Passivated

Spring Latch Plate Assembly

RoHS COMPLIANT PART NUMBERS









- Kit consists of 1 plate, 1 screw, 1 lock washer,1 hex nut.
- Order 2 kits per connector.


Shell Size	Layout	Part Number	A ± 0,38 (.015)	B ± 0,38 (.015)	Part Number Kit of 2 each
DE, DA, DB, DC	9,15, 25, 37	D110278	12,42 (.489)	14,35 (.565)	D110278-4
DD	50	D110280	15,47 (.609)	17,09 (.673)	D110280-3

Spring Latch Assembly

RoHS COMPLIANT PART NUMBERS







Shell Size	Layout	Part Number	A ± 0,38 (.015)	B ± 0,38 (.015)	C ± 0,51 (.020)	Part Number Kit of 2 each
DE, DA, DB, DC	9,15, 25, 37	D110277	12,42 (.489)	14,35 (.565)	18,59 (.732)	D110277-2
DD	50	D110279	15,47 (.609)	17,09 (.673)	18,59 (.732)	D110279-3

D110277-4 Rear panel mount version also available


- Kit consists of 1 spring, 1 screw, 1 bracket, 1 lock washer, 1 hex nut.
- Order 2 kits per connector. Front panel mounting.

chanhvinh.com

cannon

Jackscrew/Jackpost Assemblies

Refer to the accessories selection guide on pages 6-7 for use with Cannon backshells.




Jackscrew Assembly

RoHS COMPLIANT PART NUMBERS



- Kit consists of 2 studs, 2 heads, 1 tube retaining compound (US only)
- Order one kit per connector

Part Number: D110550	
Materials and Finishes	
Material:	Stainless Steel
Treatment:	Passivated




Jackpost Assembly

RoHS COMPLIANT PART NUMBERS



- Kit consists of 2 posts, 2 hex nuts, 2 lock washer
- Order one kit per connector

Part Number: D110551	
Materials and Finishes	
Material:	Stainless Steel
Treatment:	Passivated



NOTE: Jack post is not compatible with rear-panel mount connectors.

Dimensions shown in mm
Specifications and dimensions subject to change

ITT

chanhvinh.com


Guide Pin Plate


Female



- Useful in blind mate applications.
- Kit consists of 1 plate, 2 screws.
- Guide pin inserts for Size 8 cavities for Combo D® connectors also available. Refer to Combo D catalog.


Materials and Finishes	
Plate and Hardware Material:	Steel
Plate and Hardware Finish:	Chromate over Zinc





Shell Size	Layout	Part Number	A ±0,41 (.016)	B ±0,13 (.005)	C ±0,13 (.005)	D ±0,13 (.005)	E ±0,13 (.005)	F ±0,13 (.005)	G ±0,41 (.016)	H ±0,41 (.016)	J ±0,41 (.016)	K ±0,41 (.016)
DE	9	DE111920	49,61 (1.953)	40,08 (1.578)	25,00 (.986)	18,65 (.734)	15,27 (.601)	9,52 (.375)	25,40 (1.000)	30,58 (1.204)	12,29 (.484)	6,15 (.242)
DA	15	DA22214	57,96 (2.282)	48,41 (1.906)	33,32 (1.312)	22,81 (.898)	19,43 (.765)	9,52 (.375)	25,40 (1.000)	38,91 (1.532)	12,29 (.484)	6,15 (.242)
DB	25	DB22254	71,63 (2.820)	62,13 (2.446)	47,04 (1.852)	29,67 (1.168)	26,29 (1.035)	9,52 (.375)	25,40 (1.000)	51,21 (2.016)	11,91 (.469)	5,94 (.234)
DC	37	DC22071	88,11 (3.469)	78,59 (3.094)	63,50 (2.500)	37,90 (1.492)	34,52 (1.359)	9,52 (.375)	25,40 (1.000)	67,49 (2.657)	11,91 (.469)	5,94 (.234)
DD	50	DD21961	85,72 (3.375)	76,20 (3.000)	61,11 (2.406)	36,50 (1.437)	33,32 (1.312)	11,10 (.437)	28,58 (1.125)	65,10 (2.563)	14,30 (.563)	7,16 (.282)

Recommended Panel Cutout



chanhvinh.com

cannon


Male




RoHS COMPLIANT PART NUMBERS

- Useful in blind mate applications.
- Kit consists of 1 plate, 2 screws, 2 rivets, 2 guide pins, 2 washer
- Guide pin inserts for Size 8 cavities for Combo D® connectors also available. Refer to Combo D catalog.


Materials and Finishes	
Plate and Hardware Material:	Steel
Plate and Hardware Finish:	Chromate over Zinc
Guide Pin Material:	Stainless Steel





Shell Size	Layout	Part Number	A ±0,41 (.016)	B ±0,13 (.005)	C ±0,13 (.005)	D ±0,13 (.005)	E ±0,13 (.005)	F ±0,13 (.005)	G ±0,41 (.016)	H ±0,41 (.016)	J ±0,41 (.016)	K ±0,41 (.016)
DE	9	DE111919	49,61 (1.953)	40,08 (1.578)	33,91 (1.335)	18,65 (.734)	25,40 (1.000)	19,05 (.750)	25,00 (.984)	12,29 (.484)	30,58 (1.204)	6,15 (.242)
DA	15	DA22213	57,96 (2.282)	48,41 (1.906)	42,24 (1.663)	22,81 (.898)	25,40 (1.000)	19,05 (.750)	33.32 (1.312)	12,29 (.484)	38,89 (1.531)	6,15 (.242)
DB	25	DB22255	71,63 (2.820)	62,13 (2.446)	55,96 (2.203)	29,67 (1.168)	25,40 (1.000)	19,05 (.750)	47,04 (1.852)	12,29 (.484)	51,99 (2.047)	6,15 (.242)
DC	37	DC22070	88,11 (3.469)	78,59 (3.094)	72,42 (2.851)	37,90 (1.492)	25,40 (1.000)	19,05 (.750)	63,50 (2.500)	12,29 (.484)	68,25 (2.687)	6,15 (.242)
DD	50	DD21962	85,72 (3.375)	76,20 (3.000)	69,82 (2.749)	36,50 (1.437)	28,58 (1.125)	22,20 (.874)	61,11 (2.406)	15,06 (.593)	66,93 (2.635)	7,52 (.296)

Recommended Panel Cutout



Dimensions shown in mm
Specifications and dimensions subject to change


chanhvinh.com


Connector Saver

High Reliability Connector Saver



Engaging Face, Pin Side





NOTE: Hardware removed for clarity.

Shell Size	Layout	Part Number	A ± 0,40 (.015)	B ± 0,25 (.010)	C ± 0,25 (.010)
DE	9	DEBMAM9PS	30,81 (1.213)	24,99 (.984)	16,92 (.666)
DA	15	DABMAM15PS	39,14 (1.541)	33,32 (1.312)	25.25 (.994)
DB	50	DBBMAM25PS	53,04 (2.088)	47,04 (1.852)	38,96 (1.534)
DC	37	DCBMAM37PS	69,32 (2.729)	63,50 (2.500)	55,42 (2.182)
DD	50	DDBMAM50PS	66,93 (2.635)	61,11 (2.406)	52,81 (2.079)

Specifications	
Temperature:	-55° C to 105° C
Current Rating:	7 A
Dielectric withstanding Voltage:	500 VAC at Sea Level

Materials and Finishes		
Description	**Material**	**Finish**
Shells:	Steel	Yellow Chromate over Zinc
Insulator:	White Thermoplastic, UL 94V-0	—
Contacts:	Copper Alloy	Gold Over Copper
Locking Hardware:	Stainless Steel	Passivated


chanhvinh.com

Miscellaneous

Polarizing Plates

Material: Black plastic, 94-V-O rated

Part Number by Shell Size	A	B
DE115398	1.208 (30.7)	0.629 (16)
DA115398-1	1.535 (39,0)	0.629 (16)
DB115398-2	2.082 (52,9)	0.629 (16)
DC115398-3	2.726 (69,2)	0.629 (16)
DD115398-4	2.630 (66,8)	0.749 (19)



Polarizing Scheme


Polarizing Keys	A	B	C	D	E	F	G	H
Position 1	○	×	×	○	○	×	×	○
Position 2	×	○	○	×	×	○	○	×
Position 3	○	○	×	×	×	×	○	○
Position 4	×	×	○	○	○	○	×	×
Position 5	×	×	○	○	×	×	○	○
Position 6	○	○	×	×	○	○	×	×
Position 7	×	○	×	○	○	×	○	×
Position 8	○	×	○	×	×	○	×	○
Position 9	×	○	×	○	×	○	×	○
Position 10	○	×	○	×	○	×	○	×

○ Cut Key on pin connector × Cut Key on socket connector

Wire Hole Fillers (D*MA Series Only)

Material: Acetal

Part Number	Insert Type
DMA51236-1	#20 Socket
DMA51235-1	#20 Pin
225-1013-000	#22 Pin & Socket



M24308 Qualified Coupling Hardware

ITT Cannon is a qualified supplier of M24308/25 and M24308/26 Coupling Hardware

M24308/25
M24308/25-9Z
M24308/25-10Z
M24308/25-9F
M24308/25-10F
M24308/25-9P

M24308/26
M24308/26-1F
M24308/26-2F
M24308/26-1P
M24308/26-1Z
M24308/26-2Z
M24308/26-2P


Dimensions shown in mm
Specifications and dimensions subject to change

chanhvinh.com

Dust Cap



Dust caps provide protection from moisture and dust for unused I/O ports.



NOTE: C dim. applies at point of maximum Integral interface length.
Drawing shown for Black Anti-static caps. Dimensions shown are reference only.

Product Features

- Dust Caps meet the static decay test requirements of MIL-B- 81705C, Type II.
- Dust Caps have an integral flange for easy application and removal


Materials and Finishes	
Material:	Polyethylene

Black Antistatic (Surface Resistivity <1x10^5 ohm/sq.)	I.D.	A	B	C	D
DE-59-20BA	Socket	20,32 (.800)	11,43 (.450)	16,36 (.644)	7,59 (2.99)
DA-59-20BA	Socket	28,45 (1.120)	11,68 (.460)	24,59 (.968)	7,62 (.300)
DB-59-20BA	Socket	42,42 (1.670)	11,68 (.460)	38,25 (1.506)	7,49 (.295)
DC-59-20BA	Socket	58,93 (2.320)	11,68 (.460)	54,81 (2.158)	7,37 (.290)
DD-59-20BA	Socket	56,90 (2.240)	14,48 (.570)	53,11 (2.091)	10,41 (.410)
DE-60-20BA	Pin	21,84 (.860)	12,95 (5.10)	17,78 (.700)	8,92 (.351)
DA-60-20BA	Pin	30,48 (1.200)	12,95 (.510)	26,52 (1.044)	9,02 (.355)
DB-60-20BA	Pin	44,20 (1.740)	13,46 (.530)	39,60 (1.559)	9,09 (.358)
DC-60-20BA	Pin	60,71 (2.390)	13,46 (.530)	56,90 (2.240)	9,37 (.369)
DD-60-20BA	Pin	58,17 (2.290)	16.00 (.630)	54,28 (2.137)	12.04 (.474)

Interfacial Seal



Interfacial seals provide moisture resistance at the mating interface.



Product Features


- Other Interfacial Seals in the Combo D® layouts are available upon request.

Materials and Finishes	
Material:	Silastic Sheet

Shell Size	Layout	Part Number	A	B
DE	9	DE53750	16,66 (.656)	8,41 (.331)
DA	15	DA53750-1	24,99 (.984)	8,41 (.331)
DB	25	DB53750-2	38,88 1.531)	8,41 (.331)
DC	37	DC53750-3	55,14 (2.171)	8,41 (.331)
DD	50	DD53750-4	52,78 (2.078)	11,18 mm (.440)
DC	21WA4	075-0354-003	55,14 (2.171)	8,41 (.331)
DE	15	273-0333-000	16,66 (.656)	8,41 (.331)
DB	44	273-0335-000	38,88 1.531)	8,41 (.331)
DC	62	273-0336-000	55,14 (2.171)	8,41 (.331)
DD	78	273-0337-000	52,78 (2.078)	11,10 (.437)

Potting Shell

Potting shells are molded with a thin flange 0,76 (.030) to permit the use of D Subminiature locking devices.



Materials and Finishes	
Material:	Nylon
Color:	Natural (white)

Shell Size	Layout	Part Number
DE	9	DE50904-1
DA	15	DA50905-1
DB	25	DB50906-1
DC	37	DC50907-1
DD	50	DD50908-1

chanhvinh.com

Index

Standard RoHS Part #	Part #	Page #
070372-0045	Same	9
070372-0046	Same	9
070372-0047	Same	9
075-0354-003	Same	28
250-8501-004	Same	16
250-8501-009	Same	16
250-8501-010	Same	16
250-8501-013	Same	16
273-0333-000	Same	28
273-0334-000	Same	28
273-0335-000	Same	28
273-0336-000	Same	28
273-0337-000	Same	28
980-2000-345	Same	10
980-2000-346	Same	10
980-2000-347	Same	10
980-2000-348	Same	10
980-2000-350	Same	16
980-2000-351	Same	16
980-2000-352	Same	16
980-2000-353	Same	16
980-2000-354	Same	16
D110277	Same	22
D110278	Same	22
D110279	Same	22
D110280	Same	22
D110550	Same	23
D110551	Same	23
D121073-19	Same	16
D121073-39	Same	20
D121073-42	Same	20
D20418-2	D20418-134	20
D20418-39	D20418-136	20
D20418-50	D20418-135	20
D20418-74	D20418-137	20
D20419	D20419-211	19
D20419-104	D20419-214	19
D20419-18	D20419-212	19
D20419-21	D20419-213	19
D20420	D20420-157	19
D20420-13	D20420-158	19
D20420-15	D20420-159	19
D20420-86	D20420-160	19
D53018	Same	21
D70372-16	Same	9
D70372-17	Same	9
D70372-18	Same	9
D70372-19	Same	9
D70372-20	Same	9
D70372-21	Same	9
D70372-22	Same	9
D70372-23	Same	9
D70372-24	Same	9
D70372-25	Same	9
D70372-26	Same	9
D70372-27	Same	9
D70372-28	Same	9
D70372-29	Same	9
DA115339-21	Same	17
DA115398-1	Same	27
DA121073-150	Same	15
DA121073-50	Same	15
DA19678-1	DA19678-212	14
DA19977-1	DA19977-68	14
DA20961	DA20961-26	13
DA22213	Same	25
DA22214	Same	24
DA24658	DA24658-28	13
DA50905-1	Same	28
DA51210	Same	18
DA51211	Same	18
DA51220-1	Same	21
DA53750-1	Same	28
DA-59-20	Same	28
DA-60-20	Same	28
DABMAM15S	Same	26
DABS-15	Same	17
DABSS090	Same	9
DABSA090	Same	9
DABSB090	Same	9
DB115339-22	Same	17
DB115398-2	Same	27
DB121073-151	Same	15
DB121073-51	Same	15
DB19678-2	DB19678-213	14
DB19977-2	DB19977-69	14
DB20962	DB20962-30	13
DB22254	Same	24
DB22255	Same	23
DB24659	DB24659-27	13
DB50906-1	Same	28
DB51212	Same	18
DB51213	Same	18
DB51221-1	Same	21
DB53750-2	Same	28
DB-59-20	Same	28
DB-60-20	Same	28
DBBMAM25PS	Same	26
DBBS-25	Same	17
DBBSS120	Same	9
DBBSA120	Same	9
DBBSB120	Same	9
DC115339-23	Same	17
DC115398-3	Same	27
DC121073-152	Same	15
DC121073-52	Same	15
DC19678-3	DC19678-214	14
DC19977-3	DC19977-70	14
DC20963	DC20963-27	13
DC22070	Same	25
DC22071	Same	24
DC24660	Same	13
DC50907-1	Same	28
DC51214	Same	18
DC51215	Same	18
DC51222-1	Same	21
DC53750-3	Same	28
DC-59-20	Same	28
DC-60-20	Same	28
DCBMA37PS	Same	28
DCBSS150	Same	9
DCBSA150	Same	9
DCBSB150	Same	9
DD115398-4	Same	27
DD115339-24	Same	17
DD121073-153	Same	15
DD121073-53	Same	15
DD19678-4	Same	14
DD19977-4	Same	14
DD20964	DD20964-32	13
DD21961	Same	24
DD21962	Same	25
DD24661	Same	13
DD50908-1	Same	28
DD51217	Same	18
DD51223-1	Same	21
DD53750-4	Same	28
DD-59-20	Same	28
DD-60-20	Same	28
DDBMAM50PS	Same	26
DDBSS170	Same	9
DDBSA170	Same	9
DDBSB170	Same	9
DE111919	Same	25
DE111920	Same	24
DE115339-20	Same	17
DE115398	Same	27
DE121073-154	Same	15
DE121073-54	Same	15
DE19977-5	DE19977-72	14
DE24657	DE24657-29	13
DE44994	DE44994-14	13
DE50904-1	Same	28
DE51218	Same	18
DE51219	Same	18
DE51224-1	Same	21
DE53750	Same	28
DE-59-20	Same	28
DE-60-20	Same	28
DEBMAM9PS	Same	26
DEBS-9	Same	17
DEBSS090	Same	9
DEBSA090	Same	9
DEBSB090	Same	9
DMA51235-1	Same	27
DMA51236-1	Same	27

chanhvinh.com

About ITT Cannon

ITT is a diversified leading manufacturer of highly engineered critical components and customized technology solutions for the energy, transportation and industrial markets. Building on its heritage of innovation, ITT partners with its customers to deliver enduring solutions to the key industries that underpin our modern way of life. Founded in 1920, ITT is headquartered in White Plains, N.Y., with employees in more than 35 countries and sales in a total of approximately 125 countries. For more information visit itt.com

ITT's Cannon brand offers a product portfolio that remains one of the most extensive in the industry. Continuous investment in technology, research and investment have enabled us to provide new, innovative solutions to markets including:

- **Commercial Aerospace**
- **Military & Defense**
- **Industrial**
- **Medical**

When you specify an ITT Cannon interconnect solution, you can rely on products designed, developed and manufactured to the highest quality and reliability standards. This tradition of excellence is based on ITT's corporate culture of operating its businesses under the principles of Six Sigma. At ITT, Six Sigma is not just a quality philosophy but a complete corporate culture that drives the entire business. Our Value Based Management and Value-Based Product Development systems are two cornerstones that allow for the development of both leadership and product engineering principles.

Six Sigma Manufacturing

ITT Cannon operates manufacturing facilities in the United States, Germany, Italy, Mexico, China and Japan, all of which have particular product area strengths that allow ITT Cannon to offer a truly global presence to our customers. Our facilities are world class and accommodate full vertical integration, utilizing the latest manufacturing technologies including automated and robotic machining centers, Super Market manufacturing cells, Kanban pull systems, and automated electrical, mechanical, and optical test and inspection equipment. The combination of our manufacturing strength and our advanced manufacturing facilities allows ITT to offer products at market driven prices. Our capabilities, especially in robotics, computerized precision tooling, Kaizen Project Management, Six Sigma tools and testing give ITT the most optimized global manufacturing footprint in the interconnect industry.

The Custom Difference

As an industry leader in harsh environment interconnect applications, ITT's world class engineering teams work directly with our customers to design and develop cost-effective solutions for their applications. In many cases we may modify one of our standard designs to ensure a highly reliable solution where timing is critical. When custom connectors are required, we collaborate with clients and partners with a goal to design the most reliable, cost-effective solution possible. Our engineering and product management teams provide a thorough analysis of proposed solutions, ensuring our customers receive the right solution for their program and application needs.

RoHS Compliance Information

ITT has implemented a strict parts control plan for all ITT electronics plants worldwide that allows the Cannon product portfolio to meet the requirements of the European Union Directive 2002/95/EC better known as the Reduction of Hazardous Substances initiative. As appropriate, specific Cannon products may be ordered with an R prefix number which insures our customers will receive RoHS compliant parts for their commercial electronics applications and equipment. Since most RoHS hazardous substances center around specific metal plating and lead solder coatings, ITT's products for RoHS compliance are available in the following plating finishes: electroless nickel, stainless steel, anodize over aluminum and gold plating. It should be noted that gold plating would be recommended as the replacement for tin-lead solder when ordering board mount connectors.

RoHS COMPLIANT PART NUMBERS

chanhvinh.com

D-Subminiature Connectors

Invented by Cannon engineers in 1952 for aircraft radio systems, the D-Subminiature was designed as a smaller, lightweight rectangular alternative to larger, heavier connectors of the time. Today, Cannon continues its legacy of innovation through highly engineered D-Sub connector styles, sizes, configurations and accessories. From rocket launchers and telecommunications, to avionics and high-speed rail, its performance, reliability and versatility have made this Cannon invention one of the most widely used connectors in the world.




Non-Magnetic Series

D*M, D*MM, D*MA with NM, NMB option connectors are used when non magnetic characteristics are required.




D*H

Hermetic Military D connectors are designed to meet environmental conditions of extreme pressure differential.




MIL-DTL-24308[2]

These high reliability D-Sub connectors are the finest quality and are qualified to MIL-DTL-24308.




D*MAM

D*MAM crimp connectors are designed according to MIL-DTL-24308.



D*MM

D*MM straight PCB connectors are designed according to MIL-DTL-24308.



GD*

GD* connectors provide high-density and moisture protection.




2D

2D connectors feature double the contact density in the same insert area.



D*MA

D*MA crimp connectors are designed according to MIL-DTL-24308



D*M

D*M straight PCB connectors are equivalent to MIL-DTL-24308 qualified versions (except for finishes).



Stainless Steel

A broad range of D-Sub connectors are available with stainless steel shells for corrosion resistance.



D*NG

D*NG pressfit connectors provide a low-cost alternative to traditional through hole solder contacts (straight only).



D*SF

Speedy D connectors terminate ribbon cables without stripping and without splicing.



D*U

D*U is a low-cost, crimp type D-Subminiature series.




D*

D* connectors are available for high performance uses according to DIN 41652.



ZD*

ZD* connectors are available for applications where price is the primary driver.



ZD*A

ZD*A high density connectors are available for applications where price is the primary driver.



D*A

D*A crimp connectors are available for applications where price is the primary driver.



Combo-D

Combo-D connectors offer an industry standard shield I/O interconnect, with the flexibility of a customized special.

Dimensions shown in mm
Specifications and dimensions subject to change

chanhvinh.com

PRODUCT SAFETY INFORMATION

THIS NOTE MUST BE READ IN CONJUNCTION WITH THE PRODUCT DATA SHEET/CATALOG. FAILURE TO OBSERVE THE ADVICE IN THIS INFORMATION SHEET AND THE OPERATING CONDITIONS SPECIFIED IN THE PRODUCT DATA SHEET/ CATALOG COULD RESULT IN HAZARDOUS SITUATIONS.

1. MATERIAL CONTENT AND PHYSICAL FORM

Electrical connectors do not usually contain hazardous materials. They contain conducting and non-conducting materials and can be divided into two groups:
a) Printed circuit types and low-cost audio types which employ all plastic insulators and casings;
b) Rugged, Fire Barrier and High Reliability types with metal casings and either natural rubber, synthetic rubber, plastic, or glass insulating materials.
Contact materials vary with type of connector and application and are usually manufactured from either copper, copper alloys, nickel, alumel, chromel or steel. In special applications, other alloys may be used.

2. FIRE CHARACTERISTICS AND ELECTRIC SHOCK HAZARD

There is no fire hazard when the connector is correctly wired and used within the specified parameters. Incorrect wiring or assembly of the connector or careless use of metal tools or conductive fluids, or transit damage to any of the component parts may cause electric shock or burns. Live circuits must not be broken by separating mated connectors as this may cause arcing, ionization and burning. Heat dissipation is greater at maximum resistance in a circuit. Hot spots may occur when resistance is raised locally by damage (e.g., cracked, or deformed contacts, broken strands of wire). Local overheating may also result from the use of the incorrect application tools or from poor quality soldering or slack screw terminals. Overheating may occur if the ratings in the product data sheets/ catalogues are exceeded and can cause breakdown of insulation and hence electric shock. If heating is allowed to continue, it intensifies by further increasing the local resistance through loss of temper of spring contacts, formation of oxide film on contacts and wires and leakage currents through carbonization of insulation and tracking paths. Fire can then result in the presence of combustible materials, and this may release noxious fumes. Overheating may not be visually apparent. Burns may result from touching overheated components.

3. HANDLING

Care must be taken to avoid damage to any component parts of electrical connectors during installation and use. Although there are normally no sharp edges, care must be taken when handling certain components to avoid injury to fingers. Electrical connectors may be damaged in transit to the customers, and damage may result in creation of hazards. Products should therefore be examined prior to installation/use and rejected if found to be damaged.

4. DISPOSAL

Incineration of certain materials may release noxious or even toxic fumes.

5. APPLICATION

Connectors with exposed contacts should not be selected for use on the current supply side of an electrical circuit because an electric shock could result from touching exposed contacts on an unmated connector.

Voltages more than 30 V ac or 42.5 V dc are potentially hazardous, and care should be taken to ensure that such voltages cannot be transmitted in any way to exposed metal parts of the connector body. The connector and wiring should be checked before making live to ensure that there is no damage to metal parts or insulators, no solder blobs, loose strands, conducting lubricants, swarf, or any other undesired conducting particles. Circuit resistance and continuity check should be made to make certain that there are no high resistance joints or spurious conducting paths. Always use the correct application tools as specified in the data sheets/catalogues.
Do not permit untrained personnel to wire, assemble or tamper with connectors. For operation voltage please see appropriate regulations for the applicable region/country.

6. IMPORTANT GENERAL INFORMATION

(i) Air and creepage paths/Operating voltage. The admissible operating voltages depend on the individual applications and the applicable safety regulations (including, but not limited to, region/country-specific regulations). For this reason, the air and creepage path data are only reference values. A reduction of air and creepage paths due to PC board and/or harnessing is normal.
(ii) Temperature. All information given are temperature limits. The operation temperature depends on the individual application.
(iii) Other important information. ITT continuously endeavors to improve its products. Therefore, the products may deviate from the description, technical data and shape as shown in this catalogue and/or data sheets.

7. MISCELLANEOUS

"Cannon" and "Veam" are brands of ITT, Inc. ("ITT"). ITT's connector products are intended to be used in accordance with the specifications in this publication (and any other relevant publications that are applicable to the specific product). Any use or application that deviates from the stated operating specifications is not recommended and may be unsafe. No information and data contained in this publication shall be construed to create any liability on the part of ITT or its successors, assigns, officers, directors, employees, affiliates, and agents, including, but not limited to, any liability for any patent infringements or other rights of third parties which may result from its use. Any new issue of this publication shall automatically invalidate and supersede all previous issues. Reprinting this publication is generally permitted, provided that ITT's prior written consent is obtained, and the source is indicated.

This publication is not to be construed as an offer. It is intended merely as an invitation to make an offer. Product availability, prices, and delivery dates are exclusively subject to ITT's order confirmation form; the same applies to orders based on development samples delivered. Please refer to ITT's Terms and Conditions of Sale located at www.ittcannon.com for the full text of the terms and conditions that apply to ITT's connector products.

Commodities in this catalogue may be controlled for export by the International Traffic in Arms Regulations (ITAR) and Export Administration Regulations (EAR) when specifically designed, modified, or configured for articles controlled by the United States Government.

chanhvinh.com

Notes

chanhvinh.com

chanhvinh.com

Notes

chanhvinh.com

cannon

Amazing things happen when great things connect



chanhvinh.com

Connect with your ITT Cannon representative today or visit us ittcannon.com

Connect with the experts

ITT's Cannon brand is a world leader in the design and manufacture of highly engineered connector solutions for multiple end markets.

Why ITT

ITT is a focused multi-industrial company that designs and manufactures highly engineered critical components and customized technology solutions. ITT's Cannon brand is a leading global manufacturer of connector products serving international customers in aerospace, defense, medical, industrial and transportation end markets. ITT's Connector business, which also includes the Veam and BIW Connector Systems brand, manufactures and supplies a variety of connectors and interconnects that make it possible to transfer data, signal and power in an increasingly connected world.

Connect with your ITT Cannon representative today or visit us at ittcannon.com

Follow us

NORTH AMERICA

USA - Irvine, CA
+1.800.854.3028

MEXICO - Nogales
+52.631.3110050

EUROPE

GERMANY - Weinstadt
+49.7151.699.0

UK - Basingstoke
+44.1256.347400

ITALY - Lainate
+39.02938721

FRANCE
+33.1.60.04.93.93

ASIA PACIFIC

SINGAPORE
+65 66974205

JAPAN - Kanagawa
+81.462.57.2010

KOREA
+82.2.702.7111

CHINA - Shenzhen City
+86.755.2726.7888

HONG KONG
+852.2732.2720

The "ITT Engineered Blocks" symbol, "ITT", "Cannon" and "Veam"are registered trademarks of ITT Inc.
Specification and other data are based on information available at the time of printing, and are subject to change without notice.

© 2026 ITT Inc.
ITT Cannon DSUB Acc. CAT 06/2026